

**CAR
SYSTEM[®]**



AI GENERATED

**EXPERIENCE.
INNOVATION.
QUALITY.**

PRODUCT CATALOGUE **2026/27**

a trademark of
VOSSCHEMIE

CONTACT HEADQUARTERS GERMANY



**CARSYSTEM IS THE FIRST ADDRESS
FOR ALL BODY AND PAINT REPAIR PRODUCTS
IN THE AUTOMOTIVE INDUSTRY**



Marco Massaro
Head of Sales

m.massaro@vosschemie.de
+49 (0) 41 22 / 717-205



Jessica Wedel
Sales Carsystem International

j.wedel@vosschemie.de
+49 (0) 41 22 / 717-108



Gaby Büchner
Sales Carsystem International

g.buechner@vosschemie.de
+49 (0) 41 22 / 717-190



Steven Lück
Head of application engineers
s.lueck@vosschemie.de
+49 (0) 173 / 722 92 18



Stefan Haza
Area Sales Manager Europe
s.haza@vosschemie.de
+49 (0) 162 / 176 21 71

62 partners, 64 countries, more than 2,000 products – global demand has made us one of the leading suppliers of non-paint products for the automotive repair industry.

This market-position is the result of the uncompromising focus on quality and the consequence of almost 70 years of experience in the global market.

As a trademark of VOSSCHEMIE, based in Uetersen / Germany, we benefit from decades of development and production of polyester fillers. Around these core competences we are constantly expanding our wide range of products every year and developing innovative solutions in all categories.

We supply a full system of products you need for a competent and professional automotive body repair. Good if everything comes from one source. Better when all products are precisely verified to each other. The best if certified quality secures constant standards (certified to DIN EN ISO 9001:2015).

EXPERIENCE. INNOVATION. QUALITY.

AI GENERATED



THE COMBINATION OF **EXPERIENCE, INNOVATION AND QUALITY** DEFINES EXCELLENCE IN THE AUTOMOTIVE REPAIR SECTOR.

WHAT DOES THAT MEAN FOR YOU?
OPTIMISE YOUR WORK PROCESS AND MAXIMISE YOUR EFFICIENCY WITH PRODUCTS THAT ARE AS EASY TO USE AS THEY ARE EFFECTIVE.

SAVE TIME AND EFFORT IN EVERY STEP. SAY GOODBYE TO BAD RESULTS AND LOOK FORWARD TO FLAWLESS SURFACES, THAT EMPHASISE YOUR SKILLS AND PROFESSIONALISM.

DONT SETTLE FOR LESS. TAKE YOUR SKILLS TO THE NEXT LEVEL WITH CARSYSTEM AND FEEL THE DIFFERENCE THAT EXPERIENCE, INNOVATION AND QUALITY MAKE.

T

Z

E

T

Z

O

C

006 **ABRASIVES**
ABRASIVES | ACCESSORIES

048 **PUTTIES**

076 **MASKING**

090 **PAINTING**

124 **FINISH**

150 **BONDING &
SEALING**

168 **CLEANING**

182 **PERSONAL SAFETY**

196 **PAINTING SUPPLIES**

ABRASIVES

ABRASIVES & ACCESSORIES

ABRASIVES FOR THE PROFESSIONAL USER IN THE BODYSHOP

Discover our complete range of high-quality paper-, foil- and net sanding products for wet and dry applications. Our mini sanding discs are perfect for removing dust inclusions or small imperfections in the top coat.


The CARSYSTEM abrasives are available in different sizes and grits, so you can find the right sanding disc for any surface in our range. Do you prefer wet sanding? Then we recommend our SW20 sanding water, which extends the lifetime and keeps the sandingpaper moisturized.

For hand and machine sanding, the Carsystem range includes suitable hand sanding blocks, orbital sanders and random orbital sanders from Rupes.



SANDING DISC F.23 CERAMIC

Film abrasive – 150 mm – 25 holes



Art.-No.	Specification	SP	MOQ
159.218	P 80	50	1000
159.219	P 120	50	1000
159.220	P 180	50	1000
159.221	P 240	50	1000
159.222	P 320	50	1000
159.223	P 400	50	1000
159.224	P 500	50	1000
159.225	P 600	50	1000
159.226	P 800	50	1000

DESCRIPTION

- High performance ceramic disc
- Carsystem 25-hole pattern and oval center hole
- Mineral grain mixture with ceramic content
- Strong, non-tearable foil carrier

AREA OF APPLICATION


- Suitable for all sanding jobs from coarse to fine sanding

BENEFITS

- Extremely fast removal thanks to ceramic abrasive grain
- The ceramic sanding grain gives the disc a long life and high durability
- The stearate coating prevents the disc from clogging
- Foil carrier ensures a homogeneous sanding result

SANDING DISC F.19

Film abrasive – 150 mm – 25 holes



Art.-No.	Specification	SP	MOQ
156.046	P 80	50	1000
156.048	P 120	50	1000
156.049	P 150	50	1000
156.050	P 180	50	1000
156.051	P 220	50	1000
156.052	P 240	50	1000
156.054	P 320	50	1000
156.055	P 360	50	1000
156.056	P 400	50	1000
156.057	P 500	50	1000
156.058	P 600	50	1000
156.059	P 800	50	1000

DESCRIPTION

- High performance film-based sanding disc
- Carsystem 25-hole pattern and oval center hole
- Aluminium oxide grain

AREA OF APPLICATION


- Suitable for coarse to fine sanding

BENEFITS

- Extremely high and long lasting cutting power
- Universal high performance sanding disc

SANDING DISC F.19 SOFT

Film abrasive – 152 mm – Multi hole



Art.-No.	Specification	SP	MOQ
156.933	P 320	30	600
156.934	P 400	30	600
156.935	P 500	30	600
156.936	P 600	30	600
156.937	P 800	30	600

DESCRIPTION

- High performance film-based sanding disc with foam back
- Multi hole
- Aluminium oxide grain

AREA OF APPLICATION

- Filler finish
- Blending
- Matting of surfaces

BENEFITS

- Surface structure is sanded evenly
- Extremely high and long lasting cutting power
- Comfortable sanding due to the foam back

SANDING DISC F.19 FINISH

Film abrasive – 152 mm – 15 holes



Art.-No.	Specification	SP	MOQ
156.899	P 1000	50	1000
156.900	P 1200	50	1000
156.901	P 1500	50	1000
156.902	P 2000	50	1000

DESCRIPTION

- High performance film-based sanding disc
- Carsystem 15-hole pattern and oval center hole
- Special coating
- Aluminium oxide grain

AREA OF APPLICATION

- Blending
- Matting of surfaces
- Finish (Removal of imperfections)

BENEFITS


- Extremely fast removing of surface structure and imperfections
- Special coating provides an extra fine and even sanding pattern
- Perfect levelling of the transition zone between new and old paint layers
- Reduces the reworking time in the finishing process

SANDING DISC P.25 CERAMIC

Paper abrasive – 150 mm – 25 holes

NEW

The Carsystem Sanding Disc P.25 Ceramic is a high-performance abrasive disc with Carsystem 25-hole pattern and oval center hole. Its ceramic grain ensures excellent material removal and long durability. The Carsystem hole pattern and stearate coating prevent the disc from clogging - ideal for tasks ranging from coarse to fine sanding. The robust paper backing with hook-and-loop system ensures secure attachment to the sanding pad.



SCAN ME

DESCRIPTION

- High performance ceramic disc
- Carsystem 25-hole pattern and oval center hole
- Mineral grain mixture with ceramic content
- Strong paper abrasive / Velcro® Backing
- Color: Red

AREA OF APPLICATION

- Suitable for all sanding jobs from coarse to fine sanding

BENEFITS

- Very effective stock removal is possible thanks to the ceramic abrasive grain
- Long service life
- High durability
- No fast clogging of the abrasive (CS perforation)
- The stearate coating prevents the disc from clogging

Art.-No.	Specification	SP	MOQ
160.273	P40	50	1000
160.274	P60	50	1000
159.995	P80	50	1000
159.996	P120	50	1000
159.997	P180	50	1000
159.998	P240	50	1000
159.999	P320	50	1000
160.000	P400	50	1000
160.002	P500	50	1000
160.003	P600	50	1000

For industrial and professional use only.

SANDING DISC F.19

Film abrasive – 77 mm



Art.-No.	Specification	SP	MOQ
156.647	P 80	50	1000
156.648	P 120	50	1000
156.649	P 150	50	1000
156.650	P 180	50	1000
156.651	P 220	50	1000
156.652	P 240	50	1000
156.653	P 320	50	1000
156.654	P 400	50	1000
156.655	P 500	50	1000
156.903	P 800	50	1000

DESCRIPTION

- High performance film-based sanding disc
- Aluminium oxide grain

AREA OF APPLICATION

- Suitable for coarse to fine sanding

BENEFITS

- Extremely high and long lasting cutting power
- Universal high performance sanding disc

For industrial and professional use only.

SANDING DISC F.19 FINISH

Film abrasive – 77 mm



Art.-No.	Specification	SP	MOQ
156.904	P 1500	50	1000
156.905	P 2000	50	1000

DESCRIPTION


- High performance film-based sanding disc
- Special coating
- Aluminium oxide grain

AREA OF APPLICATION

- Blending
- Matting of surfaces
- Finish (Removal of imperfections)


BENEFITS

- Extremely fast removal of surface structure and imperfections
- Special coating provides an extra fine and even sanding pattern
- Perfect levelling of the transition zone between new and old paint layers
- Reduces the reworking time in the finishing process



ProFLEX JUPITER

Film abrasive – 152 mm – 15 holes



Art.-No.	Specification	SP	MOQ
154.449	P 600	50	1000
154.450	P 800	50	1000
154.451	P 1000	50	1000
154.452	P 1200	50	1000
154.453	P 1500	50	1000
153.469	P 2000	50	1000
153.470	P 2500	50	1000
153.471	P 3000	50	1000
156.939	P 4000	50	1000

DESCRIPTION

- Ultraflexible soft film disc
- 15 holes
- Aluminium oxide grain

AREA OF APPLICATION

- Dry sanding
- Filler finish
- Blending
- Matting of surfaces
- Finish

BENEFITS

- Ultraflexible basis adapts perfectly to the surface
- Surface structure is treated extremely gentle
- Extremely fine sanding pattern
- Reduces the polishing time

APPLICATION ADVICE

We recommend the use of the ProFLEX Interface Pads.
We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth.

For industrial and professional use only.

ProFLEX JUPITER

Film abrasive – 152 mm



Art.-No.	Specification	SP	MOQ
154.660	P 1500	50	1000
154.661	P 2000	50	1000
154.662	P 2500	50	1000
154.663	P 3000	50	1000

DESCRIPTION

- Ultraflexible soft film disc
- Aluminium oxide grain

AREA OF APPLICATION

- Dry sanding
- Finish

BENEFITS

- Ultraflexible basis adapts perfectly to the surface
- Surface structure is treated extremely gentle
- Extremely fine sanding pattern
- Reduces the polishing time


APPLICATION ADVICE

We recommend the use of the ProFLEX Interface Pads.
We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth.

For industrial and professional use only.

ProFLEX JUPITER SOFT

Film abrasive – 152 mm – Multi hole



Art.-No.	Specification	SP	MOQ
156.509	P 600	15	300
156.510	P 800	15	300
156.511	P 1000	15	300
156.512	P 1200	15	300
156.513	P 1500	15	300
156.514	P 2000	15	300

DESCRIPTION

- Ultraflexible soft film disc with flexible foam back
- Multi hole
- Aluminium oxide grain

AREA OF APPLICATION

- Filler finish
- Blending
- Matting of surfaces
- Suitable for dry and wet sanding
- Manual or machine use

BENEFITS


- Surface structure is treated extremely gentle
- Extremely fine sanding pattern
- Comfortable sanding due to foam back

APPLICATION ADVICE

We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth. We recommend using the CS Sanding Water SW20 for wet sanding.

ProFLEX JUPITER SOFT H₂O

Film abrasive – 152 mm – Multi hole



Art.-No.	Specification	SP	MOQ
156.515	P 2500	15	300
156.516	P 3000	15	300
156.517	P 4000	15	300

DESCRIPTION

- Ultraflexible soft film disc with flexible foam back
- Multi hole
- Aluminium oxide grain

AREA OF APPLICATION

- Finish
- Flattening of removed imperfections
- Wet sanding

BENEFITS

- Surface structure is treated extremely gentle
- Extremely fine sanding pattern reduces the polishing time
- Comfortable sanding due to foam back

APPLICATION ADVICE

We recommend using the ProFLEX Jupiter Soft H₂O in combination with the CS Sanding Water SW20.

ProFLEX JUPITER

Film abrasive – 75 mm



Art.-No.	Specification	SP	MOQ
154.444	P 600	50	1000
154.445	P 800	50	1000
154.446	P 1000	50	1000
154.447	P 1200	50	1000
154.448	P 1500	50	1000
153.466	P 2000	50	1000
153.467	P 2500	50	1000
153.468	P 3000	50	1000
156.946	P 4000	50	1000

DESCRIPTION

- Ultraflexible soft film disc
- Aluminium oxide grain

AREA OF APPLICATION

- Dry sanding
- Filler finish
- Blending
- Matting of surfaces
- Finish

BENEFITS

- Ultraflexible basis adapts perfectly to the surface
- Surface structure is treated extremely gentle
- Extremely fine sanding pattern
- Reduces the polishing time


APPLICATION ADVICE

We recommend the use of the ProFLEX Interface Pads.
We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth.

For industrial and professional use only.

ProFLEX JUPITER SOFT H₂O

Film abrasive – 77 mm – Multihole



Art.-No.	Specification	SP	MOQ
156.524	P 2500	15	300
156.525	P 3000	15	300
156.526	P 4000	15	300

DESCRIPTION

- Ultraflexible soft film disc with flexible foam back
- Multi hole
- Aluminium oxide grain

AREA OF APPLICATION

- Finish
- Flattening of removed imperfections
- Wet sanding

BENEFITS

- Surface structure is treated extremely gentle
- Extremely fine sanding pattern reduces the polishing time
- Comfortable sanding due to foam back

APPLICATION ADVICE

We recommend using the ProFLEX Jupiter Soft H₂O in combination with the CS Sanding Water SW20.

For industrial and professional use only.

ProFLEX HYDRA

Foam abrasive – Ø 75 mm



Art.-No.	Specification	SP	MOQ
159.461	Grit 3000	15	300

DESCRIPTION

- Mineral abrasive grain
- Flexible foam carrier

AREA OF APPLICATION


- Smooth sanding right before polishing
- Fine re-sanding of coarser sanded spots
- Perfect to remove sanding scratches
- Ideally suited for wet sanding

BENEFITS

- Time saving in the subsequent polishing process
- Long abrasive life
- Gentle and homogeneous matting

ProFLEX HYDRA

Foam abrasive – Ø 152 mm



Art.-No.	Specification	SP	MOQ
159.463	Grit 3000	15	300

DESCRIPTION

- Mineral abrasive grain
- Flexible foam carrier

AREA OF APPLICATION


- Smooth sanding right before polishing
- Fine re-sanding of coarser sanded spots
- Perfect to remove sanding scratches
- Ideally suited for wet sanding

BENEFITS

- Time-saving in the subsequent polishing process
- Long abrasive life
- Gentle and homogeneous matting

ProFLEX CALLISTO

Foam abrasive – 150 mm



Art.-No.	Specification	SP	MOQ
158.797	Grit 3000	15	150
159.301	Grit 6000 +	15	150

DESCRIPTION

- Mineral abrasive grit
- Flexible foam backing
- Available grit: 3000 and 6000+

AREA OF APPLICATION

- Smooth sanding right before polishing
- Perfect to remove sanding scratches
- Fine re-sanding of imperfections
- Ideally suited for wet sanding


BENEFITS

- Saves time in the subsequent polishing process
- Long abrasive life
- Gentle and homogeneous matting

For industrial and professional use only.

ProFLEX CALLISTO

Foam abrasive – 77 mm



Art.-No.	Specification	SP	MOQ
158.795	Grit 3000	15	540
159.300	Grit 6000 +	15	540

DESCRIPTION

- Mineral abrasive grit
- Flexible foam backing

AREA OF APPLICATION

- Smooth sanding right before polishing
- Perfect to remove sanding scratches
- Fine re-sanding of imperfections
- Ideally suited for wet sanding

BENEFITS

- Saves time in the subsequent polishing process
- Long abrasive life
- Gentle and homogeneous matting

For industrial and professional use only.

ProFLEX CALLISTO

Foam abrasive – 33 mm



Art.-No.	Specification	SP	MOQ
158.793	Grit 3000	75	2700
159.299	Grit 6000 +	75	2700

DESCRIPTION

- Mineral abrasive grit
- Flexible foam backing

AREA OF APPLICATION

- Smooth sanding right before polishing
- Perfect to remove sanding scratches
- Fine re-sanding of imperfections
- Ideally suited for wet sanding

BENEFITS

- Saves time in the subsequent polishing process
- Long abrasive life
- Gentle and homogeneous matting

TEC LINE PRO FINISH

Net abrasive – 150 mm



Art.-No.	Specification	SP	MOQ
152.983	P 1000	20	120
152.984	P 2000	20	120
153.256	P 3000	20	120

DESCRIPTION

- Net abrasive disc with a Velcro® foam back

AREA OF APPLICATION

- Perfect for blending
- Matting of surfaces
- Finish
- Wet use (recommended)

BENEFITS

- Extremely good dust extraction in dry use
- Almost dust-free sanding
- Perfect water transportation in wet use
- Extremely fine and even sanding pattern

SANDING STRIPS P.25 CERAMIC

Paper abrasive – roll – 70 mm × 12 m



Art.-No.	Specification	SP	MOQ
160.408	P 80	1	20
160.409	P 120	1	20
160.410	P 180	1	20
160.411	P 240	1	20
160.412	P 320	1	20
160.413	P 400	1	20

DESCRIPTION

- High-performance ceramic abrasive strips
- Optimized hole pattern with perforation
- Dimensions per tear-off: 70 × 100 mm
- Mineral grain mixture with ceramic content

AREA OF APPLICATION

- Suitable for all sanding work from coarse to fine sanding

BENEFITS

- Extremely high cutting power
- Long lifetime and high durability thanks to ceramic abrasive grain
- Stearate coating reduces clogging of the abrasive
- Suitable for all standard sanding blocks (70 × 100 mm, 70 × 198 mm, 70 × 300 mm, 70 × 400 mm)

For industrial and professional use only.

SANDING STRIPS F.23 CERAMIC

Film abrasive – Roll – 70 mm × 12 m



Art.-No.	Specification	SP	MOQ
159.227	P 80	1	20
159.228	P 120	1	20
159.229	P 180	1	20
159.230	P 240	1	20
159.231	P 320	1	20
159.232	P 400	1	20
159.234	P 600	1	20
159.235	P 800	1	20

DESCRIPTION

- High performance ceramic strips
- Optimised hole pattern with perforation
- Dimensions per tear: 70 × 100 mm
- Mineral grain mixture with ceramic content
- Strong, non-tearable foil carrier

AREA OF APPLICATION

- Suitable for all sanding work from coarse to fine sanding

BENEFITS

- Extremely high cutting power thanks to ceramic abrasive grain
- Long lifetime and high durability thanks to ceramic abrasive grain
- Stearate coating reduces clogging of the abrasive
- Film backing ensures a homogeneous sanding result
- Suitable for all common sanding blocks (70 × 100 mm, 70 × 198 mm, 70 × 300 mm, 70 × 400 mm)

For industrial and professional use only.

TEC LINE N20

Net sanding strips 70 × 400 mm



Art.-No.	Specification	SP	MOQ
157.438	P 80	50	200
157.439	P 120	50	200
157.440	P 180	50	200
157.441	P 240	50	200
157.442	P 320	50	200
157.443	P 400	50	200

DESCRIPTION

- Net sanding stripes
- Special coating
- Aluminium oxide grain

AREA OF APPLICATION


- Suitable for every sanding application on putties and fillers from coarse to fine sanding

BENEFITS

- Due to the perforation of the individual stripes, the Tec Line N20 can be used on both 70 × 400 mm and 70 × 200 mm tools
- Extremely dust-reduced sanding
- The characteristic of the net provides a very long lifetime

SANDING FLEECE V.19

Sanding Fleece – Roll – 115 mm x 10 m



Art.-No.	Specification	SP	MOQ
156.039	Very fine / red	1	10
156.040	Ultra fine / grey	1	10

DESCRIPTION

- Sanding fleece with three-dimensional structure
- The synthetic resin soaks through the fleece and distributes the sanding grain all over

AREA OF APPLICATION

- Matting of corners, roundings or sharp edges prior to filler or paint application
- Red – very fine: prior to filler application
- Grey – ultra fine: prior to paint application

BENEFITS


- High cutting power
- Suitable for wet and dry sanding
- On a roll for easy cut off in the needed lenght

APPLICATION ADVICE

Perfectly suitable with the Carsystem matting pastes.

SANDING FLEECE V.19

Sanding Fleece – Pad – 115 x 230 mm



Art.-No.	Specification	SP	MOQ
156.041	Very fine / red	25	200
156.042	Ultra fine / grey	25	200

DESCRIPTION

- Sanding fleece with three-dimensional structure
- The synthetic resin soaks through the fleece and distributes the sanding grain all over

AREA OF APPLICATION

- Matting of corners, roundings or sharp edges prior to filler or paint application
- Red – very fine: prior to filler application
- Grey – ultra fine: prior to paint application

BENEFITS

- High cutting power
- Suitable for wet and dry sanding

APPLICATION ADVICE

Perfectly suitable with the Carsystem matting pastes.

SANDING FLEECE V.19

Sanding Fleece – Disc



Art.-No.	Specification	SP	MOQ
156.691	Very fine / red / 80 mm	25	1000
156.690	Ultra fine / grey / 80 mm	25	1000
156.044	Very fine / red / 150 mm	20	160
156.045	Ultra fine / grey / 150 mm	20	160

DESCRIPTION

- Sanding fleece with three-dimensional structure
- The synthetic resin soaks through the fleece and distributes the sanding grain all over

AREA OF APPLICATION

- Matting and dust removal on large surfaces by machine
- Red – very fine: prior to filler application
- Grey – ultra fine: prior to paint application

BENEFITS

- Removes dust and prepares the surface for filler or paint application
- Suitable for wet and dry sanding

APPLICATION ADVICE

Perfectly suitable with the Carsystem matting pastes.

TEC LINE MATTFLEX PREMIUM

Sanding Fleece – Roll – 115 mm x 10 m



Art.-No.	Specification	SP	MOQ
151.616	Very fine / red	1	5
151.617	Ultra fine / grey	1	5

DESCRIPTION

- Sanding fleece with three-dimensional structure
- The synthetic resin soaks through the fleece and distributes the sanding grain all over

AREA OF APPLICATION

- Matting and sanding of hard-to-reach areas, smallest corners, folds and dimples prior to filler or paint application
- Red – very fine: prior to filler application
- Grey – ultra fine: prior to paint application

BENEFITS


- High flexibility
- On a roll for easy cut off in the needed length

APPLICATION ADVICE

Perfectly suitable with the Carsystem matting pastes.

TEC LINE MATTFLEX PAD

Sanding fleece – Pad – 115 × 230 mm



Art.-No.	Specification	SP	MOQ
152.686	Very fine / red	25	100
157.444	Extra fine / black	25	100
152.687	Ultra fine / grey	25	100
152.688	Micro fine / gold	25	100

DESCRIPTION

- Sanding fleece with three-dimensional structure
- The synthetic resin soaks through the fleece and distributes the sanding grain all over

AREA OF APPLICATION

- Matting and sanding of hard-to-reach areas, smallest corners, folds and dimples prior to filler or paint application
- Red – very fine: prior to filler application
- Black – extra fine: prior to paint application
- Grey – ultra fine: prior to paint application – especially for blending zones
- Gold – micro fine: prior to paint application – especially for blending zones

BENEFITS

- Extremely fine sanding pattern
- Very thin und extremely flexible
- Suitable for wet and dry sanding

APPLICATION ADVICE

Perfectly suitable with the Carsystem matting pastes.

TEC LINE SOFTFLEX

Paper abrasive – Roll – 115 × 125 mm



Art.-No.	Specification	SP	MOQ
152.689	P 150	1	5
152.690	P 180	1	5
152.691	P 240	1	5
152.692	P 320	1	5
152.693	P 400	1	5
152.694	P 500	1	5
152.695	P 600	1	5
152.696	P 800	1	5

DESCRIPTION

- Paper-based abrasive with foam back
- Roll with tear-off perforation
- 200 tear-offs / box

AREA OF APPLICATION

- Manual sanding of curves and hard-to-reach areas
- Suitable from coarse to fine sanding

BENEFITS

- Flexibility due to the foam back

SOFT-ROLL

Paper abrasive – Roll – 115 × 125 mm



Art.-No.	Specification	SP	MOQ
159.422	P 120	1	5
159.423	P 180	1	5
159.424	P 240	1	5
159.425	P 320	1	5
159.426	P 400	1	5
159.427	P 500	1	5
159.428	P 600	1	5
159.429	P 800	1	5
159.430	P 1000	1	5

DESCRIPTION

- Paper-based abrasive with foam back
- Roll with tear-off perforation
- 200 tear-offs / box

AREA OF APPLICATION

- Manual sanding of curves and hard-to-reach areas
- Suitable from coarse to fine sanding

BENEFITS

- Flexibility due to the foam back
- Also available in P1000

DOUBLE SANDING SOFT PAD

Foam abrasive – 120 × 98 × 13 mm



Art.-No.	Specification	SP	MOQ
160.183	Fine / P 240 / brown	15	60
160.185	Super Fine / P 500 / green	15	60
160.186	Microfine / P 1500 / purple	15	60

DESCRIPTION

- Double-sided soft pad with foam back
- Coloured aluminium oxide grain

AREA OF APPLICATION


- Matting and sanding of hard-to-reach areas, smallest corners, folds and dimples prior to filler or paint application
- Fine: prior to filler application
- Super fine and ultra fine: prior to paint application

BENEFITS

- Very flexible
- Perfect adaption on every curve
- For wet or dry use
- Colour coding for easy assignment

CLASSICLINE SOFT PAD

Foam abrasive – 140 × 115 mm



Art.-No.	Specification	SP	MOQ
138.924	Medium / P 220 – P 280	40	160
138.925	Fine / P 320 – P 400	40	160
138.926	Super fine / P 400 – P 500	40	160
138.927	Ultra fine / P 800 – P 1200	40	160

DESCRIPTION

- Soft pad with foam back
- Aluminium oxide grain

AREA OF APPLICATION


- Matting and sanding of hard-to-reach areas, smallest corners, folds and dimples prior to filler or paint application
- Medium and fine: prior to filler application
- Super fine and ultra fine: prior to paint application

BENEFITS

- Very flexible
- Perfect adaption on every curve
- For wet or dry use

TOPLINE SOFT PAD

Foam abrasive – 140 × 115 mm



Art.-No.	Specification	SP	MOQ
126.251	Medium / P 280 – P 360	40	40
126.252	Fine / P 400 – P 500	40	40
126.253	Super fine / P 600 – P 800	40	40
126.254	Ultra fine / P 1000 – P 1200	40	40

DESCRIPTION

- Soft pad with foam back
- Aluminium oxide grain

AREA OF APPLICATION

- Matting and sanding of hard-to-reach areas, smallest corners, folds and dimples prior to filler or paint application
- Medium: prior to filler application
- Fine and ultra fine: prior to paint application

BENEFITS

- Very fine sanding pattern
- Very flexible
- Perfect adaption on every curve
- For wet or dry use

ProFLEX NEPTUNE

Film abrasive – 130 × 170 mm



Art.-No.	Specification	SP	MOQ
153.472	P 600	50	1000
153.473	P 800	50	1000
154.454	P 1000	50	1000
154.455	P 1200	50	1000
153.474	P 1500	50	1000

DESCRIPTION

- Ultraflexible soft film sanding sheet
- Aluminium oxide grain
- Perforated in the middle

AREA OF APPLICATION

- Filler finish
- Blending
- Matting and flattening of hard-to-reach areas, smallest corners, folds and dimples

BENEFITS


- Ultraflexible basis adapts perfectly to the surface
- Extremely fine sanding pattern

APPLICATION ADVICE

We recommend the use of the ProFLEX Neptune Pads Max Grip.

ProFLEX NEPTUNE SOFT

Film abrasive – 130 × 85 mm – Multihole



Art.-No.	Specification	SP	MOQ
157.791	P 600	20	400
157.792	P 800	20	400
157.794	P 1000	20	400

DESCRIPTION

- Ultraflexible soft film sheet with flexible foam back
- Multihole
- Aluminium oxide grain

AREA OF APPLICATION

- Filler finish
- Blending
- Matting and flattening of hard-to-reach areas, smallest corners, folds and dimples
- Suitable for dry and wet sanding

BENEFITS

- Ultraflexible basis adapts perfectly to the surface
- Extremely fine sanding pattern
- Comfortable sanding due to foam back

APPLICATION ADVICE

We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth. We recommend using ProFLEX Neptune Soft with the Carsystem ProFLEX Neptune Pad MaxGrip. When using wet: We recommend the Carsystem Sanding Water SW20.

ProFLEX MERCURY

Film abrasive – 29 × 35 mm



Art.-No.	Specification	SP	MOQ
154.437	P 1500	200	4000
153.460	P 2000	200	4000
153.461	P 2500	200	4000
153.462	P 3000	200	4000

DESCRIPTION

- Film-based sanding sheets
- Self adhesive
- Aluminium oxide grain

AREA OF APPLICATION

- Removing of imperfections in the surface
- Finish
- Flattening of removed imperfections

BENEFITS

- Extremely fast removal of imperfections
- Dry use makes the sanding progress immediately visible
- Also suitable for slightly larger areas

APPLICATION ADVICE

We recommend the use of the ProFLEX Mercury block soft or hard. We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth.

ProFLEX PLUTO

Film abrasive – 34 mm



Art.-No.	Specification	SP	MOQ
154.428	P 1500	100	6000
154.429	P 2000	100	6000
154.430	P 2500	100	6000
154.431	P 3000	100	6000
154.432	P 4000	100	6000
154.433	P 5000	100	6000

DESCRIPTION

- Film-based daisy disc
- Self adhesive
- Aluminium oxide grain

AREA OF APPLICATION

- Removing of imperfections in the surface
- Finish
- Flattening of removed imperfections

BENEFITS

- Extremely fast removal of imperfections
- Dry use makes the sanding progress immediately visible

APPLICATION ADVICE

We recommend the use of the ProFLEX Back Pad 30 mm PSA for machine sanding and the Pluto Sanding Blocks for manual use. We recommend an intermediate cleaning of the abrasive surface with a microfiber cloth.

ProFLEX STYX

Film abrasive – Ø 32 mm



Art.-No.	Specification	SP	MOQ
159.738	P 1500 / petrol-blue	100	6000
159.739	P 3000 / greyish-green	100	6000

DESCRIPTION

- Film-based daisy disc
- Self adhesive

AREA OF APPLICATION

- Removing of imperfections in the surface
- Finish
- Flattening of removed imperfections
- Ideally suited for wet sanding

BENEFITS

- Extremely fast removal of imperfections
- Grit P3000 can be used as a One-Step Solution

APPLICATION ADVICE

For machine sanding we recommend the ProFLEX Back Pad 30 mm PSA or the IFP Grip To Stick 30 mm. Regular intermediate cleaning or moistening of the abrasive is also recommended.

TOPLINE WP S

Paper abrasive – 230 × 280 mm



Art.-No.	Specification	SP	MOQ
136.676	P 80	50	500
136.677	P 120	50	500
136.678	P 180	50	500
136.679	P 220	100	1000
136.680	P 240	100	1000
136.682	P 320	100	1000
136.683	P 360	100	1000
136.684	P 400	100	1000
136.685	P 500	100	1000
136.686	P 600	100	1000
136.687	P 800	100	1000
136.688	P 1000	100	1000
136.689	P 1200	100	1000
136.690	P 1500	100	1000
136.691	P 2000	100	1000

DESCRIPTION

- Wet sanding paper
- Silicon carbide grain
- Flexible latex reinforced A-paper P80 – P180
- Smooth latex reinforced C-paper P220 – P2000

AREA OF APPLICATION


- Wet sanding of filler coated or painted surfaces

BENEFITS

- Very high cutting power due to the silicon carbide grain
- Highest flexibility after short soaking time due to the high quality latex reinforced paper

STRIPPING DISC

Raw cleaning disc



Art.-No.	Specification	SP	MOQ
127.999	100 mm	10	10
128.000	150 mm	10	10

DESCRIPTION

- Cleaning disc for removing semi-soft materials and paint by machine

AREA OF APPLICATION

- Removal of semi-soft materials like underbody coating, stone chip protection, sealing compounds, paint and rust by machine

BENEFITS

- The substrate remains undamaged

APPLICATION ADVICE

100 mm = max. 6,000 rpm.
150 mm = max. 4,000 rpm.

TAPE OFF DISC PREMIUM

Sticker removal disc



Art.-No.	Specification	SP	MOQ
152.013	90 mm / set of 2 discs + 1 adapter	1	50

DESCRIPTION

- Sticker removal disc
- Caramel smell

AREA OF APPLICATION

- Residue-free removal of stickers, decorative stripes, decals etc.

BENEFITS

- No discoloration of the paint

APPLICATION ADVICE

Max. 4.000 rpm

SANDING WATER SW20

Sanding water



Art.-No.	Specification	SP	MOQ
157.446	Incl. spray nozzle / 1 l	1	14
157.447	5 l	1	4

DESCRIPTION

- Sanding water
- Free of silicones

AREA OF APPLICATION

- Wet sanding on clear coat

BENEFITS

- Extends the lifetime of the abrasive
- Optimizes the wetting of the abrasive
- Foaming prevents the tying of the sanding dust with the water

APPLICATION ADVICE

We recommend using the Carsystem Sanding Water SW20 in combination with ProFLEX Jupiter Soft H₂O and all other sanding media.

GRIP TO STICK INTERFACE PAD

Interface pad – Ø 30 mm



Art.-No.	Specification	SP	MOQ
159.677	5 pcs / pack / Ø 30 mm	5	250

DESCRIPTION

- Interface pad with adhesive backing

AREA OF APPLICATION

- Finish
- Removal of imperfections in the surface

BENEFITS

- No need to change the backing pad on the polishing machine
- Provides the perfect balance of dampening and stock removal
- Reduces finish polishing time

APPLICATION ADVICE

We recommend the use with our Carsystem cordless polisher CSH-CMS01 and ProFLEX Styx and ProFLEX Pluto sanding sheets.



EXCENTER BACK PAD T.19

Back pad – 150 mm



Art.-No.	Specification	SP	MOQ
156.564	Soft / grip / M8 and 5/16"	1	50
156.227	Medium / grip / M8 and 5/16"	1	50
156.563	Hard / grip / M8 and 5/16"	1	50

DESCRIPTION

- Back pad with Carsystem hole pattern
- 25 holes and oval center hole
- Three degrees of hardness: Soft, medium, hard

AREA OF APPLICATION


- Soft = Lowest cutting power highest flexibility
- Medium = Balance between cutting power and flexibility
- Hard = Highest cutting power – lowest flexibility

BENEFITS

- Individual due to the 3 different degrees of hardness

EXCENTER BACK PAD MULTI M

Back pad – 150 mm



Art.-No.	Specification	SP	MOQ
156.570	Grip	1	100

DESCRIPTION

- Multi-hole excenter back pad
- Degree of hardness: Medium
- Suitable for all commercially available excenter machines
- Incl. M8 and 5/16" screws and Festool special adapter

AREA OF APPLICATION

- Universal back pad for dry sanding work

RUPES BACK PAD

Back pad – 150 mm



Art.-No.	Specification	SP	MOQ
158.291	Rupes 981.500 – M8 / 150 mm	1	10
158.292	Rupes 981.600 / 5/16 " / 150 mm	1	10

DESCRIPTION

- Back pad with multi hole pattern
- Strength: Hard
- Thread-M8: RUPES TA-ER-BR-RH-machines
- Thread-5/16": RUPES Skorpio E RX

ProFLEX BACK PAD PSA

Back pad – 30 mm



Art.-No.	Specification	SP	MOQ
155.153	Stick / 1/4" inner thread	2	2

DESCRIPTION

- PSA cellular rubber back pad for ProFLEX Pluto daisy discs

AREA OF APPLICATION

- Usable with the CS Mini Sanding Machine an Carsystem Orbital Sander CSH-CMS01
- Usable with the ProFLEX Pluto daisy discs

BENEFITS

- Perfect balance between cutting power and even sanding pattern in the final sanding process

FINISH SANDER BACK PAD

Back pad – 77 mm



Art.-No.	Specification	SP	MOQ
144.917	5/16" UNF connections	1	1

DESCRIPTION

- Replacement back pad for Finish Sander RC 9332
- Thread: 5/16" (fixed screw)

MINI BACK PAD

Finish back pad



Art.-No.	Specification	SP	MOQ
144.768	Medium / stick / 28 mm	1	5
144.769	Medium / grip / 28 mm	1	5

DESCRIPTION

- Replacement back pad for mini sanding machine RC 9330 and Carsystem Orbital Sander CSH-CMS01
- For self-adhesive discs / Velcro® discs
- Inner tread 1/4"



INTERFACE PAD

Interface pad – 150 mm



Art.-No.	Specification	SP	MOQ
156.225	10 mm	2	50
156.226	5 mm	2	50

DESCRIPTION

- Interface pad with Carsystem hole pattern
- 25 holes and oval center hole
- The hole pattern is based on the 15-hole pattern and 10 additional holes
- Thickness: 5 mm + 10 mm

AREA OF APPLICATION

- Sanding on all areas with curves, roundings and edges
- Usable with the Carsystem F.19, F.23 and P.25 sanding discs

BENEFITS

- Perfect adaption to the surface
- Minimizes the risk of sanding through
- The oval middle-hole helps to align the sanding disc

SOFT INTERFACE PAD

Interface pad – 150 mm



Art.-No.	Specification	SP	MOQ
140.585	Grip / 10 mm / no holes	2	10
140.584	Grip / universal	2	10

DESCRIPTION

- Universal interface pad
- Multi hole interface pad for all common hole systems
- Thickness: 10 mm

AREA OF APPLICATION

- Sanding on all areas with curves, roundings and edges

BENEFITS

- Perfect adaption to the surface
- Minimizes the risk of sanding through

ProFLEX INTERFACE PAD FINISH

Interface pad – 150 mm – 15 holes



Art.-No.	Specification	SP	MOQ
159.078	Velcro® Loop Back	2	350

DESCRIPTION

- Interface pad with female Velcro® loop back on both sides

AREA OF APPLICATION

- Ideal for use with ProFLEX Jupiter discs

BENEFITS

- Finer sanding pattern compared to other interface pads
- Reduction of polishing time

ProFLEX INTERFACE PAD FINISH

Interface pad – 75 mm



Art.-No.	Specification	SP	MOQ
159.079	Velcro® Loop Back	4	600

DESCRIPTION

- Interface pad with female Velcro® loop back on both sides

AREA OF APPLICATION

- Ideal for use with ProFLEX Jupiter discs

BENEFITS

- Finer sanding pattern compared to other interface pads
- Reduction of polishing time

ProFLEX INTERFACE PAD

Interface pad – 150 mm – 15 holes



Art.-No.	Specification	SP	MOQ
154.295	Soft / 10 mm	1	20
154.193	Medium / 10 mm	1	20
155.100	Hard / 5 mm	1	30

DESCRIPTION

- Interface pads with micro Velcro® for ProFLEX Jupiter sanding discs
- Three degrees of hardness: Soft, medium, hard
- Soft / Medium: 10 mm thickness
- Hard: 5 mm thickness

AREA OF APPLICATION


- The micro Velcro® allows the use of soft film discs (ProFLEX Jupiter)
- Soft = Finest sanding pattern for final finish sanding
- Medium = Balance between cutting power and evenness
- Hard = Highest cutting power

BENEFITS

- Selection of three different degrees of hardness
- Micro Velcro® does not provoke scratches through the soft film abrasive

ProFLEX INTERFACE PAD

Interface pad – 75 mm



Art.-No.	Specification	SP	MOQ
154.296	Soft / 10 mm	1	20
154.194	Medium / 10 mm	1	20
155.098	Hard / 5 mm	1	30

DESCRIPTION

- Interface pad with micro Velcro® for ProFLEX Jupiter sanding discs
- Three degrees of hardness: Hard, medium, soft
- Soft / Medium: 10 thickmess
- Hard: 5 mm thickness

AREA OF APPLICATION

- The micro Velcro® allows the use of soft film discs (ProFLEX Jupiter)
- Soft = Finest sanding pattern for final finish sanding
- Medium = Balance between cutting power and evenness
- Hard = Highest cutting power

BENEFITS

- Selection between three different degrees of hardness
- Micro Velcro® does not provoke scratches through the soft film

For industrial and professional use only.

ProFLEX INTERFACE PAD

Interface pad – 30 mm



Art.-No.	Specification	SP	MOQ
157.137	Hard / 5 mm	5	500

DESCRIPTION

- Interface pad with micro Velcro® for ProFLEX Jupiter daisy discs
- Cellular rubber pad
- Thickness: 5 mm

AREA OF APPLICATION

- Usable with the ProFLEX Jupiter daisy discs

BENEFITS

- Hard cellular rubber provides more stability and cutting power
- Micro Velcro® does not provoke scratches through the soft film

For industrial and professional use only.

PAD SAVER

Interface pad – 150 mm



Art.-No.	Specification	SP	MOQ
154.099	Pad Saver / 5 pcs. /bag	1	100

DESCRIPTION

- Interface pad with multi holes for all common hole systems
- Thickness: 3 mm

AREA OF APPLICATION

- The Pad Saver is used as a second Velcro® layer

BENEFITS

- Saves the original Velcro® layer of the excenter back pad

ProFLEX NEPTUNE PAD MAXGRIP

Hand pad – 120 × 75 × 6 mm – multihole



Art.-No.	Specification	SP	MOQ
158.097	Soft – medium	1	100

DESCRIPTION

- Sponge hand pad
- Micro Velcro®
- Degree of hardness: Soft – Medium

AREA OF APPLICATION

- Hand pad for all Neptune sanding sheets

BENEFITS

- Non-slip
- Ideal for dry and wet sanding with excellent water transport (Neptune Soft)
- Very comfortable feeling
- Adapts perfectly to the surface



SANDING BLOCK 400 GRIP FLEX

Hand sanding block – Velcro®



Art.-No.	Specification	SP	MOQ
150.088	14 holes / 70×400 mm	1	5

DESCRIPTION

- Flexible hand sanding file with dust extraction
- Free variable for concave and convex surfaces

AREA OF APPLICATION

- Usable with Carsystem F.23 and P.25 ceramic sanding strips and Carsystem N20 net sanding strips

BENEFITS

- For even, concave and convex surfaces

SANDING BLOCK 400 2.0

Hand sanding block 400 2.0



Art.-No.	Specification	SP	MOQ
159.534	Multi holes / 70×400 mm	1	15

DESCRIPTION

- Hand sanding block made of plastic
- Optimised suction adapted to the F.23 and P.25 Ceramic hole pattern
- Rubberised handles

AREA OF APPLICATION

- Usable with Carsystem Sanding Strips F.23 Ceramic, P.25 Ceramic and Carsystem N20 net sanding strips

BENEFITS

- Rubberised handles for more control during sanding
- Optimised suction prevents clogging of the abrasive

For industrial and professional use only.

SANDING BLOCK 300 + 100

Hand sanding block -Velcro®



Art.-No.	Specification	SP	MOQ
160.172	70×100 mm	1	50
159.571	70×300 mm	1	50

DESCRIPTION

- Hand sanding block made of medium-strength foam with Velcro®
- All-round handle

AREA OF APPLICATION

- For processing the Sanding Strips F.23 und P.25 Ceramic and P.25 Ceramic
- 1-3 tear-offs

BENEFITS

- Suitable for wet and dry sanding
- All-round handle provides a secure hold
- Adapts to any vehicle contour

For industrial and professional use only.



SANDING BLOCK 198 2.0

Hand sanding – Velcro®



Art.-No.	Specification	SP	MOQ
159.535	Multi holes / 70 x 198 mm	1	50

DESCRIPTION

- Hand sanding block with dust extraction

AREA OF APPLICATION

- Usable with Carsystem Sanding Strips F.23 ceramic, P.25 Ceramic and N20 net sanding strips

BENEFITS

- Rubberised handles for more control during sanding
- Optimised suction prevents clogging of the abrasive

SANDING BLOCK 198 KIT

Hand sanding block set – Velcro®



Art.-No.	Specification	SP	MOQ
148.702	22 holes / 70 x 198 mm	1	1

DESCRIPTION

- Set of hand sanding blocks with adjustable dust extraction
- Four exchangeable base plates for flat, concave and convex surfaces
- Multi hole for all common sanding strips

AREA OF APPLICATION

- Usable with Carsystem F.23 and P.25 ceramic sanding strips 70 x 198 mm and N20 net sanding strips

BENEFITS

- Four exchangeable base plates for flat, concave and convex surfaces

SANDING BLOCK DISC KIT 150

Hand sanding block set – Velcro®



Art.-No.	Specification	SP	MOQ
151.904	15 holes / 150 mm	1	1

DESCRIPTION

- Set of hand sanding blocks with adjustable dust extraction
- Four exchangeable base plates for flat, concave and convex surfaces
- Multi hole for all common sanding discs

AREA OF APPLICATION

- Usable with 150 mm sanding discs with Velcro®

BENEFITS

- Four exchangeable base plates for flat, concave and convex surfaces
- Dust extraction valve adjustable

SANDING BLOCK GRIP

Hand sanding block – Velcro®



Art.-No.	Specification	SP	MOQ
137.439	150 mm	1	6

DESCRIPTION

- Polyurethane hand sanding blocks

AREA OF APPLICATION

- Usable with 150 mm Velcro® discs

SANDING BLOCK 100 2.0

Hand sanding – Velcro®



Art.-No.	Specification	SP	MOQ
160.224	70 x 100 mm – with extraction	1	54

DESCRIPTION

- Hand sanding block with dust extraction

AREA OF APPLICATION

- For processing the Sanding Strips F.23 Ceramic (1 tear-off)

BENEFITS

- Rubberised handles for more control during sanding
- Optimised suction prevents clogging of the abrasive

SANDING BLOCK GRIP BOX

Hand sanding blocks – Velcro®



Art.-No.	Specification	SP	MOQ
142.009	Velcro® 150 mm	1	16

DESCRIPTION

- Polyurethane hand sanding blocks
- Four different blocks, for even, concave and convex surfaces

AREA OF APPLICATION

- Usable with 150 mm sanding discs with Velcro®

BENEFITS

- Sanding blocks for even, concave and convex surfaces

SANDING BLOCK HARD

Hand sanding block – hard



Art.-No.	Specification	SP	MOQ
137.431	125 mm × 70 mm	1	12

DESCRIPTION

- Hard rubber sanding block

AREA OF APPLICATION

- Levelling surfaces
- Wet and dry sanding

ProFLEX PLUTO SANDING BLOCK

Sanding block



Art.-No.	Specification	SP	MOQ
156.557	Soft / red	2	100
156.556	Hard / black	2	100

DESCRIPTION

- Rubber block for the use with Pluto daisy discs
- Two degrees of hardness: Soft and Hard

AREA OF APPLICATION

- Soft: Flattening of imperfections (more flexible)
- Hard: Flattening of dust inclusions

BENEFITS

- Usable on both sides
- Two degrees of hardness for the whole finish process
- Rounded edges perfect for smooth roundings

For industrial and professional use only.

ProFLEX MERCURY SANDING BLOCK

Sanding block – 27 × 33 × 15 mm



Art.-No.	Specification	SP	MOQ
156.555	Soft / red	2	100
154.173	Hard / black	2	100

DESCRIPTION

- Rubber block for the use with ProFLEX Mercury sheets
- Two degrees of hardness: Soft and hard

AREA OF APPLICATION

- Soft: Flattening of imperfections (more flexible)
- Hard: Flattening of dust inclusions

BENEFITS

- Usable on both sides
- Two degrees of hardness for the whole finish process

For industrial and professional use only.

FINE BLOCK

Fine sanding block



Art.-No.	Specification	SP	MOQ
140.979	800	1	10
140.980	1500	1	10
140.981	2000	1	10
140.982	3000	1	10

DESCRIPTION

- Carbon fine sanding block

AREA OF APPLICATION

- Removal of bigger paint imperfections e. g. paint drops or large dust inclusions

BENEFITS

- Self sharpening

APPLICATION ADVICE

We recommend using the fine sanding block only wet. Soak thoroughly before the initial use for at least 15 min. The fine block should not get dry again after being soaked for the first time.



PAINT PLANER

Paint planer and holder



Art.-No.	Specification	SP	MOQ
142.995	Paint Planer	1	1
142.996	Holder	1	1

DESCRIPTION

- Paint planer and holder
- The front side of the holder is for storing the paint planer
- The back sides can hold Velcro® adhesive daisy discs

AREA OF APPLICATION

- Removal of paint imperfections

DRY COAT 2.0

Sanding control system



Art.-No.	Specification	SP	MOQ
158.487	Set: 1 applicator / 1 foam ring / storage tray	1	32
158.488	Dry Coat 2.0 foam ring set of 2	1	200
158.489	Refill, 2 pcs. / black / 30 g	1	120
158.490	Refill, 2 pcs / orange / 15 g	1	120

DESCRIPTION

- Ergonomic adapted applicator (hand block) for easy application with the Carsystem control powder cartridges
- Included: Hand applicator + Velcro® foam ring + storage tray
- Velcro® foam ring set of 2 pcs. and control powder cartridges can be ordered separately

AREA OF APPLICATION

- Optimum sanding control of putty and filler areas
- Control powder black – for light-coloured surfaces
- Control powder orange – for dark surfaces
- Velcro® foam ring: Set of 2 pcs.

BENEFITS

- Makes the finest imperfections and structures visible on the surface
- Aerosol and solvent-free / control powder – does not clog the abrasives
- Easy one-hand-application
- Simple cartridge change due to the Velcro foam ring
- Sustainable storage tray (parking area) included
- Individual components can be ordered: foam rings, powder cartridges

APPLICATION ADVICE

The control powder reaches deep into all imperfections of the surfaces, so all kind of scratches, pinholes become visible.The Carsystem Dry Coat 2.0 requires no drying time or masking. The control powder can be sanded immediately after application.

For industrial and professional use only.

CONTROL-SPRAY

Sanding control spray



Art.-No.	Specification	SP	MOQ
125.779	400 ml	1	12

DESCRIPTION

- Black sanding control spray puts a layer of control paint onto the surface to make sanding imperfections visible
- Colour: Black

AREA OF APPLICATION

- Sanding control of putty or filled surfaces

BENEFITS

- Makes finest imperfections in the surface visible
- Fast drying, grease and silicone-free

For industrial and professional use only.

TEC LINE MATT MATTING MOUSSE

Matting paste



Art.-No.	Specification	SP	MOQ
151.947	1.0 kg	1	6

DESCRIPTION

- Water-based matting paste
- Colour: Light grey

AREA OF APPLICATION

- Blending
- Matting of transition zones
- Degreasing and cleaning of body parts

BENEFITS

- Suitable for paint or plastic parts
- Sanding, cleaning and degreasing in one step
- Improves the adhesion of the paint layer
- Perfect matting result
- Removes silicones and waxes from the surface



PREP & SCUFF

Matting paste



Art.-No.	Specification	SP	MOQ
137.547	1.3 kg	1	6
137.779	Dispenser for 5,0 kg	1	1

DESCRIPTION

- Water-based matting paste
- Colour: Light grey

AREA OF APPLICATION

- Blending
- Matting of transition zones
- Degreasing and cleaning of body parts

BENEFITS

- Sanding, cleaning and degreasing in one step
- Improves the adhesion of the paint layer
- Even matting
- Removes silicones and waxes from the surface

APPLICATION ADVICE

Hard-to-reach areas can be treated with the Prep-brush (Art.-No.: 138.301).

PREP-BRUSH

Special brush



Art.-No.	Specification	SP	MOQ
159.696	5 cm	1	24

DESCRIPTION

- Special brush for matting pastes

AREA OF APPLICATION

- For applying matting pastes on hard-to-reach areas

RUPES SKORPIO III RH

Random orbital sander, pneumatic



Art.-No.	Specification	SP	MOQ
157.334	RH353A / 3 mm orbital diameter	1	1
157.335	RH356A / 6 mm orbital diameter	1	1

DESCRIPTION

- Pneumatic random orbital single-hand sander
- 3mm / 6mm / 9mm orbital diameter
- Ø Velcro® back pad: 150mm
- Adjustable speed up to 11.000 rpm
- Thread: M8

EXCENTER CLASSIC

Random orbital sander, pneumatic



Art.-No.	Specification	SP	MOQ
139.653	Without back pad / 5 mm orbital diameter	1	1

DESCRIPTION

- Pneumatic random orbital sander without back pad
- 5 mm orbital diameter
- Thread: 5/16" - 24 inner thread

AREA OF APPLICATION

- For coarse sanding

RUPES SKORPIO E RX

Random orbital sander, electric



Art.-No.	Specification	SP	MOQ
157.326	RX253A / 3 mm orbital diameter	1	1
157.328	RX256A / 6 mm orbital diameter	1	1

DESCRIPTION

- Electric random orbital single-hand sander
- 3 mm / 6 mm orbital diameter
- Ø Velcro® back pad: 150 mm
- Adjustable speed up to 10.000 rpm
- Inner thread: 5/16"
- Power: 250 Watt

RUPES ORBITAL SANDER SL42AES

Orbital sander, electric



Art.-No.	Specification	SP	MOQ
157.329	SL42AES / 4.8 mm orbital diameter	1	1

DESCRIPTION

- Electric orbital sander
- 4.8 mm orbital diameter
- Size: 70 × 400 mm
- Adjustable speed up to 7.000 rpm
- Power: 550 Watt

RUPES ORBITAL SANDER
SLP41A

Orbital sander, pneumatic



Art.-No.	Specification	SP	MOQ
157.337	SLP41A / 4.8 mm orbital diameter	1	1
157.559	rubber plate 619.153MH / 70 x 400 mm	1	1

DESCRIPTION

- Pneumatic orbital sander
- 4.8 mm orbital diameter
- Size: 70 x 400 mm
- Adjustable speed up to 10.000 rpm

RUPES RANDOM ORBITAL
SINGLE-HAND SANDER RA75

Random orbital sander, pneumatic



Art.-No.	Specification	SP	MOQ
157.333	RA75 / 3 mm orbital diameter	1	1
147.663	Rupes Pad Velcro 5/16" – RA75 soft	1	1

DESCRIPTION

- Pneumatic random orbital single-hand sander
- 3 mm orbital diameter
- Ø Velcro® back pad: 75 mm
- Adjustable speed up to 11.000 rpm
- Thread: 5/16"

RUPES ORBITAL SANDER
RE21ALN

Orbital sander, pneumatic



Art.-No.	Specification	SP	MOQ
157.454	RE21ALN / 3 mm orbital diameter	1	1
157.558	Sanding plate 988.001MH / 70 x 198 mm	1	1

DESCRIPTION

- Pneumatic orbital single-hand sander
- 3 mm orbital diameter
- Size: 70 x 198 mm
- Adjustable speed up to 11.000 rpm

FINISH SANDER RC 9332

Random orbital sander 75 mm, pneumatic



Art.-No.	Specification	SP	MOQ
143.388	Incl. back pad / 2.5 mm orbital diameter	1	1

DESCRIPTION

- Pneumatic random orbital single-hand sander
- 2.5 mm orbital diameter
- Adjustable speed up to 10.000 rpm
- Back pad connection: Inner thread 5/16"
- Air hose connection: Inner thread 1/4"

RUPES IBRID NANO

Battery operated mini sanding and polishing machine



Art.-No.	Specification	SP	MOQ
157.318	HR81M / STB Ibrid Nano short neck	1	1
157.319	HR81ML / STB Ibrid Nano long neck	1	1
158.370	Polish Pad 9.DA 40S / extrafine / white	6	6
157.718	Polish Pad 9.DA 40M / fine / yellow	6	6
157.717	Polish Pad 9.DA 40H / hard / blue	6	6
157.784	Back pad 995.001C / Velcro® daisy discs / 30 mm	1	1
157.785	Back pad 996.001C / Velcro® daisy discs / 50 mm	1	1
157.786	Back pad 997.001C / Self adhesive daisy discs / 30 mm	1	1
157.787	Rotation unit 562.390	1	1
157.788	Orbital diameter unit / 3mm	1	1

DESCRIPTION

- Battery operated mini sanding machine
- Provided with: 12 mm orbital diameter unit and 50 mm Velcro® back pad
- Adjustable speed up to 5.000 rpm
- Running time: Approx. 30 min
- Charging time: Approx. 20 min

RUPES IBRID NANO Q-MAQ

Battery operated mini sanding and polishing machine



Art.-No.	Specification	SP	MOQ
157.320	MAQ HQM83 / STB / Ibrid Nano Q-MAG	1	1
157.644	Back pad / 75 mm	1	1

DESCRIPTION

- Battery operated random orbital sander
- 2 mm orbital diameter
- Ø Velcro® back pad: 75 mm
- Adjustable speed up to 5.000 rpm
- Running time: Approx. 30 min
- Charging time: Approx. 20 min

TAPE OFF TOOL

Axial sander



Art.-No.	Specification	SP	MOQ
133.172	1 axial sander	1	1

DESCRIPTION

- Pneumatic axial grinder
- Retarded runout

AREA OF APPLICATION

- Usable with Carsystem Tape Off Discs

BENEFITS

- Reduced speed to avoid damaging the paint

PUTTIES

PUTTIES FOR ALL KIND OF SURFACES AND APPLICATIONS FOR A PROFESSIONAL REPAIR

As one of the leading manufacturers of putties, we produce high-quality products to enable professional restoration and repair of bodywork components and vehicle surfaces in bodyshops and paint shops. Thanks to our versatile putties, which are produced in our headquarters with our own formulation, our brand has established itself on the market both nationally and internationally over the years.

Our CARSYSTEM Multi, the polyester multi-purpose putty or the universal putty with multi-adhesion, as well as the Multi Green range are our most well-known putties. Whether glass fibre putty, fine putty, with or without styrene: CARSYSTEM has almost every possible version listed in its product range.

Special putties, such as the Multi Changer, which cause a colour change during the curing phase, prove our constant introduction of innovative products for the automotive industry.



MULTI BLUE RAPID CHANGER SF

Multifunctional polyester putty, styrene-free

NEW



Art.-No.	Specification	SP	MOQ
159.923	1.3 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Styrene-free
- Multi adhesion
- Colour change during the curing time from blue to grey

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Styrene-free
- Pore-free and easy to apply due to its creamy texture
- Faster drying time
- Colour change during the curing time from blue to grey

DRYING TIME

- 12 minutes / 18 – 20 °C room and object temperature

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI BLACK RAPID

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
159.755	1.3 kg tin incl. hardener	1	6
160.343	2,2 kg incl. hardener (3 kg-cartridge)	1	6

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Black

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Multi adhesion
- No surface moisture after curing
- No control powder necessary due to the dark shade

DRYING TIME

- 10 min / 20 °C object temperature

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI GREEN PLUS 1.0 SUPER LIGHT

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
152.357	1.0 kg tin incl. hardener	1	6
152.978	1.6 kg cartridge incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Ultra lightweight putty
- Colour: Green

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Completely dry surface after curing
- Improved sandability due to the latest filling agents
- Curing time: 12 min / 20 °C objecttemperature
- Multi adhesion

DRYING TIME

- 12 min / 20 °C object temperature

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI GREEN

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
146.706	1.6 kg tin incl. hardener	1	6
147.337	2.52 kg cartridge incl. hardener	1	6
149.134	8.11 kg cartridge incl. hardener	1	2

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Green

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Reduced surface moisture after curing
- Good balance between being semi-solid and creamy
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES



MULTI FLOW

Polyester multi light putty

NEW

The Carsystem Multi Flow is an ultra-light polyester multifunctional putty with a self-levelling, pore-free surface. It provides excellent adhesion on common metal surfaces, wood, GRP and 2-comp. polyester putty, delivering smooth, flawless results with minimal sanding effort. Ideal for filling small to medium imperfections, scratches, and sanding marks, the Multi Flow putty is easy to apply, highly sandable, and ensures a perfect, professional finish every time.

DESCRIPTION

- Very light polyester multifunctional putty
- Self-levelling, non-porous surface
- Colour: Light-blue

AREA OF APPLICATION

- For filling small and medium imperfections and scratches

BENEFITS

- Multi adhesion on common metal surfaces, wood, GRP and 2-comp. polyester putty
- Very smooth and pore-free surface results
- Self-levelling properties
- Very easy to sand

DRYING TIME

- 20 – 30 min / 18 – 20 °C room and object temperature

Art.-No.	Specification	SP	MOQ
160.378	1 kg tin incl. hardener	1	6



SCAN ME



STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI GREEN RAPID

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
158.233	1.3 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Green

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Hardly surface moisture after curing
- Improved sandability due to the latest filling agents
- Multi adhesion

DRYING TIME

- 10 min / 20 °C object temperature

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI GREEN SF

Multifunctional polyester putty styrene-free



Art.-No.	Specification	SP	MOQ
156.543	1.75 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Styrene-free
- Colour: Green

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Styrene-free
- Very easy to apply due to its creamy consistency
- Multi adhesion

APPLICATION ADVICE

Styrene-free filler differs from conventional fillers in terms of odour.

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI GREEN CHANGER

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
157.622	1.6 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Green

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Colour change during the curing time from green to yellow
- Reduced surface moisture after curing
- Good balance between being semi-solid and creamy
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI GREEN GLAS

Multifunctional fiberglass reinforced polyester putty



Art.-No.	Specification	SP	MOQ
146.707	1.65 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Glass fibre reinforced putty
- Colour: Green

AREA OF APPLICATION

- For filling very deep imperfections, for repairing treated rust spots and GRP parts
- Perfectly suitable for GRP repair

BENEFITS

- Short glass fibres
- Multi adhesion
- Very precise application

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI GREEN GLAS LIGHT

Multifunctional fiberglass reinforced lightweight polyester putty



Art.-No.	Specification	SP	MOQ
158.116	1.3 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Glass fibre reinforced ultra lightweight putty
- Colour: Green

AREA OF APPLICATION

- For filling very deep imperfections, for repairing treated rust spots and GRP

BENEFITS

- Short glass fibres
- Multi adhesion
- Very precise application
- Optimized sandability

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
130.857	1.0 kg tin incl. hardener	1	6
127.977	2.0 kg tin incl. hardener	1	6
134.155	1.5 kg cartridge incl. hardener	1	8
132.214	2.9 kg cartridge incl. hardener	1	6
128.145	9.7 kg cartridge incl. hardener	2	2

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Beige

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Very easy to apply due to its creamy consistency
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI LIGHT

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
141.503	1.3 kg tin incl. hardener	1	6
142.155	2.2 kg cartridge incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Ultra lightweight putty
- Colour: Light beige

AREA OF APPLICATION

- For filling small to medium-sized imperfections, dents and scratches

BENEFITS

- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

MULTI SILVER LIGHT

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
140.795	1.5 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Lightweight putty
- Colour: Silver

AREA OF APPLICATION

- For filling small to medium-sized imperfections, dents and scratches

BENEFITS

- Creates a visually good-looking transition zone due to its silver colour
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI PLUS

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
138.451	1.6 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Universal putty
- Colour: Light grey

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Good balance between being semi-solid and creamy
- Very easy to apply
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

MULTI SOFT

Multifunctional polyester putty



Art.-No.	Specification	SP	MOQ
137.206	2.0 kg tin incl. hardener	1	6

DESCRIPTION

- Multifunctional polyester putty
- Fill and fine putty
- Colour: Light grey

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches

BENEFITS

- Very easy to apply due to its creamy consistency
- Multi adhesion

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

For industrial and professional use only.

SOFT

Polyester – fill putty



Art.-No.	Specification	SP	MOQ
127.972	1.8 kg tin incl. hardener	1	6
132.116	2.6 kg cartridge incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Fill putty
- Colour: Beige

AREA OF APPLICATION

- For filling medium-sized to deep imperfections, dents and scratches

BENEFITS

- Easy to apply due to its creamy consistency

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

METALLIC

Polyester – fill putty



Art.-No.	Specification	SP	MOQ
130.852	1.0 kg tin incl. hardener	1	6
127.911	2.0 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Fill putty
- High density due to aluminum content
- Colour: Silver

AREA OF APPLICATION

- For filling medium-sized to deep imperfections, dents and scratches

BENEFITS

- Creates a visually good-looking transition zone due to its silver colour

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

ALU SPEZIAL

Polyester – hard putty



Art.-No.	Specification	SP	MOQ
148.524	1.8 kg tin incl. hardener	1	6

DESCRIPTION

- Special polyester putty
- Hard putty
- Extremely high hardness
- Colour: Light grey

AREA OF APPLICATION

- For filling very deep imperfections
- Rebuilding of edges and bonded aluminum parts

BENEFITS

- Replaces the tin application for aluminium
- No sagging of transition zones on bonded replacement parts

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✗	✓	✓

STEEL

Polyester – hard putty



Art.-No.	Specification	SP	MOQ
138.587	0.9 kg tin incl. hardener	1	6

DESCRIPTION

- Special polyester putty
- Hard putty
- Extremely high hardness
- Colour: Silver

AREA OF APPLICATION

- Replaces the tin application for welded steel panels
- For filling very deep imperfections
- Rebuilding of deformed edges

BENEFITS

- Highly break resistant
- Fast drying

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

ELASTIC BEIGE

Polyester – fine putty



Art.-No.	Specification	SP	MOQ
127.976	2.0 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Fine putty
- Colour: Beige

AREA OF APPLICATION

- For filling small to medium-sized imperfections, dents and scratches

BENEFITS

- Provides an extra fine surface almost free of pores
- Minimizes the sanding effort

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

ELASTIC WHITE

Polyester – fine putty



Art.-No.	Specification	SP	MOQ
130.856	1.0 kg tin incl. hardener	1	6
127.975	2.0 kg tin incl. hardener	1	6
132.723	10.0 kg cartridge incl. hardener	2	2

DESCRIPTION

- Polyester putty
- Fine putty
- Colour: White

AREA OF APPLICATION

- For filling small to medium-sized imperfections, dents and scratches

BENEFITS

- Provides an extra fine surface almost free of pores
- Minimizes the sanding effort

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

ANTI RUST PUTTY

Anti rust putty



Art.-No.	Specification	SP	MOQ
149.612	1.8 kg tin incl. hardener	1	6

DESCRIPTION

- Special polyester putty
- Anti rust putty
- Colour: Red brown

AREA OF APPLICATION

- For filling small imperfections, dents and scratches
- To provide additional rust protection

BENEFITS

- Additional anti rust layer

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

LIQUID PUTTY

Polyester – liquid putty



Art.-No.	Specification	SP	MOQ
143.496	1.04 kg bottle incl. hardener	1	8

DESCRIPTION

- Polyester putty
- Liquid putty
- Colour: Beige

AREA OF APPLICATION

- For filling small imperfections, dents and scratches

BENEFITS

- Provides a perfect result almost free of pores
- Self-levelling

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

GLAS

Polyester – glass fibre reinforced putty



Art.-No.	Specification	SP	MOQ
130.854	1.0 kg tin incl. hardener	1	6
127.974	1.8 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Glass fibre reinforced putty
- Colour: Green

AREA OF APPLICATION

- For filling very deep imperfections, for repairing treated rust spots and GRP parts
- Perfectly suitable for GRP repair

BENEFITS

- Extra long glass fibres

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

GLAS WHITE

Polyester – glass fibre reinforced putty



Art.-No.	Specification	SP	MOQ
144.808	1.8 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Glass fibre reinforced putty
- Colour: White

AREA OF APPLICATION

- For filling very deep imperfections, for repairing treated rust spots and GRP parts
- Perfectly suitable for GRP repair

BENEFITS

- Extra long glass fibres

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

FASER

Polyester – glass fibre reinforced putty



Art.-No.	Specification	SP	MOQ
138.443	1.4 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Special glass fibre reinforced putty
- Less fibres and more resin compared to normal glass fibre putties
- Colour: Brown transparent

AREA OF APPLICATION

- For filling very deep imperfections, for repairing treated rust spots and GRP parts
- Perfectly suitable for GRP repair

BENEFITS

- Extra long glass fibres

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

MULTI SUPER FLEX

Polyester putty highly elastic



Art.-No.	Specification	SP	MOQ
153.284	1.8 kg tin incl. hardener	1	10

DESCRIPTION

- Multifunctional polyester putty
- Highly elastic putty
- Colour: Dark grey

AREA OF APPLICATION

- For filling small imperfections, dents and scratches on very flexible plastic parts

BENEFITS

- No loss of adhesion in the transition zone
- No adhesion primer necessary
- Multi adhesion
- Sanding control due to dark colour

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✓	✓	✓	✓	✓	✓

For industrial and professional use only.

PLASTIC PRO

Polyester – plastic putty



Art.-No.	Specification	SP	MOQ
149.613	1.0 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Plastic contour putty
- Colour: Black

AREA OF APPLICATION

- For filling small imperfections, dents and scratches on plastic surfaces

BENEFITS

- Outstanding adhesion on plastic surfaces
- No loss of adhesion in the transition zone
- No adhesion primer necessary
- Sanding control due to black colour

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✓	✓	✓

For industrial and professional use only.

FLEX

Polyester – plastic putty



Art.-No.	Specification	SP	MOQ
134.796	1.0 kg tin incl. hardener	1	12

DESCRIPTION

- Polyester putty
- Plastic contour putty
- Colour: Dark grey

AREA OF APPLICATION

- For filling small scratches and imperfections on plastic surfaces

BENEFITS

- Outstanding adhesion on plastic surfaces
- No loss of adhesion in the transition zone
- No plastic primer necessary

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✓	✓	✓

CARBO PUTTY

Polyester – carbon putty



Art.-No.	Specification	SP	MOQ
148.018	0.5 kg tin incl. hardener	1	12

DESCRIPTION

- Special polyester putty
- Fill and fine putty
- Colour: Transparent

AREA OF APPLICATION

- Base layer on horizontal CRP and wood surfaces to fill pores and imperfections
- Transparent base on carbon parts
- Can be applied directly to CRP

BENEFITS

- Provides a surface almost free of pores
- Self-levelling
- Minimizes the sanding time
- No sagging on carbon parts
- Improves the top coat quality

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

CARBO SPRAY

Polyester – sprayable putty for carbon parts



Art.-No.	Specification	SP	MOQ
148.019	0.820 kg tin incl. hardener	1	6

DESCRIPTION

- Special polyester putty
- Sprayable putty
- Colour: Transparent

AREA OF APPLICATION

- For filling small to deep imperfections, dents and scratches
- Transparent base on carbon parts
- Can be applied directly to CRP

BENEFITS

- Very high layer thickness possible
- Very even application by spray gun
- No sagging on carbon parts
- Improves the top coat quality

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

CARBO SPRAY THINNER

Carbo spray thinner



Art.-No.	Specification	SP	MOQ
148.234	1.0 l tin	1	6

DESCRIPTION

- Thinner

AREA OF APPLICATION

- Thinner for Carbo Spray

SPRAY

Polyester – sprayable putty



Art.-No.	Specification	SP	MOQ
127.978	1.5 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Sprayable putty
- Colour: Grey

AREA OF APPLICATION

- For filling deep imperfections, dents and scratches
- Cars, trucks and exhibition stand construction

BENEFITS

- Very high layer thickness possible
- Very even application by spray gun

APPLICATION ADVICE

We recommend to apply an isolating layer in advance (e.g. acrylic filler 35µ). This isolating layer must not be sanded through. This isolating layer avoids blistering in bad environmental conditions.

For industrial and professional use only.

SPRAY PLUS

Polyester – sprayable putty



Art.-No.	Specification	SP	MOQ
135.597	1.5 kg tin incl. hardener	1	6

DESCRIPTION

- Polyester putty
- Sprayable filler
- Colour: Light grey

AREA OF APPLICATION

- For filling deep imperfections, dents and scratches
- Cars, trucks and exhibition stand construction
- Additionally usable on CRP panels

BENEFITS

- Very high layer thickness possible
- Very even application by spray gun
- Optimized drying time and surface structure

APPLICATION ADVICE

We recommend to apply an isolating layer in advance (e.g. acrylic filler 35µ). This isolating layer must not be sanded through. This isolating layer avoids blistering in bad environmental conditions.

SPRAY THINNER

Thinner



Art.-No.	Specification	SP	MOQ
124.315	1.0 l tin	1	6

DESCRIPTION

- Thinner for CS Spray Filler and CS Spray Plus

AREA OF APPLICATION

- Thinner for polyester spray putty

BPO HARDENER

Hardener



Art.-No.	Specification	SP	MOQ
132.413	Red / 40 g	1	1

DESCRIPTION

- BPO hardener paste
- Colour: Red (standard hardener)

AREA OF APPLICATION

- Hardener for polyester putty

POLYESTER REPAIR RESIN

Polyester repair resin



Art.-No.	Specification	SP	MOQ
126.050	1,000 g incl. hardener	1	6

DESCRIPTION

- Polyester repair resin

AREA OF APPLICATION

- For processing of glass fibre fabric and mats, for repairing small holes in the surface
- For repairing GRP parts

1K NC FILLER

Nitrocellulose – filler



Art.-No.	Specification	SP	MOQ
158.139	Tube / 200 g	1	24

DESCRIPTION

- Nitrocellulose filler
- 1K Filler for application with a spatula
- Colour: Light grey

AREA OF APPLICATION

- For filling smallest imperfections, pinholes and stone chip damages

BENEFITS

- Fast drying
- Multi adhesion

POLYESTER REPAIR SET

Polyester repair set



Art.-No.	Specification	SP	MOQ
126.054	Set / 800 g	1	12

DESCRIPTION

- Polyester repair set
- Polyester resin, hardener and glass fibre mat
- Dimension of the glass fabric:
- 126.054 = 800 g Set: 125 x 40 cm

AREA OF APPLICATION

- For repairing small holes in the surface
- For repairing GRP parts

GLASS FIBRE REINFORCED PUTTY

Polyester – glass fibre reinforced putty



Art.-No.	Specification	SP	MOQ
124.036	250 g tin incl. hardener	1	12

DESCRIPTION

- Polyester putty
- Glass fibre reinforced putty
- Colour: Green

AREA OF APPLICATION

- For filling very deep imperfections
- Repairing treated rust spots and GRP parts
- Perfectly suitable for GRP repair

BENEFITS

- Extra long glass fibres

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

FILL PUTTY

Polyester – fill putty



Art.-No.	Specification	SP	MOQ
124.550	250 g tin incl. hardener	1	12
124.552	1,000 g tin incl. hardener	1	12

DESCRIPTION

- Polyester putty
- Fill putty
- Colour: Grey

AREA OF APPLICATION

- For filling deep to very deep imperfections, dents and scratches

BENEFITS

- Very high filling performance

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

FINE PUTTY

Polyester – fine putty



Art.-No.	Specification	SP	MOQ
124.124	250 g tin incl. hardener	1	12
124.126	1,000 g tin incl. hardener	1	12

DESCRIPTION

- Polyester putty
- Fine putty
- Colour: White

AREA OF APPLICATION

- For filling small to medium-sized imperfections, dents and scratches

BENEFITS

- Provides a very fine surface almost free of pores
- Minimizes the sanding time

STEEL	ALUMINIUM	GALVANIZED STEEL	GRP	PLASTICS	2 COMP. POLYESTER PUTTY	WOOD
✓	✗	✗	✓	✗	✓	✓

For industrial and professional use only.

GLASS FIBRE MAT

300 g per m²



Art.-No.	Specification	SP	MOQ
125.423	0.5 m²	1	12
125.424	1.0 m²	1	75

DESCRIPTION

- Glass fibre mat
- Weight: 300 g/m²

AREA OF APPLICATION

- For covering small holes in the surface on non-bearing parts

BENEFITS

- Stabilizes parts against tensile strength

APPLICATION ADVICE

Usable with polyester repair resin.

ALUMINIUM MESH

Aluminium repair mesh



Art.-No.	Specification	SP	MOQ
126.041	25 x 20 cm	1	200

DESCRIPTION

- Aluminium repair mesh

AREA OF APPLICATION

- Modelizing of forms before using glass fibre mats or glass fibre fabric

BENEFITS

- Simple handling of edged work pieces

APPLICATION ADVICE

Can be adapted to the form of the work piece by bending.Usable with glass fibre putties.

PUTTY KNIFE

Steel spreader



Art.-No.	Specification	SP	MOQ
137.435	60 mm	1	12
137.436	80 mm	1	12
137.437	100 mm	1	12

DESCRIPTION

- Steel spreader with a plastic handle

AREA OF APPLICATION

- For removing and mixing putties

BENEFITS

- Solvent resistant plastic handle

RUBBER SPREADER SET

Rubber spreader



Art.-No.	Specification	SP	MOQ
159.448	Set of 3 spatulas (90, 105 and 115 mm)	1	50

DESCRIPTION

- Spatula set in three widths: 90, 105 and 115 mm
- Soft rubber spatula

AREA OF APPLICATION

- For applying putty to extreme shapes
- Particularly suitable for curved surfaces, holes and cracks
- For mixing and applying putty

BENEFITS

- 3 sizes per set guarantee the right spatula size for every task
- Clean, straight edges for precise work
- Stiff and yet flexible

JAPANESE PUTTY KNIFE

Japanese steel spreader



Art.-No.	Specification	SP	MOQ
139.356	1 Set	1	100

DESCRIPTION

- Set of steel spreaders
- 4 steel spreaders (5, 8, 10 and 12 cm)

AREA OF APPLICATION

- For mixing and applying putty manually

BENEFITS

- Solvent resistant

BLACKY

Rubber spreader



Art.-No.	Specification	SP	MOQ
137.433	100 x 60 mm	10	10

DESCRIPTION

- Rubber plastic spreader

AREA OF APPLICATION

- For mixing and applying putty manually

BENEFITS

- Solvent resistant
- Extremely flexible

EASY CLEAN BOX

Putty spreader cleaning box



Art.-No.	Specification	SP	MOQ
153.206	Spreader cleaning device	1	2
159.363	Replacement fleece – 3 pcs.	1	100

DESCRIPTION

- Putty spreader cleaning box for reusable putty spreaders
- Solvent-resistant

AREA OF APPLICATION

- For fast and easy cleaning of steel, plastic or rubber putty spreaders

BENEFITS

- Closed container for reduced smell
- Significantly cleaner workplace

APPLICATION ADVICE

We recommend the Carsystem H₂O Cleaner for slower evaporation and less smell.

PLASTIC SPREADER

Plastic spreader



Art.-No.	Specification	SP	MOQ
146.961	115 x 77 mm	100	100

DESCRIPTION

- Plastic spreader

AREA OF APPLICATION

- For mixing and applying putty manually

BENEFITS

- Solvent-resistant
- Flexible

PUTTY MIX BOARD

Putty mix board



Art.-No.	Specification	SP	MOQ
142.206	100 tear-offs / 26 x 22 cm	1	10

DESCRIPTION

- Putty mix board
- 100 tear-offs

AREA OF APPLICATION

- Supporting plate to mix putty and hardener

BENEFITS

- Big area for mixing putty
- Easy disposal of the used tear-off
- No cleaning or sanding necessary

SPEEDMIXER 3 KG

Putty dispenser – electrical



Art.-No.	Specification	SP	MOQ
151.017	Speedmixer 3 kg	1	1
146.427	Mixing nozzles green (pack of 100 pcs.)	1	5
152.088	Multi Green slow – Speedmixer / green / 2,523 kg cartridge incl. hardener	6	6

DESCRIPTION

- Electrically operated putty dispenser
- For 3 kg putty cartridges

AREA OF APPLICATION

- Automatic dosing and mixing of filler and hardener

BENEFITS

- Perfect ratio between putty and hardener
- Avoids wrong dosage
- Bubble-free putty
- No hand mixing necessary

APPLICATION ADVICE

Manual pre-injection of hardener.

SPEEDMIXER 10 KG

Putty dispenser – electro-pneumatic



Art.-No.	Specification	SP	MOQ
143.347	Speedmixer 10 kg	1	1
146.955	Mixing nozzles / yellow / XL (pack of 100 pcs.)	1	5
143.810	Elastic weiss / very slow / 10 kg cartridge incl. hardener	2	2
144.131	Multi / beige / 9,63 kg cartridge incl. hardener	2	2
143.205	Multi / slow / beige / 9,61 kg cartridge incl. hardener	2	2
145.419	Multi / very slow / beige / 9,61 kg cartridge incl. hardener	2	2
146.808	Multi Light / slow / beige / 6,94 kg cartridge incl. hardener	2	2
147.451	Multi Light / super slow / beige / 6,94 kg cartridge incl. hardener	2	2
149.614	Multi Green / slow / green / 8,18 kg cartridge incl. hardener	2	2

DESCRIPTION

- Electro-pneumatic putty dispenser
- For 10 kg putty cartridges

AREA OF APPLICATION

- Automatic dosing and mixing of putty + hardener

BENEFITS

- Perfect ratio between putty and hardener
- Avoids wrong dosage
- Bubble-free putty
- No hand mixing necessary

APPLICATION ADVICE

Fully automatic dispensing of the putty.

PUTTY DISPENSER

Putty dispenser – pneumatic



Art.-No.	Specification	SP	MOQ
123.859	A 3C	1	1
123.840	A 10C	1	1
160.576	Repair Kit: Sealing ring / white plastic sealing plug	1	1

DESCRIPTION

- Pneumatic putty dispenser
- For 3 kg and 10 kg cartridges
- Wall mount

AREA OF APPLICATION

- Pneumatic dispensing of putty and hardener

BENEFITS

- Perfect ratio between putty and hardener
- Avoids wrong dosage

APPLICATION ADVICE

Wall mount only.

DUALMATIC

Putty dispenser – manual



Art.-No.	Specification	SP	MOQ
123.892	For 3 kg cartridges	1	1
126.854	Handle for Dualmatic	1	1
126.861	Cut off with handle	1	1

DESCRIPTION

- Dispenser for 3 kg putty cartridges
- Manual withdrawal
- Wallmounting is recommended

AREA OF APPLICATION

- Mobile putty dispenser, also suitable for table or wall mount

BENEFITS

- Perfect ratio between putty and hardener
- Avoids wrong dosage

APPLICATION ADVICE

Amount of hardener adjustable (summer / winter).

MASKING

TAPES AND MASKING FILMS FOR PRECISION IN PAINTING AND REPAIRS


The CARSYSTEM masking range protects your workspace fast and effective against wetness, dirt, and paint mist. We offer a huge product line of high-quality paint protection film, functional tapes and practical accessories for e.g. rims, vehicle sensors and steering wheels.

The CARSYSTEM masking films, packed as rolls, can be cut as needed without material surplus.

Discover the CARSYSTEM Foam Tape T-Soft which is outstanding to seal up splits and protect your car interior reliably against paint mist.

MASTER TAPE II

Masking tape



Art.-No.	Specification	SP	MOQ
140.201	15 mm x 50 m	60	60
140.202	19 mm x 50 m	48	48
140.203	25 mm x 50 m	36	36
140.204	30 mm x 50 m	28	28
140.205	38 mm x 50 m	24	24
140.206	50 mm x 50 m	24	24

DESCRIPTION

- High performance masking tape
- Highly solvent-resistant
- Waterproof
- Temperature-resistant up to 120 °C / 1 h

AREA OF APPLICATION


- All masking work especially at high temperatures

BENEFITS

- Very strong initial tack

TOP TAPE

Masking tape



Art.-No.	Specification	SP	MOQ
139.262	15 mm x 50 m	60	60
139.263	19 mm x 50 m	48	48
139.264	25 mm x 50 m	36	36
139.265	30 mm x 50 m	32	32
139.266	38 mm x 50 m	24	24
139.267	50 mm x 50 m	24	24

DESCRIPTION


- Standard masking tape
- Temperature-resistant up to 80 °C / 1 h

AREA OF APPLICATION

- Suitable for all standard masking work

MASTER TAPE GREEN

Masking tape



Art.-No.	Specification	SP	MOQ
149.221	19 mm x 50 m	48	48
149.222	25 mm x 50 m	36	36
149.223	30 mm x 50 m	28	28
149.225	38 mm x 50 m	24	24
149.226	50 mm x 50 m	24	24

DESCRIPTION

- All-around masking tape
- Solvent-resistant
- Waterproof
- Temperature-resistant up to 110 °C / 1 h

AREA OF APPLICATION


- Suitable for all standard masking work

BENEFITS

- Strong initial tack

SLIM TAPE

Special masking tape



Art.-No.	Specification	SP	MOQ
133.827	18 mm x 50 m	10	160

DESCRIPTION

- Special masking tape
- Special paper base
- Extremely thin
- Waterproof
- Temperature-resistant up to 100 °C / 1 h

AREA OF APPLICATION

- Suitable for difficult surfaces, e.g. rubber, plastics, door openers and chromed parts
- "Last tape" before painting

BENEFITS

- High curve stability
- Perfect cutting ability

RED TAPE

Masking tape

NEW



DESCRIPTION

- Water- and solvent-resistant masking tape
- Natural rubber adhesive
- Temperature-resistant all-around masking tape for all common painting applications

AREA OF APPLICATION

- Masking tape for all standard painting applications
- Suitable for bonding on painted metal, rubber and glass
- Designed for indoor use and short-term outdoor masking with clean removal within 3 days
- Solvent-resistant

BENEFITS


- Temperature-resistant up to 110 °C
- Extra-small roll core (Ø ~2.5 cm) – practical and space-saving handling
- Unique visibility (red color)
- Easy removal without adhesive residue
- Drying cycle: 90 °C (1 hr.) – 110 °C (30 min.)
- Excellent adhesive strength and fast bonding
- 3-day UV-resistance

Art.-No.	Specification	SP	MOQ
160.210	18 mm x 50 m	13	52
160.211	30 mm x 50 m	8	32
160.213	48 mm x 50 m	5	20



SLIM TAPE GREEN

Special masking tape



Art.-No.	Specification	SP	MOQ
150.081	18 mm x 18 m	8	200

DESCRIPTION

- Special masking tape
- Special paper base
- Extremely thin
- Waterproof
- Temperature-resistant up to 100 °C / 1 h

AREA OF APPLICATION


- Suitable for difficult surfaces, e.g. rubber, plastics, door openers and chromed parts
- "Last tape" before painting

BENEFITS

- Small and handy, fits into every pocket
- High curve stability
- Perfect cutting ability

FINE LINE TAPE BLUE

Fine line tape



Art.-No.	Specification	SP	MOQ
140.083	3 mm x 33 m	1	50
140.084	6 mm x 33 m	1	50
140.085	9 mm x 33 m	1	32
140.086	12 mm x 33 m	1	24
140.087	19 mm x 33 m	1	20

DESCRIPTION

- Fine line tape
- PVC base
- Waterproof
- Temperature-resistant up to 155 °C / 1 h
- Highly solvent-resistant

AREA OF APPLICATION

- Multi colour and design painting
- Masking of curves and long, straight lines
- Suitable for masking work on rubber and plastic surfaces

BENEFITS

- Highly flexible
- Does not stretch when unrolled

WR-LIFTING TAPE PREMIUM

Masking tape with plastic edge – perforated



Art.-No.	Specification	SP	MOQ
155.734	Perforated / 9 + 11 mm x 10 m	1	24

DESCRIPTION

- Special tape
- Perforated masking tape with a plastic edge
- Waterproof
- Temperature-resistant up to 120 °C / 1 h
- We recommend to tear off from plastic to tape

AREA OF APPLICATION

- For masking window sealings, lip seals, front and back lights and indicators

BENEFITS

- 2 in 1, length wise perforated masking tape with a plastic edge in 9 mm and 11 mm
- Tape and plastic edge are perforated for easy tear-off
- Paint edge disappears under the sealing

SILVER TAPE

Fabric tape



Art.-No.	Specification	SP	MOQ
135.715	50 mm x 50 m	1	18

DESCRIPTION

- Fabric tape
- Waterproof
- Temperature-resistant up to 80 °C / 3 h

AREA OF APPLICATION

- Usable for different masking work
- Sanding edge protection
- Support tape for glued parts

BENEFITS

- High adhesion on a multitude of surfaces

WR-LIFTING TAPE

Masking tape with plastic edge



Art.-No.	Specification	SP	MOQ
155.720	9 mm x 10 m	1	24

DESCRIPTION

- Special tape
- Masking tape with a plastic edge
- Waterproof
- Temperature-resistant up to 120 °C / 1 h

AREA OF APPLICATION

- For masking window sealings, lip seals, front and back lights and indicators

BENEFITS

- Paint edge disappears under the sealing

BLACK TAPE

Fabric tape



Art.-No.	Specification	SP	MOQ
147.753	50 mm x 50 m	1	18

DESCRIPTION

- Fabric tape
- Waterproof
- Temperature-resistant up to 80 °C / 3 h

AREA OF APPLICATION

- Usable for different masking work
- Sanding edge protection
- Support tape for glued parts

BENEFITS

- High adhesion on a multitude of surfaces

MASKING PAPER MASTER II

Masking paper – Roll



Art.-No.	Specification	SP	MOQ
159.878	20 cm x 450 m	1	150
159.880	60 cm x 450 m	1	60
159.882	90 cm x 450 m	1	37
159.883	120 cm x 450 m	1	30
159.884	150 cm x 450 m	1	30

DESCRIPTION

- Special masking paper
- Robust
- Solvent-resistant
- Free of PFAS (Barrier through mechanical processing of the paper fiber)
- 40 g/m²

AREA OF APPLICATION

- Masking paper for all masking work

MASKING PAPER TOP II

Masking paper – Roll



Art.-No.	Specification	SP	MOQ
155.528	20 cm x 450 m	1	150
155.529	60 cm x 450 m	1	60
155.530	90 cm x 450 m	1	37
155.531	120 cm x 450 m	1	30
155.532	150 cm x 450 m	1	30

DESCRIPTION

- Standard masking paper
- Sealed on one side
- Tight
- 40 g/m²

AREA OF APPLICATION

- Standard masking paper for all masking work

EASY MASK II

Masking film transparent – Roll

NEW



DESCRIPTION

- Standard transparent masking film
- Protected from dust in a dispenser box
- Roll core: ø 38 mm
- Thickness: 10 µm

AREA OF APPLICATION

- For all necessary masking work in a paint shop
- Masking film for cars and car parts

BENEFITS

- The film is stored in a dispenser box, protected from dust
- The film is transparent to ensure precise cutting
- Due to its static properties, the film adheres firmly to the vehicle
- The film provides paint adhesion
- Easy to cut
- 120°C temperature resistance

APPLICATION ADVICE

Carsystem EASY MASK II should not be used on wet or dirty surfaces.

Art.-No.	Specification	SP	MOQ
160.434	4 x 150 m	1	66
160.435	5 x 120 m	1	45



WM TAPE

Adhesive Tape



Art.-No.	Specification	SP	MOQ
140.794	50 mm x 66 m	6	36

DESCRIPTION

- Packaging tape

AREA OF APPLICATION

- For sealing packages



MASKING FILM YELLOW

Masking film – Roll



Art.-No.	Specification	SP	MOQ
155.572	400 cm x 200 m (middle folding)	1	28
155.573	500 cm x 120 m (middle folding)	1	28
156.948	600 cm x 100 m (middle folding)	1	28

DESCRIPTION

- Premium masking film
- Extremely thick
- Paint adhesive
- Strongly static
- Correction of masking tape possible
- Heat-resistant up to 110 °C
- Dust protected in a cardboard box
- Thickness: 17µm

AREA OF APPLICATION

- Premium masking film for all masking work

BENEFITS


- Vehicles with residual moisture
- Extremely tear-proof
- Perfect cutting ability
- Avoids water marks from residual moisture
- Highly static
- One man use
- Sticks perfectly on the car and can be applied wrinkle-free
- The strong static avoids overspray from crawling under the film

APPLICATION ADVICE

Due to the high static we recommend when repositioning, to lift the whole film off the car and re-place it. Very high static properties. For repositioning, we recommend to lift the film with two persons.

MASKING FILM BLUE

Masking film – Roll



Art.-No.	Specification	SP	MOQ
155.570	400 cm x 150 m (middle folding)	1	28
155.569	400 cm x 300 m (middle folding)	1	18
155.571	500 cm x 120 m (middle folding)	1	28

DESCRIPTION

- Paint adhesive
- Strongly static
- Heat-resistant up to 110 °C
- Dust protected in a cardboard box
- Thickness: 13 µm

AREA OF APPLICATION

- Vehicles with residual moisture

BENEFITS

- Highly static
- One man use
- Sticks perfectly on the car and can be applied wrinkle-free
- The strong static avoids overspray from crawling under the film
- Avoids water marks from residual moisture

APPLICATION ADVICE

Due to the high static we recommend when repositioning, to lift the whole film off the car and re-place it. Very high static properties. For repositioning, we recommend to lift the film with two persons.

MASKING FILM GREEN

Masking film – Roll



Art.-No.	Specification	SP	MOQ
155.565	400 cm x 300 m (middle folding)	1	28
155.567	500 cm x 120 m (middle folding)	1	45
155.568	600 cm x 100 m (middle folding)	1	28

DESCRIPTION

- Standard masking film
- Paint adhesive
- Strongly static
- Heat-resistant up to 110 °C
- Dust protected in a cardboard box
- Thickness: 11 µm

AREA OF APPLICATION

- Standard masking film for all masking work

BENEFITS

- Highly static
- One man use
- Sticks perfectly on the car and can be applied wrinkle-free
- The strong static avoids overspray from crawling under the film

APPLICATION ADVICE

Due to the high static we recommend when repositioning, to lift the whole film off the car and re-place it. Very high static properties. For repositioning, we recommend to lift the film with two persons.

AUTO MASK

Handy masking film incl. tape



Art.-No.	Specification	SP	MOQ
125.476	Refill-roll 0.55 x 33 m	1	40
125.517	Refill-roll 1.80 x 33 m	1	20
133.060	Refill-roll 2.70 x 20 m	1	20

DESCRIPTION

- Masking film with integrated adhesive tape
- Paint adhesive
- Static
- Thickness: 8 µm

AREA OF APPLICATION

- For masking windows, bumpers and sills
- Manual use

MMIR KNIFE PREMIUM

Cutter tool



Art.-No.	Specification	SP	MOQ
151.513	Film knife	2	2

DESCRIPTION

- Cutter tool for plastic film
- Coated blade

AREA OF APPLICATION

- For cutting plastic film

BENEFITS

- Reduced risk of injury thanks to the embedded blade

Self-adhesive protective covering film

DESCRIPTION

- Tear-resistant, extremely durable protective and fixing film
- Dimensions: 75 cm × 60 m
- Thickness: 75 µm
- Self-adhesive
- Adheres to many surfaces
- UV-resistant
- Interior protection

AREA OF APPLICATION

- Effective and clever protection against all parts of cars that have been in accidents, partially dismantled or damaged by vandalism
- All necessary covering work in the automotive sector
- Emergency fastening and securing of car parts

BENEFITS

- Versatile
- UV-resistance for up to 6 months
- Removes without leaving any residue after use
- Strong adhesive strength

APPLICATION ADVICE

Carsystem Crash Film achieves the best adhesion on surfaces that are free from oil, grease, dust and solvents.



Art.-No.	Specification	SP	MOQ
160.381	75 cm x 60 m	1	1



For industrial and professional use only.

Surface Protection Film – 60 cm x 20 m

Art.-No.	Specification	SP	MOQ
158,145	60 cm x 20 m	1	1

DESCRIPTION

- Surface protection film
- Self-adhesive
- Structured surface with an anti-slip effect
- Thickness: 240 µm

AREA OF APPLICATION

- Protective film for areas, which need protection against dirt, moisture, paint, oils
- Floors or surfaces in paint mixing rooms
- For smooth and rough surfaces such as wood or concrete
- Aircraft wings during repair and maintenance

BENEFITS

- Resistant to chemicals and solvents
- Recyclable
- Can be easily applied and removed without leaving any residue

APPLICATION ADVICE

Only for indoor use (no weather resistance). The protective film SPF is not antistatic. We recommend checking the suitability very carefully when using in ATEX areas.

Foam tape



Art.-No.	Specification	SP	MOQ
157.974	25 m	1	300

DESCRIPTION

- Special foam tape
- Silicone-free glue
- Temperature-resistant up to 80 °C / 1h

AREA OF APPLICATION

- For closing gaps on doors, bonnets and trunk lids
- Protects inner areas from overspray

BENEFITS

- Avoids hard paint edges
- Easy placement
- Perfect edge finish
- No glue residues

FOAM TAPE

Foam tape



Art.-No.	Specification		MOQ
148.861	13 mm x 50 m	1	140
148.862	19 mm x 35 m	1	84

DESCRIPTION

- Foam tape
- Silicone-free glue
- Temperature-resistant up to 80 °C / 1h

AREA OF APPLICATION

- For closing gaps on doors, bonnets and trunk lids
- Protects inner areas from overspray

BENEFITS

- Avoids hard paint edges

ALL IN ONE COVERS

Interior protection 5-in-1



Art.-No.	Specification		MOQ
159.480	880 x 1500 mm / set	1	1

DESCRIPTION

- Vehicle interior protection set with 5 components for: seat, footwell, steering wheel, gear shifter and handbrake
- 200 sets on a roll

AREA OF APPLICATION

- Covering the vehicle interior during repair and service work
- For protection against water, dirt, dust, oil and paint

BENEFITS

- Suitable for all car interiors
- Comes in a practical dispenser box
- Set solution saves storage space and time

PDC EASY PAINT

Painting assistant for parking sensors



Art.-No.	Specification		MOQ
159.500	5 pcs. per set	1	24

DESCRIPTION

- Painting solution for painting parking sensors (PDCs)
- Solvent-resistant
- Magnets provide safe drying after painting (e.g. paint stand, spray booth wall, etc.)
- 5 pcs. painting boxes, 2 pcs. magnets, 1 piece of foam (spacer)

AREA OF APPLICATION

- Painting solution for commercially available parking sensors with a diameter of 18 mm

BENEFITS

- Time-saving masking of park distance sensors (Not every single sensor needs to be masked)
- Ideal drying due to the magnetic fastening option of the painting box

WHEEL COVER

Cover hood



Art.-No.	Specification		MOQ
142.483	17 inches / 1 pack = 4 pcs.	4	56
158.211	20-21 inches / 1 pack = 4 pcs.	4	56

DESCRIPTION

- Cover hood for car wheels
- Paint and heat protection
- Aluminum sealed fabric
- Dustproof
- Waterproof

AREA OF APPLICATION

- Fast masking of wheels before painting
- Protects car wheels from dust and overspray

For industrial and professional use only.

TEC LINE STICK

Sensor pad



Art.-No.	Specification	SP	MOQ
152.554	150 pcs. / box / 18 mm	1	50

DESCRIPTION

- Covers for parking sensors
- PET plastic
- Temperature-resistant: -40 °C up to +180 °C
- Solvent-resistant

AREA OF APPLICATION

- For covering parking sensors or key holes
- Protection against sanding, painting and polishing

BENEFITS

- Time-saving
- No dismantling of parking sensors

APPLICATION ADVICE

We recommend to remove the sensor cover while the paint is still liquid to avoid paint edges.

For industrial and professional use only.

LIQUID MASKING

Liquid masking film



Art.-No.	Specification	SP	MOQ
138.718	19 L	1	1

DESCRIPTION

- Liquid masking film
- Detergent included
- Water-based
- Water-soluble
- Solvent-resistant
- Colour: Transparent - red

AREA OF APPLICATION

- Protects the vehicle from overspray, polishing splashes, dust and slight mechanical damage

BENEFITS

- Less waste
- Car can be moved safely in the work shop

APPLICATION ADVICE

We recommend the application with a new filler gun. Nozzle: 1.9 - 2.2 mm.

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

PAINTING

CLEAR COATS, FILLERS AND 1K SPRAYS FOR THE CAR PAINTER

Professional painting guaranteed – CARSYSTEM has built up a large range of high-quality clear coats, fillers and thinners over the years.

The associated complementary products, such as our popular CPS system, simplify painting and lead to perfect results on the vehicle. From spot repair to complete painting, whether matt or glossy – CARSYSTEM offers a wide range of products for all areas of application in bodyshops.

Discover our versatile product range, including 2K clear coat with highest UV protection suitable for carbon fiber, the CARSYSTEM UV or acrylic fillers, as well as thinners in a wide variety of versions. Convince yourself of the high quality and an optimal result on the vehicle.



2K CLEAR VOC SPEED PLUS

2K Clear coat



Art.-No.	Specification	SP	MOQ
152.563	A+B comp. / 1.5 L	1	12
151.899	A-comp. / 5.0 L	1	4
151.901	Hardener / 2.5 L	1	4

DESCRIPTION

- 2K Acrylic clear coat
- Premium quality
- VOC-compliant

AREA OF APPLICATION

- All common paint works from spot repair to full vehicle

BENEFITS

- Very fast drying
- Brilliant gloss
- Very good surface quality
- Very user friendly
- Extremely wear-resistant

DRYING TIME

- 15 min / 60 °C object temperature

APPLICATION ADVICE

We recommend a fast and efficient way of working for complete paint jobs.

2K CARBO CLEAR PLUS

2K Carbo clear coat



Art.-No.	Specification	SP	MOQ
153.217	A-comp. / 1 L	1	12
153.218	Hardener / 0.5 L	1	12
153.207	A-comp. / 5 L	1	4
153.208	Hardener / 2.5 L	1	4

DESCRIPTION

- 2K Acrylic clear coat
- Premium clear coat for carbon surfaces
- VOC-compliant

AREA OF APPLICATION

- Special clear coat for carbon parts

BENEFITS

- Very fast drying time
- Brilliant gloss
- Very good surface quality
- Very user-friendly
- Extremely wear-resistant
- High UV protection

DRYING TIME

- 15 min. / 60 °C object temperature

For industrial and professional use only.

CC.21 X-PRESS FIVE

2K Clear coat



Art.-No.	Specification	SP	MOQ
158.251	A+B comp. / 1.5 L	1	12
158.249	A-comp. / 5 L	1	4
158.250	Hardener / 2.5 L	1	4

DESCRIPTION

- 2K Acrylic clear coat
- Premium quality
- VOC-compliant

AREA OF APPLICATION

- For small to medium paint work

BENEFITS

- Extremely fast drying time
- Excellent gloss and flow properties
- Very user-friendly
- Very good surface quality

DRYING TIME

- 15 – 20 min / 40 °C object temperature

For industrial and professional use only.

CC.20 X-PERT

2K Clear coat



Art.-No.	Specification	SP	MOQ
158.423	A + B comp. / 1.5 L	1	12
157.450	A-comp. / 5 L	1	4
157.451	Hardener / 2.5 L	1	4

DESCRIPTION

- 2K Acrylic clear coat
- All-purpose clear coat
- VOC-conform

AREA OF APPLICATION

- All common paint work in a paint shop from individual parts up to full vehicle paintings

BENEFITS

- Fast drying time
- Very high final hardness
- Brilliant gloss

DRYING TIME

- 20 – 25 min. / 40 °C object temperature

APPLICATION ADVICE

We recommend a fast and efficient way of working for complete paint jobs.

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

2K CLEAR VOC CC.25 HS-AS

2K Clear coat

DESCRIPTION

- 2K HS acrylic lacquer
- Developed for use on solvent- and water-based base coats

AREA OF APPLICATION

- Suitable for painting individual parts as well as entire vehicle sections.

BENEFITS

- Particularly user-friendly
- Very high gloss level
- Excellent flow properties on vertical surfaces
- Suitable for all types of repairs

DRYING TIME

- 15 min / 60 °C object temperature
- 25 – 30 min / 40 °C object temperature

APPLICATION ADVICE

It is strongly recommended to work within the system. When using non-system thinners or hardeners, drying and adhesion issues cannot be ruled out.



Art.-No.	Specification	SP	MOQ
160.417	A+B comp. / 1.5 L / standard	1	12
160.418	A+B comp. / 1,5 L / fast	1	12
160.419	A-comp. / 5.0 L	1	4
160.420	Hardener / 2,5L / standard	1	4
160.422	Hardener / 2,5L / fast	1	4

2K CLEAR VOC CC.26 ECO-X 15/60

2K Clear coat

DESCRIPTION

- 2K acrylic lacquer

AREA OF APPLICATION

- VOC-compliant clear coat is suitable for coating individual parts as well as complete vehicle sections, such as front ends

BENEFITS

- Fast drying
- Excellent flow properties
- High final hardness and outstanding scratch resistance
- Very high gloss level
- Resistant to runs
- User-friendly

DRYING TIME

- 15 min / 60 °C object temperature
- 3 – 4 h / 20 °C object temperature

APPLICATION ADVICE

It is strongly recommended to use the product within the specified system. When using thinners and hardeners from other manufacturers or non-system products, drying and adhesion problems cannot be ruled out.



Art.-No.	Specification	SP	MOQ
160.613	A+B Comp. / 1,5 L	1	12
160.614	A-comp. / 5 L	1	4
160.615	Hardener / 2,5 L	1	4



For industrial and professional use only.



For industrial and professional use only.



2K CLEAR VOC MATT

2K Clear coat matt



Art.-No.	Specification	SP	MOQ
148.983	A-comp. / matt / 1.0 L	1	12
148.986	A-comp. / silk-matt / 1.0 L	1	12
148.985	Hardener standard / 0.5 L	1	12
148.984	Hardener fast / 0.5 L	1	12

DESCRIPTION

- 2K Acrylic clear coat matt
- Matt level: Matt – 148.983
- Matt level: Silk-matt – 148.986
- VOC-compliant

DRYING TIME

- 30 min / 60 °C object temperature (hardener standard)

ACTIVATOR

Reaction accelerator



Art.-No.	Specification	SP	MOQ
147.695	1 L	1	12

DESCRIPTION

- Reaction accelerator additive

AREA OF APPLICATION

- Additive to speed up the drying process of Carsystem fillers and clear coats
- Max. addition in fillers: 10 %
- Max. addition in clear coats: 2 %

BENEFITS

- Accelerates the drying time about 15 %

APPLICATION ADVICE

Only usable with standard or slow hardeners to avoid adhesion problems or matting.

ACRYL THINNER

Acrylic thinner



Art.-No.	Specification	SP	MOQ
153.171	Slow / 5 L	1	4
150.331	Standard / 1 L	1	12
141.479	Standard / 5 L	1	4
152.456	Fast / 5 L	1	4

DESCRIPTION

- Acrylic thinner
- Colour: Transparent

AREA OF APPLICATION

- For all Carsystem fillers and clear coats

HIGH GLOSS ADDITIVE

High-gloss additive



Art.-No.	Specification	SP	MOQ
152.788	1 L	1	12

DESCRIPTION

- High-gloss additive
- Colour: Transparent

AREA OF APPLICATION

- Additive for all Carsystem clear coats

BENEFITS

- Improves gloss and surface quality

APPLICATION ADVICE

Mix High Gloss Additive and A-component first before adding the hardener to avoid adhesion problems.

SPOTBLENDER

Blending thinner



Art.-No.	Specification	SP	MOQ
148.989	1 L	1	12

DESCRIPTION

- Blending thinner

AREA OF APPLICATION

- For homogeneous transition zones between old and new paint for 1K and 2K clear coats and 2K top coats

EF.21 EP-FILLER

2K Hybrid filler



Art.-No.	Specification	SP	MOQ
158.248	A+B comp. / 1.5 L	1	12

DESCRIPTION

- 2K Hybrid filler – acrylic / epoxy
- Universal filler
- Colour: Yellowish (approx. RAL 7032)
- VOC-compliant

AREA OF APPLICATION

- All common filling works from spot repair to full vehicle
- Adhesion to steel, aluminium, KTL, old and new coatings on and under polyester puttys

BENEFITS

- Settable as wet on wet
- High corrosion resistance
- Excellent sandability
- Chromate-free

DRYING TIME

- Standard: 30 min / 60 °C object temperature
- Wet-on-wet: 30 min / 20 °C object temperature

AF.21 X-PERT

2K Acrylic filler



Art.-No.	Specification	SP	MOQ
158.216	A-comp. / white / 3.6 L	1	4
158.218	A-comp. / grey / 3.6 L	1	4
158.219	A-comp. / black / 3.6 L	1	4
158.220	Hardener / 0.9 L	1	4
158.221	Thinner standard / 1 L	1	12
159.237	Thinner Multi Wet-On-Wet / 1 L	1	12
160.315	Thinner Air Dry Additive / 1 L	1	12

DESCRIPTION

- 2K Acrylic filler
- Universal filler
- VOC-compliant

AREA OF APPLICATION

- All common filling works from spot repair to full vehicle
- Very good adhesion to steel, aluminium, e-coat primers, plastic (wet on wet application) and polyester fillers
- Painting new parts with e-coat primers
- Anti-corrosion protection

BENEFITS

- Settable as wet-on-wet
- Excellent sandability
- Layer thickness can be flexibly adjusted (from low to very high layer thickness)
- Application on e-coat primers without sanding
- Also adheres to plastic in wet-on-wet setting

DRYING TIME

- Standard: 25 min. / 60 °C object temperature
- Wet-on-wet: 25 min. / 20 °C object temperature

AF.21 1K FILLER

1K Hybrid filler



Art.-No.	Specification	SP	MOQ
158.244	Grey / 1 L	1	12
158.245	Thinner / 1 L	1	12

DESCRIPTION

- 1K Hybrid filler – acrylic / epoxy
- VOC-compliant
- Colour: Grey

AREA OF APPLICATION

- For isolating putty spots
- Painting of new parts
- Filling of plastic parts with direct adhesion without applying a primer first (except PE & PP)

BENEFITS

- 100% rust protection
- Very user-friendly
- Very good sandability

DRYING TIME

- 10 min / 60 °C object temperature

2K FILLER AIR PLUS

2K Acrylic filler



Art.-No.	Specification	SP	MOQ
152.580	A + B comp. / grey / 1.25 L	1	12
152.416	A-comp. / white / 3.6 L	1	4
152.417	A-comp. / grey / 3.6 L	1	4
152.418	A-comp. / black / 3.6 L	1	4
152.419	Hardener / 0.9 L	1	12

DESCRIPTION

- 2K Acrylic filler
- VOC-compliant

AREA OF APPLICATION

- Perfectly suitable for small parts, spot repair and air drying
- All common paint works from spot repair to full vehicle

BENEFITS

- Fast air-drying
- Very good sandability

DRYING TIME

- 15 – 20 min / 60 °C object temperature

2K VOC FILLER 540

2K Acrylic filler



Art.-No.	Specification	SP	MOQ
144.541	A+B comp. / hardener very fast / white / 1.25 L	1	12
144.539	A+B comp. / hardener very fast / grey / 1.25 L	1	12
144.540	A+B comp. / hardener very fast / black / 1.25 L	1	12
144.354	A-comp. / white / 3.6 L	1	4
144.026	A-comp. / grey / 3.6 L	1	4
144.353	A-comp. / black / 3.6 L	1	4
144.977	Hardener VOC 541 / standard / 0.9 L	1	12
144.027	Hadener very fast / 0.9 L	1	12

DESCRIPTION

- 2K Acrylic filler
- Universal filler
- VOC-compliant

AREA OF APPLICATION

- All common paint works from spot repair to full vehicle

BENEFITS

- High filling power
- Variable due to three different hardeners
- Winter hardener CT available for low temperatures (cold temperature)

DRYING TIME

- 30 – 45 min / 60 °C object temperature (hardener standard)

For industrial and professional use only.

2K FILLER VARIO PLUS

2K Acrylic filler



Art.-No.	Specification	SP	MOQ
152.058	A+B comp. / light grey / 1.2 L	1	12
152.057	A-comp. / light grey / 3.5 L	1	4
147.682	Hardener / 0.7 L	1	12

DESCRIPTION

- 2K Acrylic filler
- High build filler
- Colour: Light grey
- VOC-compliant

AREA OF APPLICATION

- All common paint works from spot repair to full vehicle
- Also usable as a high build filler
- Filler: 60 to 180 µ
- High build filler: 85 to 255 µ

BENEFITS

- Very high filling power
- The filler can be variably adapted by adding up to 30 % thinner

DRYING TIME

- Normal layer: 30 – 35 min / 60 °C object temperature
- High build: 45 min / 60 °C object temperature

For industrial and professional use only.

TINTING PASTE FILLER

Tinting paste



Art.-No.	Specification	SP	MOQ
148.505	Red / 0.5 L	1	30
148.504	Black / 0.5 L	1	30

DESCRIPTION

- Tinting paste

AREA OF APPLICATION

- Tinting paste for Carsystem acrylic fillers
- Max. addition: 1 – 5 %

BENEFITS

- For matching the filler to the basecoat shade

APPLICATION ADVICE

Mix tinting paste and A-component first before adding the hardener to avoid adhesion problems.



AF.25 PRIMER WET ON WET

2K Acryl filler

NEW



Art.-No.	Specification	SP	MOQ
160.263	A+B comp. / white / 1,0 L	1	12
160.262	A+B comp. / grey / 1,0 L	1	12
160.261	A+B comp. / black / 1,0 L	1	12
160.267	A-comp. / grey / 3,0 L	1	4
160.265	A-comp. / black / 3,0 L	1	4
160.268	B-comp. / 1,0 L	1	4

DESCRIPTION

- 2K Acrylic Wet-on-Wet Primer

AREA OF APPLICATION

- The primer can be used on steel, aluminum, galvanized surfaces, e-coated (KTL) parts, and various plastics (ABS, PA6, PP/EPDM, PC, PVC).

BENEFITS

- Very easy to apply
- Low material consumption due to excellent flow characteristics
- Smooth and satin-matte finish
- No impact on the final appearance of the clear coat (no sanding marks, shrinkage, orange peel, etc.)
- Corrosion protection

DRYING TIME

- Wet-on-wet: 20 min. / 20°C object temperature

For industrial and professional use only.

HPP PRIMER

1K Plastic primer



Art.-No.	Specification	SP	MOQ
154.706	White / 1 kg	1	6
154.707	Grey / 1 kg	1	6
154.708	Black / 1 kg	1	6
154.712	Thinner / 1 L	1	12

DESCRIPTION

- 1K Plastic primer
- Special primer
- Wet-on-Wet primer for plastic parts

AREA OF APPLICATION

- Prior to painting of solvent resistant uncoated plastic parts (e.g. PP, PVC, EPP, PP-EPDM)

BENEFITS

- Extremely time-saving
- No pretreatment of the plastic surfaces necessary
- Cleaning with alcohol-based plastic cleaner is mandatory

DRYING TIME

- Wet-on-wet: 15 min / 20 °C object temperature

APPLICATION ADVICE

We recommend the Carsystem ISO-VE 7030 cleaner for cleaning the plastic parts. Not suitable for PE/PC.

For industrial and professional use only.

2K CARBO FILLER
TRANSPARENT 1,0

2K Polyurethane Filler



Art.-No.	Specification	SP	MOQ
157.988	A – Comp. / transparent / 1,0 L	12	12
157.989	B – Comp. / 0,7 L	12	12

DESCRIPTION

- 2K Polyurethane filler
- High transparent carbon filler
- VOC-compliant

AREA OF APPLICATION

- All common filler work on carbon parts

BENEFITS

- High filling power
- Very good sandability
- Low marking of the matrix
- UV-resistant

DRYING TIME

- 60 min. / 60°C object temperature
- 30 min. / 80°C object temperature

APPLICATION ADVICE

Note: The maximum total film thickness should not exceed 180 µm, corresponding to a maximum of three coats of approximately 60 µm each when using a 1.6 mm nozzle size. If the total film thickness exceeds 180 µm, the filler may take on a milky or cloudy appearance during application or drying. This optical effect is temporary and will disappear after complete drying and subsequent sanding.

To ensure optimal coating results, it is strongly recommended to strictly follow the application instructions and specified film thickness guidelines.

UV CLEAR

Transparent UV Clear coat



Art.-No.	Specification	SP	MOQ
154.528	100 ml	1	20

DESCRIPTION

- UV clear coat
- Clear coat for dip application
- VOC-compliant
- Colour: Transparent

AREA OF APPLICATION

- Filling of pinholes, small scratches and stone chips in the clear coat

BENEFITS

- Extremely time-saving
- Perfect solution for spot repairs

DRYING TIME

- 30 – 60 sec. (CS UV lamps)

2K HIGH-SPEED KLARLACK

2K Spot-repair clear coat



Art.-No.	Specification	SP	MOQ
149.421	400 ml	1	6

DESCRIPTION

- 2K Acrylic clear coat spray
- Colour: Transparent

AREA OF APPLICATION

- For painting small parts
- Especially suitable for spot repair

BENEFITS

- No spray gun application necessary
- Very fine atomisation
- Long pot life (approx. 24 h after activation)

CLEAR COAT SPRAY

Paint spray – transparent



Art.-No.	Specification	SP	MOQ
126.025	400 ml	1	12

DESCRIPTION

- 1K Clear coat spray
- Colour: Transparent-glossy

AREA OF APPLICATION

- Spot repair

BENEFITS

- Fast drying and polishable

SPOTBLENDER SPRAY

Blending thinner spray



Art.-No.	Specification	SP	MOQ
145.987	400 ml	1	12

DESCRIPTION

- Blending thinner spray
- Colour: Transparent

AREA OF APPLICATION

- For homogeneous transition zones in the blending area of 1K and 2K clear coats as well as top coats

BENEFITS

- No spray gun application necessary

RALLYE-SPRAY PREMIUM

Paint spray – black glossy



Art.-No.	Specification	SP	MOQ
149.219	500 ml	1	6

DESCRIPTION

- Acrylic paint spray
- Colour: Black glossy

AREA OF APPLICATION

- Repair of imperfections in the paint
- Paint application on new parts

BENEFITS

- High opacity
- Fast drying
- Polishable

RALLYE-SPRAY PREMIUM

Paint spray – black matt



Art.-No.	Specification	SP	MOQ
149.218	500 ml	1	6

DESCRIPTION

- Acrylic paint spray
- Colour: Black matt

AREA OF APPLICATION

- Repair of imperfections in the paint
- Paint application on new parts

BENEFITS

- High opacity
- Fast drying

For industrial and professional use only.

RALLYE-SPRAY GLOSS

Paint spray – gloss



Art.-No.	Specification	SP	MOQ
126.053	White glossy / 400 ml	1	12
126.026	Black glossy / 400 ml	1	12

DESCRIPTION

- Acrylic paint spray

AREA OF APPLICATION

- Repair of imperfections in the paint

BENEFITS

- Fast drying
- Polishable

For industrial and professional use only.

RALLYE-SPRAY MATT

Paint spray – matt



Art.-No.	Specification	SP	MOQ
126.027	400 ml	1	12

DESCRIPTION

- Acrylic paint spray
- Colour: Black matt

AREA OF APPLICATION

- Repair of imperfections in the paint

BENEFITS

- Fast drying

THERMO-SPRAY

Paint spray – heat resistant



Art.-No.	Specification	SP	MOQ
126.086	Black / 400 ml	1	12
126.087	Silver / 400 ml	1	12

DESCRIPTION

- Silicone resin-based paint spray
- Temperature resistant up to 650 °C

AREA OF APPLICATION

- Protects parts in the engine compartment and exhaust pipes

BENEFITS

- Extremely high temperature resistance

SILVER WHEEL

Silver wheel spray



Art.-No.	Specification	SP	MOQ
126.021	400 ml	1	12

DESCRIPTION

- Acrylic paint spray
- Colour: Silver

AREA OF APPLICATION

- For painting steel rims

BENEFITS

- Abrasion-resistant
- Weather-resistant

For industrial and professional use only.

2K EPOXY FILL PRIMER

2K Spot-repair epoxy primer



Art.-No.	Specification	SP	MOQ
159.158	Beige / 400 ml	1	6

DESCRIPTION

- 2K Epoxy filler spray
- Colour: Beige

AREA OF APPLICATION

- For priming small parts
- Especially suitable for spot repair

BENEFITS

- Variable spray nozzle
- Perfect adhesion and rust protection properties
- Free of isocyanate

For industrial and professional use only.

PRIMER SURFACING SPRAY

Primer spray



Art.-No.	Specification	SP	MOQ
126.024	400 ml	1	12

DESCRIPTION

- Primer spray
- Nitro-combi-based
- Colour: Grey

AREA OF APPLICATION

- Primer for all paint works

BENEFITS

- Good rust protection properties
- Weather-resistant

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-
SEALING

CLEANING

PERSONAL
SAFETY

PAINTING
SUPPLIES

PRIMER SPRAY

Primer spray



Art.-No.	Specification	SP	MOQ
125.949	Red brown / 400 ml	1	12
132.907	Grey / 400 ml	1	12

DESCRIPTION

- Primer spray
- Alkyd resin-based

AREA OF APPLICATION

- Primer for all paint works

BENEFITS

- Very good rust protection properties

ETCH PRIMER

Primer



Art.-No.	Specification	SP	MOQ
143.028	400 ml	1	6

DESCRIPTION

- Rust protection spray
- Colour: Grey

AREA OF APPLICATION

- Specific for repairing of original primers on aluminum car bodies
- Isolating of sanded trough spots
- Adhesion promoter on all steel, zinc and aluminum substrates for spot and partial paintings

BENEFITS

- Easy to use
- Fast flash-off and drying time

ZINC SPRAY

Rust protection



Art.-No.	Specification	SP	MOQ
126.030	400 ml	1	12

DESCRIPTION

- Rust protection spray
- Colour: Grey
- Temperature resistant up to 490 °C (acc. DIN50976, 53167, 50021, 53151)

AREA OF APPLICATION

- Rust protection for the body interior in spot welding
- Cold galvanizing of metal surfaces

SPRAY FILLER SPRAY

Spray filler



Art.-No.	Specification	SP	MOQ
125.580	400 ml	1	12

DESCRIPTION

- Spray putty aerosol
- Acryl-based
- Colour: Grey

AREA OF APPLICATION

- Levelling of small imperfections and isolating polyester putty layers

BENEFITS

- Outstanding filling power
- Short drying time
- Quickly sandable

1K EPOXY PRIMER

1K Epoxy primer



Art.-No.	Specification	SP	MOQ
151.958	400 ml	1	12

DESCRIPTION

- 1K Epoxy primer spray
- Colour: Grey

AREA OF APPLICATION

- Spot and partial paintings
- Isolating of sanded-through spots
- Overpaintable with water- and solvent-based paints

BENEFITS

- Highest possible rust protection
- Perfect isolation against moisture
- UV-resistant

APPLICATION ADVICE

Damaged areas on metal substrates must be thoroughly cleaned with silicone remover. When used as a primer, we recommend to apply a 2K filler on top. When used in several layers or in high layer thickness, overpainting can be done wet on wet with water- or solvent-based paints.

1K EASY PRIMER

1K Filling primer



Art.-No.	Specification	SP	MOQ
151.537	White / 400 ml	1	12
151.538	Grey / 400 ml	1	12
151.539	Black / 400 ml	1	12

DESCRIPTION

- 1K Primer spray

AREA OF APPLICATION

- Spot and partial paintings
- Isolating of sanded-through spots
- Overpaintable with water- and solvent-based paints
- Overpaintable wet on wet

BENEFITS

- Rust protection primer and filler in one step
- Weldable
- Free of chromate

1K EASY FILLER

1K High build primer



Art.-No.	Specification	SP	MOQ
159.584	White / 400 ml	1	12
151.522	Lightgrey / 400 ml	1	12
151.523	Black / 400 ml	1	12

DESCRIPTION

- 1K Acrylic filler spray
- High build primer

AREA OF APPLICATION

- Spot and partial paintings
- Filling small spots prior to painting
- Overpaintable with water- and solvent-based paints

BENEFITS

- High filling and opacity power
- Time saving compared to the use of a spray gun
- Suitable for wet and dry sanding
- Free of chromate

PLASTIC PRIMER

Plastic primer



Art.-No.	Specification	SP	MOQ
145.986	Transparent / 400 ml	1	12

DESCRIPTION

- Plastic primer spray

AREA OF APPLICATION

- For all car and truck plastic parts inside and outside
- Suitable for spot repairs

APPLICATION ADVICE

Can be used on the following plastics: PP, PP/EPDM, ABS, SAN, PUR-RIM, R-TRU, PPO, PBT, PUR flexible foam, UP-GF plastics. Not suitable for PE and PC.

BUMPER STRUCTURANT SPRAY

Bumper structurant spray black



Art.-No.	Specification	SP	MOQ
142.982	400 ml	1	12

DESCRIPTION

- Acrylic structurant paint spray
- Colour: Black

AREA OF APPLICATION

- Repairs and renewals of old, faded out or damaged plastic parts
- Reforms the structure close to the original

BENEFITS

- No plastic primer needed
- No spray gun application necessary

APPLICATION ADVICE

We recommend the Carsystem Replacement Spray Head Red (145.840) for fan or wide spray application.

BUMPER PAINT SPRAY

Bumper spray



Art.-No.	Specification	SP	MOQ
142.820	Grey / 400 ml	1	6
142.821	Black / 400 ml	1	6

DESCRIPTION

- Acrylic paint spray

AREA OF APPLICATION

- Repairs and renewals of old, faded out or damaged plastic parts

BENEFITS

- No plastic primer needed
- No spray gun application necessary

APPLICATION ADVICE

Usable on PP, PP/EPDM, ABS.

For industrial and professional use only.

BUMPER PAINT

Structurant paint for plastics



Art.-No.	Specification	SP	MOQ
147.447	1.0 L	1	12

DESCRIPTION

- Acrylic structurant paint
- Colour: Black

AREA OF APPLICATION

- Repairs and renewals of old, faded out or damaged plastic parts
- Reforms the structure close to the original

BENEFITS

- No plastic primer needed
- Can be applied directly to the plastic without prior priming

For industrial and professional use only.

PREFILL-SPRAY

Aerosol tin – fillable



Art.-No.	Specification	SP	MOQ
125.686	Without pin / 275 ml	1	12

DESCRIPTION

- Prefill paint spray
- Filled with 275 ml propellant, solvent and additives
- To be filled with 100 ml of paint

AREA OF APPLICATION

- Fillable with solvent-based paint

BENEFITS

- Replaces a spray gun in spot repairs

APPLICATION ADVICE

Filling machine required

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

PREFILL-SPRAY WATER

Aerosol tin – fillable



Art.-No.	Specification	SP	MOQ
140.608	Without pin / 300 ml	1	12

DESCRIPTION

- Prefill paint spray
- Filled with 300 ml propellant, solvent and additives
- To be filled with 100 ml of paint

AREA OF APPLICATION

- Fillable with water-based paint

BENEFITS

- Replaces a spray gun in spot repairs

APPLICATION ADVICE

Filling machine required

REPLACEMENT SPRAY HEAD

Replacement Spray Head – adjustable



Art.-No.	Specification	SP	MOQ
153.793	Replacement Spray Head adjustable	1	300

DESCRIPTION

- Adjustable replacement spray head
- Suitable for:
 - 1K Epoxy Primer
 - 1K Easy Primer
 - 1K Easy Filler

REPLACEMENT SPRAY HEAD

Replacement spray head – red



Art.-No.	Specification	SP	MOQ
145.840	Spray nozzle spare part / red	1	100

DESCRIPTION

- Replacement spray head
- Colour: Red
- For fan or wide spray application

AREA OF APPLICATION

- For fan or wide spray application
- Suitable for: Bumper Structurant Spray, Prefill Spray and Prefill Spray Water

PAINT SYSTEM CPS 3.0

Disposable paint cup system with red locking ring



Art.-No.	Specification	SP	MOQ
160.085	Set / 180 ml / 125 µm / 50 pcs	1	1
160.086	Set / 400 ml / 125 µm / 50 pcs	1	1
160.087	Set / 650 ml / 125 µm / 50 pcs	1	1
160.088	Set / 850 ml / 125 µm / 50 pcs	1	1
160.090	Set / 180 ml / 190 µm / 50 pcs	1	1
160.091	Set / 400 ml / 190 µm / 50 pcs	1	1
160.092	Set / 650 ml / 190 µm / 50 pcs	1	1
160.093	Set / 850 ml / 190 µm / 50 pcs	1	1
160.376	Lids / 180 ml / 125 µm / 25 pcs	1	1
160.377	Lids / 400 ml / 125 µm / 25 pcs	1	1
160.379	Lids / 650 & 850 ml / 125 µm / 25 pcs	1	1

DESCRIPTION

- Disposable paint cup system with red locking ring

AREA OF APPLICATION

- For processing water-based and solvent-based paint systems

BENEFITS

- Thanks to the quick-release, a quarter turn is all it takes to securely lock the cup system.
- The recess in the hard cup allows the insert to be safely fixed and the lid to be removed in a controlled way
- 360° spraying possible
- Direct mixing and spraying without decanting
- Easy storage of leftover material – cleanly sealed

APPLICATION ADVICE


Before removing the cup, we recommend emptying the paint channel. To do this, hold the spray gun upside down, keep the nozzle closed and briefly pull the trigger. The paint channel is now emptied and the cup can be removed cleanly.



ADAPTER FOR CPS PAINT CUP SYSTEMS

Stainless steel and aluminium spray gun adapters

NEW



Art.-No.	Specification	SP	MOQ
158.063	Adapter A7 – Devilbiss / Steel	1	1
158.064	Adapter A5 – Anest Iwata W400 / Steel	1	1
158.065	Adapter A87 – Anest Iwata WS400 + LS400 / Steel	1	1
158.066	Adapter A82 – SATA QCC / Steel	1	1
158.717	Adapter A19 – Walcom GEO/HTE / Steel	1	1
158.718	Adapter A17 – Walcom EGO/SLIM / Steel	1	1
160.187	Adapter A31 – Iwata LPH-80 / Steel	1	1
160.188	Adapter A7 – Devilbiss / Aluminium	1	1
160.189	Adapter A5 – Iwata W400 / Aluminium	1	1
160.190	Adapter A87 – Iwata WS400 / Aluminium	1	1
160.191	Adapter A82 – SATA QCC / Aluminium	1	1
160.192	Adapter A19 – Walcom GEO/HTE / Aluminium	1	1
160.193	Adapter A17 – Walcom EGO/SLIM / Aluminium	1	1
160.194	Adapter A31 – Iwata LPH-80 / Aluminium	1	1

DESCRIPTION

- High-quality adapters for all common paint spray guns

AREA OF APPLICATION

- Threaded adapter connection to Carsystem CPS cup systems

BENEFITS

- Suitable for CPS 2.0 and CPS 3.0
- Made of stainless steel or aluminium

MULTI-MIX CUP

Disposable mixing cups



Art.-No.	Specification	SP	MOQ
140.545	Cup / 385 ml	200	200
140.546	Cup / 750 ml	200	200
140.547	Cup / 1400 ml	200	200
140.548	Cup / 2300 ml	100	100

DESCRIPTION

- Disposable mixing cups

AREA OF APPLICATION

- For clean and accurate mixing of all fillers, base coats, clear coats, etc.

APPLICATION ADVICE

Only use the scale of the mixing cup and not the scale of a measuring stick. The cups are conical in shape, so there may be differences.

MULTI-MIX LIDS

Disposable lids



Art.-No.	Specification	SP	MOQ
140.549	Lid / 385 ml	200	200
140.550	Lid / 750 ml	200	200
140.551	Lid / 1400 ml	200	200
140.552	Lid / 2300 ml	200	200

DESCRIPTION

- Lids for disposable Multi-Mix Cups

AREA OF APPLICATION

- For sealing the Carsystem Multi-Mix Cups 2.0
- For storing residual material

DISPENSER MULTI-MIX

Wall bracket for Multi-Mix Cups



Art.-No.	Specification	SP	MOQ
137.664	0.385 L	1	1
137.665	0.75 L	1	1
137.666	1.4 L	1	1
137.667	2.3 L	1	1

DESCRIPTION

- Dispenser for Multi-Mix Cups 2.0

AREA OF APPLICATION


- Storage for Multi-Mix Cups 2.0

BENEFITS

- Space-saving storage
- Protection against contamination from the environment

MULTI STRAIN

Paint strainer



Art.-No.	Specification	SP	MOQ
146.957	Blue / 125 µ	125	1000
146.958	Yellow / 190 µ	125	1000

DESCRIPTION

- Disposable paint strainer
- Paper funnel with precise nylon-based filter
- Dust-free

AREA OF APPLICATION

- Filtration of all common painting materials

PAINT STRAINER

Paint strainer



Art.-No.	Specification		MOQ
158.430	Blue / 125 µ	250	1000
158.431	Yellow / 190 µ	250	1000

DESCRIPTION

- Disposable paint strainer
- Paper funnel with precise nylon-based filter

AREA OF APPLICATION

- Filtration of all common painting materials

BENEFITS

- Dispenser box
- Reduces the risk of soiling due to external influences
- Safe and clean storage system directly at the workplace

DISPENSER FOR PAINT STRAINERS

Dispenser



Art.-No.	Specification	SP	MOQ
146.960	Dispenser	1	1

DESCRIPTION

- Dispenser for paint strainers
- Space for 150 paint strainers

AREA OF APPLICATION

- For paint strainers

BENEFITS

- Space-saving solution
- Protection against contamination from dust and overspray

MIXING STICK BLACK

Plastic mixing stick



Art.-No.	Specification		MOQ
144.752	23 x 1.8 cm	100	100

DESCRIPTION

- Plastic mixing stick
- Solvent-resistant

AREA OF APPLICATION

- For easy stirring and mixing of paint materials
- Nicely flexible

MIXING STICK FAST

Plastic mixing stick



Art.-No.	Specification	SP	MOQ
159.834	Box à 500 pcs. / Black / 20 x 1,8 cm	1	3

DESCRIPTION

- Plastic mixing stick
- Solvent-resistant
- S – shaped

AREA OF APPLICATION

- The Mixing Stick Fast is ideal for mixing or stirring products (e.g. paint, filler, etc.) without leaving any residue.

BENEFITS

- Its S-shape creates uniform movements in different directions, which ensures better mixing.

CAN SCRAPER

Plastic mixing stick



Art.-No.	Specification	SP	MOQ
159.672	Set of 5 can scrapers	1	100

DESCRIPTION

- Plastic mixing stick
- Solvent-resistant
- Length: 31 cm

AREA OF APPLICATION

- For easy stiring and mixing of paint materials
- Residual emptying of 1 litre and 3.6 litre containers

BENEFITS

- Reduction of paint waste

MULTI-MIX BUCKET

Paint mixing bucket



Art.-No.	Specification	SP	MOQ
144.649	36 pcs. per carton / 5.5 L	1	1
145.315	Lid / 5.5 L	1	1

DESCRIPTION

- Disposable paint mixing bucket with a handle

AREA OF APPLICATION

- For mixing bigger quantities of paint material

BENEFITS

- Very stable
- Antistatic

PLASTIC CAN EMPTY

Paint tins



Art.-No.	Specification	SP	MOQ
144.957	100 pcs. per carton / 0.5 L	100	100
144.958	100 pcs. per carton / 1.0 L	100	100
145.784	100 pcs. per carton / 1.8 L	100	100

DESCRIPTION

- Plastic paint tin
- Solvent-resistant
- Tacky labels included

AREA OF APPLICATION

- Stock of solvent- and water-based paint
- Long stock life due to the airtight closing lid

BENEFITS

- Hard and very stable plastic tin
- Airtight lid prevents content from drying out

SPRAY OUT CARDS METAL

Colour match card



Art.-No.	Specification	SP	MOQ
153.758	200 pcs. per box / white	1	5
153.759	200 pcs. per box / dark grey	1	5

DESCRIPTION

- Colour match cards metal

AREA OF APPLICATION

- Colour matching

COLOR MATCH CARD PAPER

Colour match card



Art.-No.	Specification	SP	MOQ
141.109	250 pcs. per box / 70×179 mm	1	24

DESCRIPTION

- Colour matching card
- Paper-based kit with 250 pcs.
- Holder included

AREA OF APPLICATION

- Colour matching
- Disposable cards

APPLICATION ADVICE

Not suitable for water-based paint. Control of opacity.

TOUCH UP

Paint bottle – fillable 20ml



Art.-No.	Specification	SP	MOQ
150.764	Transparent / 20 ml×100 pcs.	1	8

DESCRIPTION

- Plastic-based paint bottles with a brush
- Including mixing ball made of stainless steel and brush

AREA OF APPLICATION

- Can be filled with paint
- Repairing of stone chips and scratches in the surface

BENEFITS

- Unbreakable

TOUCH UP

Paint bottle – fillable 50ml



Art.-No.	Specification	SP	MOQ
150.769	Transparent / 50 ml×25 pcs.	1	20

DESCRIPTION

- Plastic-based paint bottles with a brush
- Including mixing ball made of glass

AREA OF APPLICATION

- Can be filled with paint
- Repairing of stone chips and scratches in the surface

BENEFITS

- Unbreakable

MICRO TIP

Repair tip



Art.-No.	Specification	SP	MOQ
140.976	Box with 100 pcs.	1	1

DESCRIPTION

- Micro repair sticks with a micro fibre head

AREA OF APPLICATION

- For filling stone chips, silicone funnels and scratches in the varnish

BENEFITS

- Extra dispenser function for removing individual tips

APPLICATION ADVICE

Perfectly suitable with UV Clear (154.528)

For industrial and professional use only.

BRUSH SET

Set of brushes



Art.-No.	Specification	SP	MOQ
140.970	Set	1	10

DESCRIPTION

- Set of small brushes
- Content: 3 sizes / 12 pcs. per size
- No. 4 / No. 6 /No. 8

AREA OF APPLICATION

- For repairing imperfections, stone chips, etc.

PG - FG FINE FILTER

Fine filter



Art.-No.	Specification	SP	MOQ
138.680	Bag with 10 pcs.	10	10

DESCRIPTION

- Fine filter

AREA OF APPLICATION

- Paint filters for use in SATA gravity flow cup

For industrial and professional use only.

DUST NEEDLE

Dust needle



Art.-No.	Specification	SP	MOQ
140.971	Set	1	50
140.972	Needles in blister / 10 pcs.	10	5000

DESCRIPTION

- Dust needle
- Content: 10 pcs.
- Holder included

AREA OF APPLICATION

- For removing particles or lints from freshly painted surfaces

CAR POLISHES AND SEALANTS FOR THE PERFECT FINISH IN THE BODYSHOP

From silicone-free cutting compounds and finish polishes to water-based high gloss finish sealers, waxes and electric polishing machines: your bodyshop is ideally equipped with the high-quality polishing products from CARSYSTEM.

We recommend our polishing pads for high-quality paint preparation and optimal processing of sanding polishes. Our polishing pads are available in a wide range of designs and qualities.

Carsystem's different polishing systems are perfectly coordinated and are suitable for removing sanded imperfections and deep scratches on fresh or hardened top coats, as well as for the safe removal of fine scratches and holograms.

With our large selection of absorbent and lint-free microfibre cloths, you have the optimal cloth for every step of the work. Polishing machines from RUPES complement our product portfolio and ensure the perfect finish in combination with our polishes, pads and matching finish back pads.



POLISH C-05 CUT

High performance cutting compound



Art.-No.	Specification	SP	MOQ
156.345	1 kg	1	6

DESCRIPTION

- High performance cutting compounds
- Water-based
- Free of silicones
- Colour: Green

AREA OF APPLICATION

- Extremely fast removal of defects on fresh and completely hardened top coats
- Especially developed for fresh and used paint surfaces

BENEFITS

- Extremely high cutting performance
- Good deep shine

APPLICATION ADVICE

We recommend using the Carsystem Polish C-05 Cut in combination with the CS Polish Foam Green and using the Carsystem Polish C-30 Finish subsequently on dark paints.

POLISH C-07 CUT

High performance cutting compound



Art.-No.	Specification	SP	MOQ
157.445	1 kg	1	6

DESCRIPTION

- High-performance cutting compound
- Water-based
- Free of silicones
- Colour: Yellow

AREA OF APPLICATION

- Very fast removal of defects on fresh and completely hardened top coats
- Especially developed for fresh and used paint surfaces

BENEFITS

- Very high cutting performance
- Very good deep shine

APPLICATION ADVICE

We recommend using Carsystem Polish C-07 Cut in combination with the CS Polish Foam Yellow and, for dark colours, Carsystem Polish C-30 Finish.

POLISH C-10 STRONG

High performance cutting compound



Art.-No.	Specification	SP	MOQ
151.634	1 kg	1	6

DESCRIPTION

- High-performance cutting compounds
- Water-based
- Free of silicones
- Colour: White

AREA OF APPLICATION

- Fast removal of imperfections in fresh and completely hardened top coats
- Especially developed for fresh and used paint surfaces

BENEFITS

- High cutting performance
- Extremely good deep shine
- Polishing on a low temperature level

APPLICATION ADVICE

We recommend using the Carsystem Finish Quadra Pad C10 and, for dark colours, Carsystem Polish C-30.

POLISH C-30 FINISH

Anti hologram polish



Art.-No.	Specification	SP	MOQ
151.636	1 kg	1	6

DESCRIPTION

- Anti-hologram polish
- Water-based
- Free of silicone
- Colour: Grey

AREA OF APPLICATION

- Removal of finest scratches, swirl marks and holograms on dark paints
- Perfect as the last finishing step

BENEFITS

- Very effective removal of holograms without streaks
- Perfect deep shine
- Low dusting
- Good material displacement

APPLICATION ADVICE

We recommend using it with the Carsystem Finish Foam White AH, Finish Sandwich Pad C-30 or Finish Foam Black AH.

C-WAX C-80

High gloss finish sealer



Art.-No.	Specification	SP	MOQ
158.243	500 g	1	10

DESCRIPTION

- Water-based high gloss finish sealer
- Free of silicones

AREA OF APPLICATION

- Sealing of painted surfaces
- Protects the paint from weathering, fingerprints and slight mechanical damage
- Perfectly suitable as assembly protection in industry or car dealerships
- Can be applied by hand or machine

BENEFITS

- Very good resistance to alkaline cleaners and environmental influences
- Extremely smooth surface
- Long-lasting protection
- Brilliant deep shine
- Very quick and easy to use

APPLICATION ADVICE

We recommend using the Carsystem Wax Puck.

REFINISH 1

Cutting compound



Art.-No.	Specification	SP	MOQ
132.437	880 ml	1	12

DESCRIPTION

- Cutting compounds
- Free of silicones

AREA OF APPLICATION

- Removal of scratches, dust inclusions and orange peel from fresh and old paints
- Especially suitable for faded and old paint surfaces

NANO CARNAUBA WAX

High gloss wax



Art.-No.	Specification	SP	MOQ
151.945	1.0 l	1	6

DESCRIPTION

- High gloss wax with nano technology
- Water-based
- Free of silicones
- Colour: Yellow

AREA OF APPLICATION

- Sealing of paint surfaces
- Protects the paint from weathering

BENEFITS

- Dirt-repellent
- Provides a deep, mirror-like shine

APPLICATION ADVICE

We recommend the application with the Carsystem Wax Puck.

DISPENSER BOTTLE INCL. CAP

Dispenser bottle



Art.-No.	Specification	SP	MOQ
156.575	Dispenser bottle incl. cap	1	1

DESCRIPTION

- Dispenser bottle incl. cap for polishes
- 250 ml

BENEFITS

- Perfect dosage of the amount of polish compound
- Low weight
- Perfect handling



MAXIMUM PERFORMANCE. PERFECT FINISH.

The Compound X1500 combines extremely high cutting power with a surprisingly fine finish – in just one single step. Due to its high abrasiveness, the polish is ideal for the rapid removal of sanding marks. After 15 seconds of polishing, the abrasive grain breaks down into finer particles, ensuring a smooth polishing pattern and high gloss.

Thanks to the grain breakdown during the polishing process, the Compound X1500 is also excellent for dark paints – delivering impressive results with minimal reworking.



PERFECT FINISH IN EVERY DETAIL.

Polish X8000 has been developed to provide a fine and safe finish for modern automotive coatings. It contains microscopic small abrasives that remove even the finest scratches and holograms with maximum control.

Thanks to its balanced formula, the polish is easy and safe to use and ensures a consistent finish with long-lasting high gloss. Ideal as the final polishing step to remove holograms and enhance the depth of gloss.

COMPOUND X1500

High performance cutting compound

Art.-No.	Specification	SP	MOQ
160.446	500 g	1	10

DESCRIPTION

- High-performance cutting compound
- Water-based
- Free of silicones

AREA OF APPLICATION

- For use with Compound X1500 to rapidly remove sanded imperfections in the topcoat and to remove scratches from OEM paintwork

BENEFITS

- Very high cut in the first 10 seconds
- Fast and visible polishing results
- Becomes significantly finer after a short time
- Low speed range (600–1.500 rpm) – safe to use
- Polish does not dry out – no dust formation during polishing
- High efficiency
- No splashing during polishing
- Can be used rotary and eccentrically
- High gloss level, even on dark paints
- One-step polishing possible on light paints
- Very easy to clean after polishing – without applying pressure

POLISH X8000

Anti hologram polish

Art.-No.	Specification	SP	MOQ
160.451	500 g	1	10

DESCRIPTION

- Fine and safe finish
- Microscopic abrasive grain for targeted and controlled removal of the finest scratches and holograms

AREA OF APPLICATION

- Removal of finest scratches, swirl marks and holograms on dark paints
- Perfect as the last finishing step

BENEFITS

- Removes the finest scratches
- Easy and safe to use
- Long-lasting, hologram-free results – contains no silicones or oils
- Very high gloss level
- Very economical
- No splashing during polishing
- Can be used with rotary and eccentric polishers
- Very easy to clean after polishing – without applying pressure



FREE OF
SILICONES

NEW

For industrial and professional use only.

For industrial and professional use only.

POLISHING PAD HC X1500

Heavy Cut – Maximum cut. Fast results.

The specially developed Polishing Pad X1500 HC for the Compound X1500 ensures maximum speed and complements the high-performance polish perfectly. The hardness and density of the polishing pad are ideal for removing sanded imperfections in the shortest possible time. The sandwich construction offers the maximum flexibility for the user and makes it safe to use on sensitive paintwork or complex surfaces.



Art.-No.	Specification	SP	MOQ
160.447	HC X1500 / 145 mm	2	200
160.448	HC X1500 / 85 mm	2	500
160.449	MC X1500 / 145 mm	2	200
160.450	MC X1500 / 85 mm	2	500

POLISHING PAD MC X1500

Medium Cut – The perfect balance – for any surface.



The Polishing Pad X1500 MC offers the perfect balance between removal rate, speed and safety. The slightly reduced hardness of the polishing pad ensures a lower removal rate, but also makes it an all-rounder for every surface and every user. The sandwich construction supports the user and ensures perfect handling even with complex components or sensitive surfaces.

DESCRIPTION

- Heat-resistant foam polishing pad
- High degree of hardness
- Colour: Red HC X1500 - White MC X1500

AREA OF APPLICATION

- For use with Compound X1500 to rapidly remove sanded imperfections in the topcoat and to remove scratches from OEM paintwork

BENEFITS

- Sandwich construction provides flexibility, safety, and even pressure distribution
- Shape- and heat-resistant foam provides maximum performance
- Suitable for rotary and random orbital poling machines
- Conical shape provides precise polishing
- No water, soap, or cleaner required for cleaning – the polishing pad can be cleaned quickly and easily with compressed air

APPLICATION ADVICE

Maximum performance is achieved when used in combination with CS Compound X1500.

POLISHING PAD AH X8000

Anti Hologramm – 100% shine – 0% holograms

The Polishing Pad X8000 AH has been specially developed to use with the Polish X8000 and is the ideal choice for the final polishing step. Thanks to its fine-pored structure, the pad enhances the performance of the microscopically small abrasive grains, enabling the safe removal of the finest scratches and delivering a hologram-free finish.

DESCRIPTION

- Polishing pad with a low degree of hardness

AREA OF APPLICATION

- Used in combination with Polish X8000 for the easy and fast removal of fine scratches and the elimination of holograms in clear coats

BENEFITS

- Low hardness is ideal for removing holograms
- Dense foam structure provides maximum paint protection
- Shape- and heat-resistant foam delivers maximum performance
- Perfect for the final polishing step
- Suitable for rotary and dual-action polishers
- Conical shape enables precise polishing
- No water, soap, or cleaner required for cleaning – the polishing pad can be cleaned quickly and easily with compressed air

APPLICATION ADVICE

Maximum performance is achieved when used in combination with CS Polish X8000.



Art.-No.	Specification	SP	MOQ
160.452	145 mm	2	200
160.453	85 mm	2	500

MICROFIBER X300 DUO

Clean. Safe. Always to hand.

The Microfibre X300 offers high-quality microfibre cloths for daily use in the paint shop. The optimal fibre density ensures excellent dirt and polish absorption whilst being gentle on any surface.

Two different colours allow for a clear separation of application areas, e.g. coarse polishing, fine polishing or general cleaning.

Thanks to the two dispensing openings, the microfibre cloths can be removed quickly, cleanly and individually – ideal for an efficient and organised workflow.

DESCRIPTION

- Microfiber cloths 40 x 40 cm
- 300 g/m²
- Dispenser box containing 12 cloths per color
- Colours: Red and white
- Ultrasonic cut

AREA OF APPLICATION

- For all common cleaning works

BENEFITS

- Ultrasonic cut – no seam = no scratches
- Two colours for clear separation of work or application areas
- Excellent absorption of dirt or polish residue
- Gentle on paintwork, glass and plastic
- Practical box with 2 dispensing openings

APPLICATION ADVICE

Washable up to 30 °C without detergents.



Art.-No.	Specification	SP	MOQ
160.457	red and white / 40 x 40 cm	1	1

NEW



For industrial and professional use only.

For industrial and professional use only.

FINISH QUADRA PAD C-10

Polishing pad



Art.-No.	Specification	SP	MOQ
151.906	85 mm	4	4
151.640	145 mm	1	1
151.905	160 mm	1	1

DESCRIPTION

- Finish foam pad
- Hardness: Hard
- Spider cut
- Double layer construction

AREA OF APPLICATION

- For processing of cutting compounds

BENEFITS


- Double layer construction supports the foam and provides a consistent performance
- Spider cut for more aggressivity

APPLICATION ADVICE

We recommend using the Carsystem Polish C-10 strong.

POLISH FOAM GREEN

Polishing pad



Art.-No.	Specification	SP	MOQ
157.050	90 mm	2	200
157.051	145 mm	2	100

DESCRIPTION

- Polish foam pad
- Hardness: Hard

AREA OF APPLICATION

- For processing of cutting compounds

APPLICATION ADVICE

We recommend using the Polish Foam Green with the Polish C-05 Cut.

FINISH SANDWICH PAD C-30

Polishing pad



Art.-No.	Specification	SP	MOQ
151.908	85 mm	4	4
151.639	145 mm	1	1

DESCRIPTION

- Finish foam pad
- Hardness: Medium
- Double layer construction

AREA OF APPLICATION

- For processing of fine and anti-hologram polishes

BENEFITS

- Double layer construction supports the foam and provides a consistent performance

APPLICATION ADVICE

We recommend using the Carsystem Polish C-30 Finish.

POLISH FOAM YELLOW

Polishing pad



Art.-No.	Specification	SP	MOQ
157.056	90 mm	2	200
157.057	145 mm	2	100

DESCRIPTION

- Polish foam pad
- Hardness: Medium

AREA OF APPLICATION

- For processing of cutting compounds

APPLICATION ADVICE

We recommend using the Polish Foam Yellow with the Polish C-07 Cut.

FINISH FOAM WHITE AH

Polishing pad



Art.-No.	Specification	SP	MOQ
157.052	90 mm	2	200
157.053	145 mm	2	100

DESCRIPTION

- Finish foam pad
- Hardness: Soft

AREA OF APPLICATION

- For processing of fine and anti-hologram polishes and waxes

APPLICATION ADVICE

We recommend using the Polish Foam White AH with the Polish C-30 finish.

FINISH FOAM BLACK AH

Polishing pad



Art.-No.	Specification	SP	MOQ
157.064	90 mm	2	200
157.065	145 mm	2	100

DESCRIPTION

- Finish foam pad
- Hardness: Soft

AREA OF APPLICATION

- For processing of fine and anti-hologram polishes and waxes

APPLICATION ADVICE

We recommend using the Finish Foam Black AH in combination with all common fine and anti-hologram-polishes and waxes.

POLISH FOAM WHITE SC

Polishing pad



Art.-No.	Specification	SP	MOQ
157.054	90 mm	2	200
157.055	145 mm	2	100

DESCRIPTION

- Polish foam pad
- Hardness: Hard

AREA OF APPLICATION

- For processing of grinding polishes

APPLICATION ADVICE

We recommend using the Polish Foam White SC in combination with all common abrasive polishes.

FINISH FOAM ORANGE

Polishing pad



Art.-No.	Specification	SP	MOQ
153.088	85 x 25 mm	2	100
153.076	145 x 25 mm	1	100

DESCRIPTION

- Polish foam pad
- Hardness: Medium

AREA OF APPLICATION

- For processing of cutting compounds

LAMB WOOL PAD WHITE S EDGE

Lamb wool pad



Art.-No.	Specification	SP	MOQ
157.163	80×17 mm	1	1
157.232	130×25 mm	1	10

DESCRIPTION

- 100 % premium lamb wool
- Protective armour due to turned-in edge
- The turned-in edge forms an edging on the backside which fixes the backpad perfectly

AREA OF APPLICATION

- Designed for polishing strong curves, narrow edges and hard-to-reach areas e. g. entrance areas, window frames, roof pillars

BENEFITS

- Protects surrounding parts from damage
- Easy polishing also in hard to reach areas
- Very fast removal of scratches
- Highest quality offers extremely long durability

LAMB WOOL PAD GOLD S

Lamb wool pad



Art.-No.	Specification	SP	MOQ
157.166	80×17 mm	1	500
157.290	150×17 mm	1	10

DESCRIPTION

- 100% lamb wool
- Soft backpad

AREA OF APPLICATION

- For processing of cutting compounds

BENEFITS

- Highest quality offers extreme long durability
- Polishing on a low temperature level
- Very high cutting power for an efficient removal of sanding marks

For industrial and professional use only.

RUPES POLISH PAD

Polishing pad



Art.-No.	Specification	SP	MOQ
158.854	Ultra fine / white / 130 / 150 mm	1	1
158.853	Fine / yellow / 130 / 150 mm	1	1
158.856	Ultra fine / white / 150 / 180 mm	1	1
158.855	Fine / yellow / 150 / 180 mm	1	1

DESCRIPTION

- Polish foam pad
- Hardness: Ultra fine, fine

AREA OF APPLICATION

- The 9.DA pad FINE is suitable for processing abrasive polishes
- The 9.DA pad ULTRA FINE is suitable for processing anti-hologram polishes

BENEFITS

- Also suitable for random orbital machines

For industrial and professional use only.

FINISH WAFFLE FOAM BLACK AH

polishing pad



Art.-No.	Specification	SP	MOQ
157.066	85 mm	2	200
157.067	145 mm	2	100

DESCRIPTION

- Finish Waffle Foam
- Hardness: Soft

AREA OF APPLICATION

- For processing of fine and anti-hologram polishes and waxes

APPLICATION ADVICE

We recommend using the Finish Foam Black AH in combination with all common fine & anti-hologram-polishes and waxes.

POLISH WAFFLE FOAM
YELLOW

Polishing pad



Art.-No.	Specification	SP	MOQ
157.058	85 mm	2	200
157.059	145 mm	2	100

DESCRIPTION

- Polish waffle foam
- Hardness: Medium

AREA OF APPLICATION

- For processing of cutting compounds

APPLICATION ADVICE

We recommend using the Polish Foam Yellow with the Polish C-07 Cut.

CAR MOP WHITE

Polishing pad



Art.-No.	Specification	SP	MOQ
133.149	150x50 mm	1	10

DESCRIPTION

- Polish foam pad
- Hardness: Hard

AREA OF APPLICATION

- For processing of cutting compounds

APPLICATION ADVICE

We recommend using the Car Mop white with Refinish 1.

FINISH WAFFLE PAD ORANGE

Polishing pad



Art.-No.	Specification	SP	MOQ
153.114	135 x 25 mm	2	100

DESCRIPTION

- Polish waffle foam pad
- Hardness: Medium

AREA OF APPLICATION

- For processing of cutting compounds

WAX PUCK

Application foam



Art.-No.	Specification	SP	MOQ
152.565	128 – 130 mm	1	1

DESCRIPTION

- Polyurethane foam

AREA OF APPLICATION

- Effective application of polishes and waxes

BENEFITS

- Ergonomic handle

FINISH CONTROL FOAM C-99

Control Foam



Art.-No.	Specification	SP	MOQ
156.614	400 ml	1	12

DESCRIPTION

- Micro Foam-Spray
- Water-based
- Free of silicones
- Colour: White

AREA OF APPLICATION

- For checking and cleaning between the polishing steps

BENEFITS

- Removes oily and waxy residues
- Makes any remaining sanding marks visible

APPLICATION ADVICE

Finish Control Foam C-99 should be removed with a microfiber cloth after a short exposure time.

REFINISH RESTORER

Plastic conditioner



Art.-No.	Specification	SP	MOQ
159.706	250 ml	1	12
159.707	1 l	1	6

DESCRIPTION

- Plastic conditioner
- Air drying natural oil
- Free of silicones
- Colour: Yellowish-transparent

AREA OF APPLICATION

- For refurbishing faded plastic and metallic surfaces (e.g. aluminum, chrome, stainless steel, non ferrous metals)
- For removing polishing splashes from plastics

BENEFITS

- Infiltrates deep into surfaces

APPLICATION ADVICE

Only for exterior use. The product shall be tested first before application on white surfaces.

MICRO FIBER CLOTH

Sky Blue



Art.-No.	Specification	SP	MOQ
156.587	260 g/m ² / light blue	5	360

DESCRIPTION

- Micro fiber cloth
- Ultrasonic cut
- 40 × 40 cm
- 260 g/m²
- 80% polyester / 20% polyamide

AREA OF APPLICATION

- For all common cleaning works

BENEFITS

- The edges do not scratch

APPLICATION ADVICE

Washable up to 30 °C without detergents.

MICRO FIBER CLOTH

Wave Cut



Art.-No.	Specification	SP	MOQ
156.588	300 g/m ² / white	5	300

DESCRIPTION

- Micro fiber cloth
- Ultrasonic cut
- 40 × 40 cm
- 300 g/m²
- 80% polyester / 20% polyamide

AREA OF APPLICATION

- Perfect for sharp edged panels
- For all common cleaning works

BENEFITS

- Universal micro fiber cloth
- The edges do not scratch

APPLICATION ADVICE

Washable up to 30 °C without detergents.

For industrial and professional use only.

MICRO FIBER CLOTH

2 IN 1



Art.-No.	Specification	SP	MOQ
156.589	380 g/m ² / dark blue	3	240

DESCRIPTION

- Micro fiber cloth
- Ultrasonic cut
- 40 × 40 cm
- 380 g/m²
- 80% polyester / 20% polyamide

AREA OF APPLICATION

- For all common cleaning works

BENEFITS

- Two different sides (short fibers / long fibers)
- Flexible use
- The edges do not scratch

APPLICATION ADVICE

Washable up to 30 °C without detergents.

For industrial and professional use only.

MICRO FIBER CLOTH

Fluffy



Art.-No.	Specification	SP	MOQ
156.590	500 g/m ² / grey	2	180

DESCRIPTION

- Micro fiber cloth
- Ultrasonic cut
- 40 × 40 cm
- 500 g/m²
- 80% polyester / 20% polyamide

AREA OF APPLICATION

- High absorption of polishes, waxes and dust
- "Final cloth": extremely gentle on the surface

BENEFITS

- Very long and soft fibers
- Perfect absorption
- The edges do not scratch

APPLICATION ADVICE

Washable up to 30 °C without detergents.

MICRO FIBER CLOTH

Polish Extreme



Art.-No.	Specification	SP	MOQ
156.591	800 g/m² / black / yellow	1	100

DESCRIPTION

- Micro fiber cloth
- Corded edges
- 40 × 40 cm
- 800 g/m²
- 80% polyester / 20% polyamide

AREA OF APPLICATION

- Polishing cloth
- High absorption of polishes and waxes

BENEFITS

- Extremely high absorption
- Very gentle on the surface
- The edges do not scratch

APPLICATION ADVICE

Washable up to 30 °C without detergents.

CAR POLISH ROLL

Disposable polishing cloth



Art.-No.	Specification	SP	MOQ
134.582	370 tear-off / 36 × 40 cm	1	1

DESCRIPTION

- Disposable polishing cloth
- Dispenser with 370 tear-offs
- Perforated
- Size: 36x40 cm

AREA OF APPLICATION

- Cleaning and degreasing of surfaces

BENEFITS

- Extremely soft
- Free of lints
- Tear resistant
- Highly absorbent

FINISH BACK PAD M-14

Finish back pad



Art.-No.	Specification	SP	MOQ
157.721	123 mm	1	1

DESCRIPTION

- Finish Back Pad for polishing pads with Velcro®
- Extra thick foam pad
- Degree of hardness: Soft
- Thread: M-14

BENEFITS

- Adapts perfectly to uneven surfaces
- Distributes the pressure on the surface more evenly

FINISH BACK PAD

Finish back pad



Art.-No.	Specification	SP	MOQ
139.206	128 mm	1	10

DESCRIPTION

- Finish back pad for polishing pads
- Thread: M14

POLISHING BACK PAD

Finish back pad



Art.-No.	Specification	SP	MOQ
144.916	M6 / 77 mm	1	1

DESCRIPTION

- Replacement back pad for Polishing Machine RC166
- Thread: M6 (fixed screw)

APPLICATION ADVICE

The back pad can be used for the RC 166 polishing machine or the 159.007 RUPES 9P01.055 Velcro® back pad M6 / 75 mm.

ROTARY POLISHER CSH-CRP01 KIT

Rotary Polisher, cordless



Art.-No.	Specification	KP	MOQ
159.822	CSH-CRP01	1	6
160.111	Back pad 74 mm 1/4" – 20	1	1

DESCRIPTION

- Lightweight, handy cordless polishing machine
- Adjustable speed levels: 700 – 2.500 rpm
- Battery life in continuous use: 30 minutes
- Battery life with interruptions: up to 2 days
- Charging time: 60 minutes
- Thread on pad: external thread 1/4"-20
- Pad: 74 mm Ø – Velcro®

AREA OF APPLICATION

- Removing scratches, polishing painted surfaces, and applying waxes and polishes for a glossy finish. Also suitable for interiors, interior trims and chrome accents.

BENEFITS

- Flexible – no cables or pneumatic hoses required
- Fatigue-free – well-balanced, ergonomic design
- User-friendly – low noise levels and minimal vibration
- Adjustable speed control – precise settings for delicate paints or demanding surfaces
- Practical – dust-free and secure storage in the included case



ORBITAL SANDER CSH-CMS01 KIT

Cordless orbital sander



Art.-No.	Specification	SP	MOQ
159.067	CSH-CMS01 / 3 mm	1	6

DESCRIPTION

- Lightweight, handy cordless orbital sander
- Adjustable speed levels: 4.000 – 10.000 rpm
- Battery life in continuous use: 40 minutes
- Battery life with interruptions: up to 2 days
- Charging time: 60 Minutes
- 3 mm orbit

AREA OF APPLICATION

- Spot sanding
- Removal of paint defects such as dust, particles, etc.

BENEFITS

- Flexible – no cables or air hoses required
- Fatigue-free – well-balanced, ergonomic design
- User-friendly – low noise levels and low vibrations
- Practical – dust-free and secure storage in the included case

APPLICATION ADVICE

For perfect results, we recommend using the CS Mini Back Pad 28 mm GRIP (Velcro version 144.769), CS Mini Back Pad 28 mm STICK (adhesive version 144.768) or the Universal Set CS Grip-To-Stick (Velcro-adhesive adapter version 159.677).



For industrial and professional use only.

CORDLESS SANDER CSH-COS01

Cordless random orbital sander

NEW



Art.-No.	Specification	SP	MOQ
160.108	CSH-COS01	1	6
160.109	74mm – 5/16"	1	1

DESCRIPTION

- Lightweight, compact cordless random orbital sander
- Adjustable speed levels: 4.000 – 10.000 rpm
- Battery life in continuous use: 30 minutes
- Battery runtime with interruptions: up to 2 days
- Charging time: 60 minutes
- Thread type: Internal thread 1/4"-20
- Thread on pad: external thread 1/4"-20
- Pad: 74 mm Ø – Velcro®

AREA OF APPLICATION

- Ideal for fine sanding and correction work, removing dust inclusions, precise detail tasks, and smart repair applications.

BENEFITS

- Flexible – no cables or compressed air hoses
- Fatigue-free – balanced, ergonomic design
- User-friendly – low noise level, low vibration
- Finely adjustable speed – precise control for sensitive paintwork or demanding surfaces
- Practical – dust-free and safe storage in the carry case

For industrial and professional use only.

SPARE BATTERY 5,0AH

Spare Battery for CSH-COS01 and CSH-CRP01

NEW



Art.-No.	Specification	SP	MOQ
160.110	5,0Ah	1	1

DESCRIPTION

- High-capacity battery perfect for long working periods
- Constant power for consistent sanding or polishing results
- Protective mechanisms against overcharging, overheating and deep discharge

AREA OF APPLICATION

- The perfect addition to our existing CS cordless sander CSH-COS01 and our CS cordless polisher CSH-CRP01.

BENEFITS

- Longer working hours without frequent recharging
- Low self-discharge even after prolonged storage
- Long service life due to high number of charging cycles

For industrial and professional use only.

RAPID CHARGER FOR CSH-BATTERY-POWERED

replacement charger

NEW



Art.-No.	Specification	SP	MOQ
159.064	10,8 V / 55 W	1	0

DESCRIPTION

- Replacement charger for:
- Orbital Sander CSH-CMS01
- Rotary Polisher CSH-CRP01
- Cordless Sander CSH-COS01

BENEFITS

- Intelligent charging system
- Overcharge protection
- Protects against overheating

APPLICATION ADVICE

Approximate charging times:
2.5 Ah batteries – 50–60 minutes /
5.0 Ah batteries – 100–120 minutes

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

RUPES POLISHING MACHINE LHR15

Polishing machine, electric, Bigfoot



Art.-No.	Specification	SP	MOQ
157.323	LHR15 III	1	1
157.641	Polishing back pad 125 mm	1	1

DESCRIPTION

- Electric random orbital polishing machine
- 15 mm orbit diameter
- Ø Velcro® back pad: 125 mm
- Adjustable speed up to 5.200 rpm.
- Thread: M8-F

POLISHING MACHINE RC 166

Polishing machine, pneumatic



Art.-No.	Specification	SP	MOQ
143.723	Mini Polishing Machine RC 166 incl. polishing back pad	1	1

DESCRIPTION

- Pneumatic polishing machine
- Incl. back pad: 77 mm
- Adjustable speed up to 2.500 rpm.
- Thread: M6

APPLICATION ADVICE

The 159.007 RUPES 9P01.055 Velcro backing pad M6 / 75 mm can be used as well.

RUPES POLISHING MACHINE LH19E

Polishing machine, Bigfoot



Art.-No.	Specification	SP	MOQ
157.322	LH19E	1	1
157.640	Polishing back pad M14	1	1

DESCRIPTION

- Electric polishing machine
- Rotating
- Ø Velcro® back pad: 125 – 165 mm
- Adjustable speed up to 1.700 rpm.
- Thread: M14

MINI SANDING MACHINE RC 9330

Mini sanding machine, pneumatic



Art.-No.	Specification	SP	MOQ
143.724	Mini sanding machine / incl. back pad stick and grip	1	1

DESCRIPTION

- Pneumatic random orbital sander for daisy discs incl. 2 back pads (for Velcro® and PSA discs)
- Adjustable speed up to 7.500 rpm.
- Thread: 5/16"

AREA OF APPLICATION

- Finish sanding with daisy discs
- For Velcro® and PSA discs

RUPES MINI POLISHING MACHINE HLR75STB

Polishing Machine, battery powered



Art.-No.	Specification	SP	MOQ
158.647	HLR 75 STB battery powered	1	1

DESCRIPTION

- Battery powered mini polishing machine
- Battery with LED display: 18 V – 2.5 Ah
- Battery life: 35 – 45 min.
- Battery charging time: 35 min.
- Orbital
- 12 mm orbital diameter
- Back pad: 75 mm
- Adjustable speed up to 5.500 rpm.
- Scope of delivery:
 - HLR75STB polishing machine
 - 2 × rechargeable batteries 18 V – 2.5 Ah
 - 1 × battery charger

RUPES CLEANING AND MAINTENANCE OIL

Maintenance oil



Art.-No.	Specification		MOQ
150.190	50 ml	1	5

DESCRIPTION

- Transparent maintenance oilSilicone-free

AREA OF APPLICATION

- Maintains and lubricates pneumatic grinding and polishing machines

BENEFITS

- Also applicable at low temperatures
- Corrosion and wear protection

RUPES ANGLE POLISHING MACHINE LH76P

Angle polishing machine, pneumatic



Art.-No.	Specification	SP	MOQ
157.331	LH76P	1	1

DESCRIPTION

- Pneumatic polishing machine
- Ø Velcro® back pad: 75 mm
- Adjustable speed up to 5,000 rpm.
- Thread: 3/8"

BONDING & SEALING

ADHESIVES, SEALANTS AND PROTECTION COATINGS FOR UNDERBODY AND BODYWORK

Sealing seams, glueing windcreens, side windows and rear windows in bodywork and filling holes has never been easier – CARSYSTEMs products in the “Bonding & Sealing” category provide you with perfect glass bonding glues, sealing and repair compounds and help you achieve flawless results.

Protect your vehicle optimally with our products for underbody, bodywork and stone chip protection and supplement your equipment with spray guns, tapes, brushes and sound deadening panels.

UNIFLEX PU

Bonding and sealing compound



Art.-No.	Specification	SP	MOQ
159.160	White / 310 ml	1	12
159.161	Grey / 310 ml	1	12
159.162	Black / 310 ml	1	12

DESCRIPTION

- Bonding and sealing compound
- Polyurethane

AREA OF APPLICATION

- Elastic bonding of GRP and metal
- Sealing of seams, joints and fittings

BENEFITS

- Fast drying
- Overpaintable

UNIFLEX MS

Sprayable seam sealer



Art.-No.	Specification	SP	MOQ
160.133	Beige / 290 ml	1	12
159.108	Grey / 290 ml	1	12
160.132	Black / 290 ml	1	12

DESCRIPTION

- Spray- and brushable seam sealer
- Poly-Oxy-Propylene (POP) copolymer

AREA OF APPLICATION

- Seam sealing for overlapping panels and welded seams in original structure e. g. vehicle and carbody repair, container construction, metal construction, ventilation engineering and air-condition technology

BENEFITS

- Fast drying
- Stone chip protection

APPLICATION ADVICE

Keep UNIFLEX-MS away from fresh, not finally hardened PU material.

For industrial and professional use only.

UNIFLEX GLAS

Glass bonding glue



Art.-No.	Specification	SP	MOQ
148.927	Black / 310 ml	1	12

DESCRIPTION

- Glass bonding glue
- 1K Polyurethane
- FMVSS 212 tested

AREA OF APPLICATION

- For glueing front, side and rear windows

APPLICATION ADVICE

Holding time: 2 hours (23 °C and 50% rel. humidity) for cars with driver and co-driver airbags. Processing temperature: 5 °C to 40 °C.

For industrial and professional use only.

UNIFLEX GLAS HM

Glass bonding glue – High modulus – Non-conductive



Art.-No.	Specification	SP	MOQ
148.928	Black / 310 ml	1	12

DESCRIPTION

- Glass bonding glue
- 1K Polyurethane
- High modulus and non-conductive
- FMVSS 208/212 tested

AREA OF APPLICATION

- For glueing front, side and rear windows

BENEFITS

- Fast drying
- High modulus glue (high stiffness)
- Applicable for vehicles with integrated antenna

APPLICATION ADVICE

Holding time: 30 min. (23 °C and 50% rel. humidity) for cars with driver and co-driver airbags. Processing temperature: 5 °C to 40 °C.

UNIFLEX GLAS FAST-PRIMER

Moisture-curing glass primer



Art.-No.	Specification	SP	MOQ
144.036	Black / 30 ml	1	25

DESCRIPTION

- Moisture-curing glass primer

AREA OF APPLICATION

- Primer for Uniflex Glas and Uniflex Glas HM
- Provides adhesion between glass and glass bonding glue
- Application on the ceramic zone of the window

DRYING TIME

- 15 min

APPLICATION ADVICE

Use only in combination with Carsystem Uniflex Glas Fast-Cleaner. Surface must be clean, dry, dust- and grease-free. Glas Fast-Primer application only after surface treatment with the Carsystem Uniflex Glas Fast-Cleaner. Shake bottle well before use.

APPLICATOR

Applicator



Art.-No.	Specification	SP	MOQ
139.325	Applicator	1	100

DESCRIPTION

- Special applicator tool for liquid primers

AREA OF APPLICATION

- For the application of Carsystem Uniflex Glas Fast-Primer

KS-50.2

Brushable Seam Sealer



Art.-No.	Specification	SP	MOQ
160.007	Grey / 1,0 kg	1	12

DESCRIPTION

- Flexible 1K brushable body sealant
- Free from aromatics
- Polymer-based
- Brushable and paintable
- Temperature resistance: -25°C bis 80 °C
- Colour: Grey

AREA OF APPLICATION

- Sealing joints and seams (bolted, riveted, or spot-welded) on moving parts
- Sealing edges, connections and seams on bonnets, doors and other body components

BENEFITS

- Universal joint and seam sealing
- Brushable (brush structure remains visible)
- Overpaintable
- Sound-absorbing
- Permanent adhesion

DRYING TIME

- 30 – 60 min. / 20°C object temperature
- Fully cured: 24 – 48 Std. / 20 °C

APPLICATION ADVICE

The first skin formation occurs after 30 minutes (20°C). Complete curing is achieved after 1-2 days. Do not use on engine, exhaust, axles, springs or shock absorbers.

KS-100

Underbody protection bitumen



Art.-No.	Specification	SP	MOQ
126.032	1 l	1	12

DESCRIPTION

- Brushable underbody protection
- Bitumen-based
- Thixotropic bitumen-resin composite
- Colour: Black

AREA OF APPLICATION

- Underbody protection for car bodies

APPLICATION ADVICE

Not overpaintable.

KS-200

Cavity protection



Art.-No.	Specification	SP	MOQ
126.062	1 l	1	12

DESCRIPTION

- Sprayable cavity protection
- Wax-like cavity protection
- Melting point: 95 °C
- Colour: Brown transparent

AREA OF APPLICATION

- For preserving all cavities of car bodies

BENEFITS

- High creeping capacity also on hard-to-reach areas
- Rust protection
- Adhesion on metal

APPLICATION ADVICE

Not overpaintable.

KS-250

Cavity protection



Art.-No.	Specification	SP	MOQ
126.061	500 ml / incl. hose	1	12
159.332	Replacement tube / 60 cm	1	1

DESCRIPTION

- Sprayable cavity protection
- Wax-like cavity protection
- Melting point: 160 °C
- Colour: Brown transparent

AREA OF APPLICATION

- For the renewal or repair of existing coatings

BENEFITS

- Very high melting point
- Drip-free
- Rust protection
- Adhesion on metal

APPLICATION ADVICE

Not overpaintable.

KS-300.2

Cavity wax



Art.-No.	Specification	SP	MOQ
160.064	1 l	1	12

DESCRIPTION

- Sprayable cavity protection
- Wax-like cavity protection
- Colour: White transparent
- Melting point: > 100°C °C

AREA OF APPLICATION

- For preserving all cavities of car bodies

BENEFITS

- Very high melting point
- Drip-free
- Rust protection
- Adhesion on metal

APPLICATION ADVICE

Not overpaintable.

KS-400

Rust protection wax



Art.-No.	Specification	SP	MOQ
125.468	500 ml	1	12

DESCRIPTION

- Rust protection wax
- Liquid rust protection
- Temperature resistance: -25 °C to +160 °C
- Colour: Transparent

AREA OF APPLICATION

- Transparent conserving of rust exposed parts on car bodies
- Suitable to protect subareas of the engine
- Also protects hinges

BENEFITS

- Good water displacement
- Very temperature-resistant

APPLICATION ADVICE

Not overpaintable.

KS-500.2

Underbody protection bitumen



Art.-No.	Specification	SP	MOQ
160.065	1 l	1	12

DESCRIPTION

- Sprayable underbody protection
- Bitumen-based
- Colour: Black

AREA OF APPLICATION

- Permanent underbody protection for car bodies

BENEFITS

- Vibration-absorbing
- Anti-noise compound

APPLICATION ADVICE

Not overpaintable.

KS-550

Underbody protection bitumen



Art.-No.	Specification	SP	MOQ
126.029	500 ml	1	12

DESCRIPTION

- Sprayable underbody protection
- Bitumen-based
- Colour: Black

AREA OF APPLICATION

- For the renewal or repair of existing underbody coatings

BENEFITS

- No gun application necessary

APPLICATION ADVICE

Not overpaintable.

For industrial and professional use only.

KS-800

Underbody protection wax



Art.-No.	Specification	SP	MOQ
126.095	1 l	1	12

DESCRIPTION

- Sprayable underbody protection wax
- Permanent rust protection based on wax
- Colour: Black

AREA OF APPLICATION

- Permanent underbody protection for car bodies

BENEFITS

- High water displacement

APPLICATION ADVICE

Not overpaintable.

For industrial and professional use only.

KS-850

Underbody protection wax



Art.-No.	Specification	SP	MOQ
126.094	500 ml	1	12

DESCRIPTION

- Underbody protection wax spray
- Permanent rust protection based on wax
- Temperature resistance: -25 °C to +80 °C
- Colour: Brown

AREA OF APPLICATION

- For the renewal or repair of existing underbody coatings

BENEFITS

- Good water displacement

APPLICATION ADVICE

Not overpaintable.

KS-1000

Stone chip protection



Art.-No.	Specification	SP	MOQ
149.266	White / 1 l	1	12
149.264	Grey / 1 l	1	12
149.265	Black / 1 l	1	12

DESCRIPTION

- Sprayable stone chip and underbody protection
- Based on plastic rubber
- Free of asbestos

AREA OF APPLICATION

- Underbody treatment for car bodies
- Stone chip protection for spoilers, sills and lower door areas

BENEFITS

- Vibration-absorbing
- Anti-noise compound
- Also suitable for PVC substrates

APPLICATION ADVICE

Overpaintable after application of an adhesion primer.

KS-1050

Stone chip protection



Art.-No.	Specification	SP	MOQ
126.022	Grey / 500 ml	1	12
126.023	Black / 500 ml	1	12

DESCRIPTION

- Sprayable underbody protection
- Based on synthetic rubber
- Free of asbestos

AREA OF APPLICATION

- For the renewal or repair of existing stone chip protections

BENEFITS

- No gun application necessary
- Also suitable for PVC substrates

APPLICATION ADVICE

Overpaintable after application of an adhesion primer.

KS-3000 PLUS

HS stone chip protection



Art.-No.	Specification	SP	MOQ
152.804	Grey / 1 l	1	12
152.622	Black / 1 l	1	12

DESCRIPTION

- Sprayable stone chip and underbody protection
- Rubber/resin-based

AREA OF APPLICATION

- Stone chip and underbody protection for car bodies

BENEFITS

- Vibration-absorbing
- Anti-noise compound
- Very weather-resistant
- Very abrasion-resistant

APPLICATION ADVICE

Overpaintable with water base paint without a primer. Overpaintable with 2K or acrylic paints after application of an adhesion primer. Suitable for oven drying. Very good sandable after final hardness. Variable structure fine or rough possible.

KS-4000.2

Stone chip protection – water-based



NEW

Art.-No.	Specification	SP	MOQ
160.067	Black / 1 l	1	12

DESCRIPTION

- Sprayable underbody protection
- Water-based
- Free of solvents

AREA OF APPLICATION

- Water-based, overpaintable stone-chip protection for application using the CS KS-Gun or CS KS-Dual Gun

BENEFITS

- Water-based
- Fast drying (< 1 hour)
- Overpaintable
- Protection against corrosion


APPLICATION ADVICE

Overpaintable with standard water-based paints after surface drying (colour change to black). Can be painted over with standard solvent-based systems after complete drying. Easy to remove with warm water when wet. Close the container again after use, as the product dries very quickly.



MOUNT TAPE

Double-sided adhesive tape



Art.-No.	Specification	SP	MOQ
125.712	9 mm x 10 m	2	20
125.713	12 mm x 10 m	2	20
125.720	19 mm x 10 m	1	10

DESCRIPTION

- Double-sided tape
- Temperature resistance: -40 °C to +120 °C
- Black adhesive tape
- Based on polyethylene
- Modified acrylate glue

AREA OF APPLICATION


- Usable for permanent application with high shear and UV exposure, softeners and a wide temperature range (e.g. edge lining and emblems, side bumpers, mirror glass or counterbalance lead weights)
- Industrial mounting of signs or labels interior and exterior

BENEFITS

- High adhesive strength
- Very high UV resistance
- Good solvent resistance
- Flexible fixing also on bended surfaces

HS-ACRYL TAPE

Double-sided adhesive tape



Art.-No.	Specification	SP	MOQ
147.024	6 mm x 10 m	2	20
137.072	9 mm x 10 m	2	20
137.073	12 mm x 10 m	2	20
137.074	19 mm x 10 m	1	10

DESCRIPTION

- Double-sided tape
- Temperature resistance: -40 °C to +150 °C
- Grey adhesive tape
- Based on acryl
- Acrylate glue

AREA OF APPLICATION

- High performance tape for permanent application in extreme temperatures and humidity (e.g. edge linings and emblems, side bumpers, mirror glasses or counterbalance lead weights)
- Industrial mounting of signs or labels interior and exterior
- Suitable for metal, wood, glass and most common plastics

BENEFITS

- Extremely high initial adhesion and strength
- High temperature and humidity resistance

SOUND DEADENING PANELS

Sound deadening panels

Art.-No.	Specification	SP	MOQ
126.055	Bitumen-black / 1 carton à 5 pcs. / 25 x 50 cm	5	25
134.139	Patterned-black / 1 carton à 10 pcs. / 50 x 50 cm	10	50
134.140	Smooth-black / 1 carton à 10 pcs. / 50 x 50 cm	10	50

DESCRIPTION

- Sound-absorbing
- Self-adhesive

AREA OF APPLICATION

- For insulating sounds and vibrations

POWER PU BOND MIXER

Mixing tube – 25+50 ml

Art.-No.	Specification	SP	MOQ
159.956	Mixing tube / 12 pcs per pack / red	1	1

DESCRIPTION

- Plastic mixing tube
- Colour: Red
- Pack: 12 mixing tubes

AREA OF APPLICATION

- Mixing tube for Carsystem Power PU Bond 25/50 ml cartridges

BENEFITS

- Reliable mixing of the two components to form a homogeneous product

APPLICATION ADVICE

The Power PU Bond mixing nozzles can only be used once.

POWER PU BOND

2K PU glue



Art.-No.	Specification	SP	MOQ
159.952	transparent / 50 ml	2	20
159.954	black / 25 ml	2	20
159.955	black / 50 ml	2	20

DESCRIPTION

- 2K Polyurethane glue

AREA OF APPLICATION

- Structural and decorative repair of different plastic parts (pumper, fenders, etc.)
- Application is also possible on metal, wood or glass
- Easy rework like grinding, drilling
- Sealing of gaps, joints and seams
- Extremely long-lasting
- Weather-resistant

BENEFITS

- Fast-drying
- Overpaintable

DRYING TIME

- Handling time / pot life: 1 – 1,30 min. (20 °C)
- Tack free time: 5 min. (20 °C)
- Sandable: 15 – 20 min. (20 °C)

APPLICATION ADVICE

The 25 ml cartridges are dispensed by hand. The 2-component adhesive is mixed by using the static CS Power PU Bond Mixer – mixing nozzles when attached double syringe is activated. The 50 ml cartridges are dispensed and applied by using the CS Power PU Bond Gun (dispensing gun). The mixing nozzles can only be used once. A bonding primer is not required.



POWER PU BOND GUN

2K PU-glue gun



Art.-No.	Specification	SP	MOQ
140.927	Cartridge gun	1	1

DESCRIPTION

- Application gun for plastic repairs

AREA OF APPLICATION

- Application gun for Carsystem Power PU Bond 50 ml cartridges

UNIFLEX NOZZLE

Spare nozzles



Art.-No.	Specification	SP	MOQ
150.292	Nozzles for Uniflex PU	12	12
155.241	Nozzles for Uniflex MS	12	12

DESCRIPTION


- Spare nozzles for Carsystem Uniflex cartridges

AREA OF APPLICATION

- Spare nozzles for Carsystem Uniflex PU and Uniflex MS cartridges
- Only suitable for cartridges

POWER PU BOND FILM

Backing and supporting film



Art.-No.	Specification		MOQ
159.958	Backing / supporting	1	12

DESCRIPTION

- Backing and supporting film
- Front side: With a supporting mesh
- Back side: Plain film, to be removed after curing
- Size: 12,5 x 150 cm

AREA OF APPLICATION

- Plastic repair
- Supporting the plastic compound
- Usable with Carsystem 2K Power PU Bond compounds

UNIFLEX ADAPTER NOZZLE

V-Nozzle



Art.-No.	Specification	SP	MOQ
149.010	V-nozzle / bag of 10	1	1

DESCRIPTION

- Nozzle for seam sealing
- "V-form" nozzle

AREA OF APPLICATION

- For an even sealing of folded edges
- Only suitable for cartridges

UNIFLEX ADAPTER NOZZLE

Wing tip



Art.-No.	Specification	SP	MOQ
149.009	Blade wing tip / Bag of 10	1	1

DESCRIPTION

- Nozzle for seam sealing
- Wing tip

AREA OF APPLICATION

- Seam sealing on folded edges
- Only suitable for cartridges

UNIFLEX AIR GUN

Air gun



Art.-No.	Specification	SP	MOQ
153.224	Uniflex Air Gun	1	1

DESCRIPTION

- Cartridge air gun for the extrusion of 1K sealing compounds

AREA OF APPLICATION

- For extruding of seam sealer
- For 290 ml / 310 ml cartridges and aluminum bags up to 400 ml
- For processing of Carsystem Uniflex cartridges (PU, MS, Glas, Glas HM)

KS-BRUSH

Nylon brush



Art.-No.	Specification	SP	MOQ
141.453	30 mm	1	70

DESCRIPTION

- Special brush with nylon bristles

AREA OF APPLICATION

- For processing sealing compounds

UNIFLEX GUN

Manual gun



Art.-No.	Specification	SP	MOQ
135.108	Classic for 310 ml	1	1
139.286	Top for 290 – 400 ml	1	1

DESCRIPTION

- Manual gun for the extrusion of 1K sealing compounds

AREA OF APPLICATION

- For processing of Carsystem Uniflex cartridges (PU, MS, Glas, Glas HM)
- Classic: for 290 ml / 310 ml cartridges
- Top: for 290 ml / 310 ml cartridges and aluminum bags up to 400 ml



KS-GUN

Underbody protection gun



Art.-No.	Specification	SP	MOQ
157.032	Gun for underbody protection	1	1
142.279	Tube set / 0.95 m	1	1
147.956	KS-Gun replacement nozzle	1	1
158.017	KS-Gun nozzle	1	1

DESCRIPTION

- Pneumatic pressure cup gun
- Structure gun
- Cup content: 1l

AREA OF APPLICATION

- Rust protection, underbody protection and cavity protection
- Processing of solvent- and water-based products

BENEFITS

- Amount of air and material output adjustable
- Various structures possible



For industrial and professional use only.

MS AIR GUN

MS spray gun



Art.-No.	Specification	SP	MOQ
125.681	MS Air Gun	1	1
131.563	Spare nozzle set	1	1
140.075	MS Air Gun nozzle	1	1

DESCRIPTION

- Pneumatic cartridge gun for the extrusion and spraying of 1K sealing compounds

AREA OF APPLICATION

- Spraying and extruding of 1K sealing materials
- For 290 ml / 310 ml cartridges and aluminum bags up to 400 ml
- For processing of Carsystem Uniflex cartridges (PU, MS, Glas, Glas HM)

For industrial and professional use only.

KS-DUAL GUN

Underbody protection gun



Art.-No.	Specification	SP	MOQ
126.040	Incl. 2 additional suction pipes / without cavity protection tube	1	1
126.058	0.9m / cavity protection tube	1	1
126.048	Replacement suction pipes	1	1

DESCRIPTION

- Pneumatic underbody and cavity protection gun
- Including two suction pipes
- Quick coupling

AREA OF APPLICATION

- Rust protection, underbody protection and cavity protection

BENEFITS

- Fast change of material possible
- Low maintenance effort

CLEANING

PROFESSIONAL CLEANING PRODUCTS FOR A PERFECT PAINTING PROCESS

CARSYSTEM offers optimal cleaning products not only for plastic, GRP or CRP surfaces but also for spray guns, devices, car parts or constructions of paint shops.

The CARSYSTEM tack cloths in different variations and the paper cleaning cloths ensure removal of dust. Our products are qualified for the removal of silicones, fats, oils, waxes, tar, or glue odds and provide cleanliness for and around your workspace.



SILICONE REMOVER MILD

Silicone remover – solvent based



Art.-No.	Specification	SP	MOQ
146.711	1 l	1	12
146.704	5 l	1	4
147.023	30 l	1	1
139.212	Drump tap for 30 l	1	1

DESCRIPTION

- Silicone remover
- Solvent-based

AREA OF APPLICATION

- Silicone and grease remover
- Cleaning of dirt residues prior to painting
- For all daily cleaning works

SILICONE REMOVER WATER 2.0

Silicone remover – water based



NEW

Art.-No.	Specification	SP	MOQ
160.321	5 L	1	5

DESCRIPTION

- Special cleaner
- Water-based
- Antistatic effect – to avoid dust inclusions on surfaces
- Non-aggressive cleaning detergent

AREA OF APPLICATION

- Perfect for cleaning tools or surfaces such as plastics, glass, existing paintwork
- Cleaning of spray guns (preliminary test recommended)
- Surface cleaning before painting processs (preliminary test recommended)

BENEFITS

- Cleaning of all surfaces
- Easy removal of dirt such as oil, grease, dust, salt and minerals
- Time saving application (surface cleaning and anstistatic effect)

APPLICATION ADVICE

We recommend checking the compatibility of the surface to be cleaned in all cases. 1K primers may need to be dissolved. Ensure sufficient flash-off time.

For industrial and professional use only.

ISO-VE 7030

Isopropanol cleaner



Art.-No.	Specification	SP	MOQ
154.034	5 l	1	1
157.345	20 l	1	1

DESCRIPTION

- Special cleaner
- Isopropanol-based

AREA OF APPLICATION

- Perfectly suitable for gentle cleaning of plastic, GRP or CRP surfaces
- Residue-free removal of release agents, dirt, grease, oil, silicone, as well as residual minerals and salts from the surface
- Antistatic

BENEFITS

- Antistatic
- Very volatile
- Extremely fast cleaning

APPLICATION ADVICE

Could etch 1K materials

For industrial and professional use only.

H₂O CLEANER

Cleaner



Art.-No.	Specification	SP	MOQ
151.953	5 l	1	4

DESCRIPTION

- Intensive cleaner
- Water-based

AREA OF APPLICATION

- Efficient cleaning of tools and parts in the body shop
- Perfect for paint stripping from panel stands

BENEFITS

- Removes water-based and solvent-based paints, 2K primers and epoxy resin-based products
- Multiple times usage (pigments sediment on the bottom and can be strained off)
- Water-dilutable

APPLICATION ADVICE

Air nipples can start oxidating after a long time exposure. Aluminum nipples could corrode.



MULTI CLEANING WIPES

Cleaning wipes



Art.-No.	Specification	SP	MOQ
159.782	90 wipes / bucket	1	6

DESCRIPTION

- Multi cleaning wipes in a practical dispenser bucket
- With a double-sided surface, the wipe is ideal for use on both sides
- The one-sided abrasive rubbing bodies can remove heavy soiling, while the soft material is used for cleaning sensitive surfaces

AREA OF APPLICATION

- Universal cleaning wipes for all surfaces, objects and for hand cleaning.

BENEFITS

- Solvent-, lint- and silicone-free
- Free from allergenic ingredients
- Ideal for all common cleaning tasks

APPLICATION ADVICE

The cloths can be removed per piece through perforation. The rough side of the cloth is ideal for heavy soiling, while the soft side is used for delicate surfaces and hand cleaning.



For industrial and professional use only.

PUMP SPRAYER

Pump Sprayer



Art.-No.	Specification	SP	MOQ
157.412	White / 1 l	1	60
142.808	Translucent / 1 l	1	60
139.606	Replacement viton sealing set	1	1
146.680	Spare nozzle	1	1
153.269	Replacement viton sealing spray head	1	1

DESCRIPTION

- Pump spray bottle
- Content: Max. 0,9 l

AREA OF APPLICATION

- Application and atomisation of liquids out of buckets or barrels
- Suitable for Carsystem Silicone Remover Mild, Silicone Remover Water and ISO-VE 7030

BENEFITS

- Adjustable atomisation

APPLICATION ADVICE

Strong solvents can damage the seals.

For industrial and professional use only.

CODING CAPS

Colour code rings



Art.-No.	Specification	SP	MOQ
152.642	Coding caps set of 5 pcs.	1	1

DESCRIPTION

- Plastic colour code rings

AREA OF APPLICATION

- Colour coding for Carsystem pump bottles

BENEFITS

- Pump bottles can be clearly distinguished

CAR CLEAN DOUBLE WHITE

Paper cleaning cloth



Art.-No.	Specification	SP	MOQ
141.253	1,500 tear-offs / 38 x 24 cm	2	2

DESCRIPTION

- Paper cleaning cloth 2-layers
- Perforated roll
- 1,500 tear-offs

AREA OF APPLICATION

- For all standard cleaning works

For industrial and professional use only.



SPRAYGUN CLEANER

Spraygun cleaner



Art.-No.	Specification	SP	MOQ
158.627	400 ml	1	12

DESCRIPTION

- Solvent-based paint spray gun cleaner

AREA OF APPLICATION

- Cleaning of paint spray guns
- Removal of contamination from water- and solvent-based paints

BENEFITS

- Easy and thorough cleaning
- Enormous time saving
- Cost-effective alternative to the spray gun cleaning machine

COCKPIT-SPRAY

Cleaning spray



Art.-No.	Specification	SP	MOQ
126.020	transparent / 400 ml	1	12

DESCRIPTION

- Care and cleaning spray
- Free of silicones
- Odour: Citrus
- Colour: Transparent

AREA OF APPLICATION

- All interior plastic and rubber surfaces

BENEFITS

- Antistatic

APPLICATION ADVICE

Avoid application on steering wheel, gear handle and foot pedals.

For industrial and professional use only.

CAR CLEAN MULTI EXTREME BOX

Cellulose cleaning cloth



Art.-No.	Specification	SP	MOQ
142.765	Box à 250 pcs. / 30 x 38 cm	1	1

DESCRIPTION

- Special cellulose cleaning cloth
- Residue-free cleaning and degreasing
- Dispenser box: 250 tear-offs – 30 x 38 cm
- Colour: Turquoise

AREA OF APPLICATION

- Universal cleaning cloth for all cleaning works
- Suitable for surfaces as: painted, metal and smooth wood surfaces

BENEFITS

- Sheets in a handy dispenser box
- Highly absorbent
- Good solvent resistance
- Lint-free and non-scratch
- Extremely tear-resistant
- Without silicones, binders, fillers or other chemical additives

For industrial and professional use only.

CAR CLEAN MULTI

Cleaning cloth



Art.-No.	Specification	SP	MOQ
134.577	500 tear-offs / 35 x 32 cm	1	1

DESCRIPTION

- Very absorbent, robust, and high-quality solvent-resistant cleaning cloth
- Residue-free cleaning and degreasing
- Perforated roll

AREA OF APPLICATION

- Absorbs large volumes of solvents, oil and lubricants
- Suitable for painted, metal, and smooth wood surfaces

BENEFITS

- Highly absorbent
- Good solvent resistance
- Lint-free and residue-free
- Tear-resistant
- Without silicones, binders, fillers or other chemical additives

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

CAR CLEAN MULTI II

Cleaning cloth



Art.-No.	Specification	SP	MOQ
160.515		1	1

DESCRIPTION

- Very absorbent, robust, and high-quality solvent-resistant cleaning cloth
- Residue-free cleaning and degreasing
- Perforated roll

AREA OF APPLICATION

- Absorbs large volumes of solvents, oil and lubricants
- Suitable for painted, metal, and smooth wood surfaces

BENEFITS

- Highly absorbent
- Good solvent resistance
- Lint-free and residue-free
- Tear-resistant
- Without silicones, binders, fillers or other chemical additives

CAR CLEAN TRIPLE BLUE

Paper cleaning cloth



Art.-No.	Specification	SP	MOQ
134.578	500 tear-offs / 36×36 cm	2	2
134.579	1,000 tear-offs / 36×36 cm	1	1

DESCRIPTION

- Paper cleaning cloth
- 3 layers
- Perforated roll
- All layers are fully bonded

AREA OF APPLICATION

- For all standard cleaning works

CAR CLEAN DOUBLE BLUE

Paper cleaning cloth



Art.-No.	Specification	SP	MOQ
134.580	1,000 tear-offs / 36×36 cm	2	2

DESCRIPTION

- Paper cleaning cloth
- 2 layers
- Perforated roll
- Layers are fully bonded

AREA OF APPLICATION

- For all standard cleaning works

CLEANING WIPES

Cleaning wipes



Art.-No.	Specification	SP	MOQ
156.458	cleaning wipes roll / 475 tear-offs / 38×30 cm	1	1

DESCRIPTION

- Special cleaning wipes
- Dispenser roll
- Perforated tear-offs
- Fine multiholes

AREA OF APPLICATION

- Universal soft cleaning cloth for all cleaning works

BENEFITS

- Extremely absorbent
- Solvent-resistant
- Lint-free cleaning
- Ultra soft
- Cleans also in deepest structures
- Extremely tear-resistant, even when wet
- Washable and reusable

STAUB STOP WATER BLACK

Tack cloth



Art.-No.	Specification	SP	MOQ
158.033	10 pcs. / black / 32×40 cm	10	180

DESCRIPTION

- Tack cloth
- Non-woven with hot melt-impregnation
- Silicone & lint free

AREA OF APPLICATION

- Removal of dust
- Especially for cleaning the base coat prior to the clear coat application
- Removal of small and medium dust particles in the industry

BENEFITS

- The black, non-woven tack cloth offers very good visual control of contaminated areas on the surface
- Resealable packaging
- Leaves no adhesive residues on the cleaned surface
- Acrylic binder for better durability and abrasion resistance without fiber loss
- Retains twice as much dust than traditional tack cloths

STAUB STOP WATER

Tack cloth



Art.-No.	Specification	SP	MOQ
144.538	10 pcs.	10	150

DESCRIPTION

- Tack cloth
- Micro fiber fabric
- Water-soluble impregnation
- Free of silicones

AREA OF APPLICATION

- Absorption of dust
- Especially for cleaning the base coat prior to the clear coat application

BENEFITS

- No tacky residues
- Leaves no adhesive residues on the cleaned surface

STAUB STOP

Tack cloth



Art.-No.	Specification	SP	MOQ
132.615	1 unit	1	500
132.616	5 units (pack)	1	100

DESCRIPTION

- Tack cloth
- Rayon fabric
- Slightly sticky surface
- Free of silicones

AREA OF APPLICATION

- Dust removal prior to painting

BENEFITS

- Very good dust removal
- Does not dry out

For industrial and professional use only.

STAUB STOP SUPER WAVE

Tack cloth



Art.-No.	Specification	SP	MOQ
148.124	1 unit / 80×80 cm	1	50

DESCRIPTION

- Tack cloth
- Cotton-rayon mix in wave form
- Wave formed surface
- Free of silicones

AREA OF APPLICATION

- Removal of dust prior to painting


BENEFITS

- Wave form enlarges the absorption quantity
- Is able to hold incredible amounts of dust
- Wave form adapts to hand and surface

For industrial and professional use only.

NANO EASY CLEANER

Cleaning sponge



Art.-No.	Specification	SP	MOQ
143.383	Cleaning sponge	1	10

DESCRIPTION

- Cleaning sponge with nano coating

AREA OF APPLICATION

- Cleaning of glass, paint and plastics
- Suitable for windows, head lamps, mirrors and painted surfaces
- Do not use in conjunction with cleaning agents, cleaner can attack the nano coating

BENEFITS

- Special nano coating removes insects, overspray and dirt easily.

APPLICATION ADVICE

Only in combination with water. Added cleaning agents can damage the nano coating.

SQUEEZER

Squeezer sponge



Art.-No.	Specification	SP	MOQ
157.987	Squeezer sponge with CARSYSTEM branding	1	520

DESCRIPTION

- Soft swelling sponge
- Made of absorbent natural fibers

FINISH CLAY

Cleaning clay



Art.-No.	Specification	SP	MOQ
147.468	200 g	1	10

DESCRIPTION

- Cleaning clay

AREA OF APPLICATION

- Residue and scratch-free removal of overspray, flash rust, insects and tree gum from painted surfaces

BENEFITS

- No need for aggressive cleaning agents
- Remains wet and does not get brittle (store it in the box)

For industrial and professional use only.

SCRAPER

Paint off blade



Art.-No.	Specification	SP	MOQ
140.984	Scraper	1	200
140.985	Refill (100 Blades)	1	50

DESCRIPTION

- Paint off security blade

AREA OF APPLICATION

- Removal of overspray from glass surfaces

For industrial and professional use only.

GUN CLEAN SET

Gun cleaning set



Art.-No.	Specification	SP	MOQ
157.520	Set	1	50

DESCRIPTION

- Gun cleaning set
- 17 single items
- 6 different needles and 11 different brushes



PERSONAL SAFETY

FUNCTIONAL & PROTECTIVE EQUIPMENT FOR THE PAINTER

Perfectly equipped and well protected – CARSYSTEM offers you a wide range of products for occupational safety.

Whether respiratory protection products, protective gloves, comfortable painting suits or high-quality safety glasses made of polycarbonate, you will find the right protective clothing for your needs.

Also discover our skin-friendly hand cleaner, which removes stubborn dirt caused by paints, oil-based paints, resins or varnishes.



ERLKING LTD. 2-PIECE COVERALL

Protective Coverall



NEW

Art.-No.	Specification	SP	MOQ
160.663	Erlking Jacket / S	1	30
160.669	Erlking Pants / S	1	30
160.664	Erlking Jacket / M	1	30
160.670	Erlking Pants / M	1	30
160.665	Erlking Jacket / L	1	30
160.671	Erlking Pants / L	1	30
160.666	Erlking Jacket / XL	1	30
160.672	Erlking Pants / XL	1	30
160.667	Erlking Jacket / XXL	1	30
160.673	Erlking Pants / XXL	1	30
160.668	Erlking Jacket / 3XL	1	30
160.674	Erlking Pants / 3XL	1	30

DESCRIPTION

- Protective coverall of PPE Cat. I in limited “Erlking” design
- Jacket and pants can be ordered separately
- Pants with knee pad pockets
- Comfortable
- Very good fit
- Antistatic due to carbon fibres
- Silicone-free
- Dust- and lint-free

AREA OF APPLICATION

- Protects against low risks, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Limited design is a eye-catcher in every paint booth
- Individual size selection of jacket and pants
- Pants with knee pad pockets
- Many storage options on jacket
- Zip cover provides additional protection against overspray
- Antistatic coating (EN 1149-1:2006)



30 YEARS LTD. COVERALL JACKET

Protective coverall



Art.-No.	Specification	SP	MOQ
159.654	Coverall jacket / S	1	30
159.655	Coverall jacket / M	1	30
159.656	Coverall jacket / L	1	30
159.657	Coverall jacket / XL	1	30
159.658	Coverall jacket / XXL	1	30
159.659	Coverall jacket / 3XL	1	30

DESCRIPTION

- Protective coverall of PPE Cat. I in limited “Carsystem 30 Years Anniversary” design
- Jacket and pants can be ordered separately
- Comfortable
- Very good fit
- Antistatic due to carbon fibres
- Silicone-free
- Dust- and lint-free

AREA OF APPLICATION

- Protects against low risks, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Limited design is a eye-catcher in every paint booth
- Individual size selection of jacket and pants
- Many storage options on jacket
- Zip cover provides additional protection against overspray
- Antistatic coating (EN 1149-1:2006)

For industrial and professional use only.

CLASSIC COVERALL JACKET ANTHRACITE

Protective coverall



Art.-No.	Specification	SP	MOQ
159.194	Anthracite / XS	1	30
159.195	Anthracite / S	1	30
159.196	Anthracite / M	1	30
159.197	Anthracite / L	1	30
159.198	Anthracite / XL	1	30
159.199	Anthracite / XXL	1	30
159.200	Anthracite / 3XL	1	30

DESCRIPTION

- Protective coverall of PPE Cat. I
- Jacket and pants can be ordered separately
- Comfortable
- Very good fit
- Antistatic due to carbon fibres
- Silicone-free
- Dust- and lint-free

AREA OF APPLICATION

- Protects against low risks, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Individual size selection of jacket and pants
- Many storage options on jacket
- Zip cover provides additional protection against overspray
- Antistatic coating (EN 1149-1:2006)



CLASSIC COVERALL PANTS
KNEEPADFIT

Protective coverall pants – Kneepad pocket

NEW



Art.-No.	Specification	SP	MOQ
160.596	Anthracite / S	1	30
160.597	Anthracite / M	1	30
160.598	Anthracite / L	1	30
160.599	Anthracite / XL	1	30
160.600	Anthracite / XXL	1	30
160.601	Anthracite / 3XL	1	30

DESCRIPTION

- Protective coverall of PPE Cat. I
- Jacket and pants can be ordered separately
- Modified fit
- Knee pad pockets
- Antistatic due to carbon fibres
- Silicone-free
- Dust- and lint-free
- Washable up to 30 °C

AREA OF APPLICATION

- Protects against low risks, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Individual size selection of jacket and pants
- Many storage options on jacket and pants
- Knee pad pockets
- Zip cover provides additional protection against overspray
- Antistatic coating (EN 1149-1:2006)

For industrial and professional use only.

CLASSIC COVERALL PANTS

Protective coverall



Art.-No.	Specification	SP	MOQ
159.180	Anthracite / XS	1	30
159.181	Anthracite / S	1	30
159.182	Anthracite / M	1	30
159.183	Anthracite / L	1	30
159.184	Anthracite / XL	1	30
159.185	Anthracite / XXL	1	30
159.186	Anthracite / 3XL	1	30

DESCRIPTION

- Protective coverall of PPE Cat. I
- Jacket and pants can be ordered separately
- Comfortable
- Very good fit
- Antistatic due to carbon fibres
- Silicone-free
- Dust- and lint-free
- Washable up to 30 °C

AREA OF APPLICATION

- Protects against low risks, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Individual size selection of jacket and pants
- Many storage options on jacket and pants
- Zip cover provides additional protection against overspray
- Antistatic coating (EN 1149-1:2006)

For industrial and professional use only.

COVERALL BLACK SUIT

Protective coverall



Art.-No.	Specification	SP	MOQ
159.113	S	1	20
159.114	M	1	20
159.115	L	1	20
159.116	XL	1	20
159.117	XXL	1	20
159.118	3XL	1	20

DESCRIPTION

- Protective coverall
- 99 % nylon, 1 % carbon
- Washable up to 30 °C
- PPE Cat. I
- Silicone-free
- Dust- and lint-free

AREA OF APPLICATION

- Protects from unarmful chemicals, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Extremely breathable due to its special elastic birds eye fabric
- The knitted cuffs close wrists and ankles perfectly tight and offer a perfect comfort
- Elastic areas on the back and modern cut provide a perfect adaption to the body shape
- Antistatic coating (EN 1149-3:2004)



PAINT OVERALL BLUE

Protective overall



Art.-No.	Specification	SP	MOQ
139.232	S	1	50
139.233	M	1	50
138.472	L	1	50
138.473	XL	1	50
139.234	XXL	1	50
152.968	3XL	1	50

DESCRIPTION

- Protective overall
- Soft polyester fabric
- PPE-Cat. I

AREA OF APPLICATION

- Protects from unarmful chemicals, e. g. water-based paint or mild cleaners
- Protection against overspray

BENEFITS

- Antistatic coating (EN 1149-1:2006)
- Silicone-free
- Dust- and lint-free

COVERALL 2.0

Disposable-protective suit 2.0



Art.-No.	Specification	SP	MOQ
160.275	S	1	50
160.276	M	1	50
160.277	L	1	50
160.278	XL	1	50
160.279	2XL	1	50
160.280	3XL	1	50

DESCRIPTION

- Disposable protective overall
- Free of silicone and latex
- Dust- and lint-free
- PPE-Cat III, Type 5 + 6

AREA OF APPLICATION

- Ideal for working in paint booths
- Protects against overspray, solvents, water and harmful dust

BENEFITS

- Breathable
- Knitted cuffs close the open ends perfectly and offer additional comfort
- Silicone- and latex-free
- Dust- and lint-free
- Antistatic coating (EN 1149-5:2008)

APPLICATION ADVICE

We recommend changing the protective suit regularly to prevent lint build-up (especially on the breathable back area).

STAR MASK

Respirator



Art.-No.	Specification	SP	MOQ
141.143	M	1	12
141.145	L	1	12

DESCRIPTION

- Half mask with filters
- Exchangable filters and pre-filters
- Bayonet fixing on the filters
- Protection class FFA2 P2 R

AREA OF APPLICATION

- All common paint works

BENEFITS

- Perfect protection against dust, dirt, organic vapours of solvents
- Pre-filter for a longer lifetime of the filters

APPLICATION ADVICE

Attention to different regional legislations.

STAR MASK DISC

Filter frame



Art.-No.	Specification	SP	MOQ
144.310	Filter Holder	2	20

DESCRIPTION

- Frame for the Carsystem Star Mask Pre P2 R pre-filters

AREA OF APPLICATION

- The frame fixes the pre-filter on the charcoal filter

STAR MASK REFILL

Charcoal filter



Art.-No.	Specification	SP	MOQ
141.224	Protection class A2	2	60

DESCRIPTION

- Replacement filters for the Star Mask
- Charcoal filters-protection class A2

AREA OF APPLICATION

- Protects against dust, dirt and organic vapours

STAR MASK PRE P2 R

Pre-filters



Art.-No.	Specification	SP	MOQ
141.154	Protection class P2	10	100

DESCRIPTION

- Pre-filters for Star Mask Refill
- Protection class P2

AREA OF APPLICATION

- Protects against particles, e. g. dust, smoke and aerosols



STAR DUST 2.0 FFP2

Dust mask



NEW

Art.-No.	Specification	SP	MOQ
159.949	FFP2 – without valve	20	400

DESCRIPTION

- Dust mask / FFP mask
- Protection class FFP2 NR
- Certification: EN 149:2001+A1:2009 CE 0194
- Variable aluminium nose stripe for better fitting

AREA OF APPLICATION

- Protects against harmful oil- or water-based particles

BENEFITS

- Soft and gentle inner section
- Suitable in combination with safety glasses

APPLICATION ADVICE

We recommend to exchange the mask after every work shift.

STAR DUST 2.0 FFP3 WITH VALVE

Dust mask



NEW

Art.-No.	Specification	SP	MOQ
159.950	FFP3 – with valve	10	200

DESCRIPTION

- Dust mask / FFP mask
- Protection class FFP3 NR
- Certification: EN 149:2001+A1:2009 CE 0194
- Variable aluminium nose stripe for better fitting
- Exhaust valve

AREA OF APPLICATION

- Protects against harmful and carcinogenic oil- or water-based particles as well as against radioactive particles, airborne biological agents of risk groups 2 + 3 and enzymes

BENEFITS

- Soft and gentle inner section
- Adjustable, qualitative headbands for a comfortable fit
- Foam stripes around the nose
- Suitable in combination with safety glasses
- Exhaust valve reduces the heat accumulation inside the mask

APPLICATION ADVICE

We recommend to exchange the mask after every work shift.

For industrial and professional use only.

SAFETY LENS

Protective glasses



Art.-No.	Specification	SP	MOQ
140.955	Safety Lens	1	12

DESCRIPTION

- Safety glasses
- Polycarbonate glasses

APPLICATION ADVICE

Glasses can be cleaned with warm water and soap.

For industrial and professional use only.

UV GLASSES

UV-protective glasses



Art.-No.	Specification	SP	MOQ
154.263	UV glasses	1	12

DESCRIPTION

- UV-protective glasses
- Polycarbonate glasses

AREA OF APPLICATION

- Protects from UVA, UVB and UVC radiation

BENEFITS

- PVC nose piece for perfect fit
- Anti-slip pads
- Scratch-resistant, anti-fog glasses
- Suitable in combination with hearing protection

APPLICATION ADVICE

Glasses can be cleaned with warm water and soap.

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-
SEALING

CLEANING

PERSONAL
SAFETY

PAINTING
SUPPLIES

NITRIL HAND PREMIUM BLACK

Protection gloves



Art.-No.	Specification	SP	MOQ
156.623	S	100	1000
156.624	M	100	1000
154.347	L	100	1000
154.348	XL	100	1000

DESCRIPTION

- Nitril gloves
- 100 pieces in a dispenser box
- Free of silicones and powder

AREA OF APPLICATION

- Protects against dirt, paint and chemicals

BENEFITS

- Enhanced thickness
- Very elastic and tear-resistant
- Perfect fit and feel

APPLICATION ADVICE

Short time solvent-resistant. Touchscreen processing is possible.

LATEX HAND I PREMIUM

Protection gloves



Art.-No.	Specification	SP	MOQ
152.011	L	50	500
152.012	XL	50	500

DESCRIPTION

- Latex gloves
- 50 pieces in a dispenser box
- Powder-free
- Extra long cuff

AREA OF APPLICATION

- Perfect for fast gun cleaning
- Protects from light solvents and paints

BENEFITS

- Extra thick
- Perfect feel and touch when working with solvents and in wet / oily environments

NEOPREN HAND

Protection gloves



Art.-No.	Specification	SP	MOQ
140.939	L / pair	1	72
140.940	XL / pair	1	72
140.941	XXL / pair	1	72

DESCRIPTION

- Neoprene / Latex chemical protection gloves
- Length: 30 cm

AREA OF APPLICATION

- Perfect for handling slippery parts in moist, oily and greasy enviroments
- Protects against chemicals, acids, brines, mineral oils, greases and solvents

BENEFITS

- Perfect mixture between neoprene for chemical protection and latex for the flexibility and durability
- Palm and fingertips with honeycomb pattern for a better grip
- Good insulation against heat and cold

SUPER NITRIL HAND I

Protection gloves



Art.-No.	Specification	SP	MOQ
145.130	9 / pair	12	144
145.131	10 / pair	12	144

DESCRIPTION

- Chemical protection gloves
- Length: 30 cm
- Soft velour inner section
- Base layer: Nitril

AREA OF APPLICATION

- Perfect for handling slippery parts in moist, oily and greasy enviroments
- Protects against chemicals

BENEFITS

- Perfect feel and touch when working with solvents and in wet / oily environments
- Palm and fingertips with honeycomb pattern for better grip
- Good insulation against heat and cold



PREP HAND III

Work gloves



Art.-No.	Specification	SP	MOQ
145.132	9 / pair	12	288
145.133	10 / pair	12	288

DESCRIPTION

- Work gloves PU coated
- Palm and fingertips soft PU coated
- Base layer: Polyamide

AREA OF APPLICATION

- Perfect for assembly- and grinding work without the risk of cuts or exposure to chemicals / solvents

BENEFITS

- Extremely soft and flexible
- Breathable
- Safer grip with excellent fingertip touch
- Touch screen operation possible
- Abrasion resistance
- Perfect fit

PREP HAND II

Work gloves



Art.-No.	Specification	SP	MOQ
150.719	L	12	144
150.720	XL	12	144

DESCRIPTION

- Work gloves PU coated
- Palm and fingertips PU coated
- Base layer: Polyamide (Nylon)

AREA OF APPLICATION

- Perfect for assembly work without the risk of cuts or exposure to chemicals / solvents

BENEFITS

- Breathable
- Safer grip with excellent fingertip touch
- Abrasion resistance
- Comfortable fit

HAND CLEANER

Hand cleaner



Art.-No.	Specification	SP	MOQ
155.356	Bulk packing without pump / 3 L	1	6

DESCRIPTION

- Mild hand cleaner
- Usage during or after work
- Free of silicones
- Plant-based scrubs

AREA OF APPLICATION

- Removes even resistant dirt of greases and bitumen

BENEFITS

- Pleasant smell
- Free of solvents
- Biodegradable
- Smooth and comfortable feel due to a natural and skin-friendly oil
- Bulk packing with 3 l

PUMP FOR HAND CLEANER 3 L

Pump for Hand Cleaner classic



Art.-No.	Specification	SP	MOQ
155.359	Pump for Hand Cleaner 3 l	1	1

DESCRIPTION

- The Carsystem Pump is suitable for the Hand Cleaner and Hand Cleaner Extreme 3 l.

HAND CLEANER EXTREME

Hand cleaner



Art.-No.	Specification	SP	MOQ
155.348	Soft bottle without wall dispenser / 2 L	1	6
155.357	Bulk packing without pump / 3 L	1	6

DESCRIPTION

- Intensive hand cleaner
- Usage during or after work
- Free of silicones
- Plant-based scrubs

AREA OF APPLICATION

- Removes even resistant dirt of oil paint, oil paint and resins

BENEFITS

- Pleasant apple smell
- Free of solvents
- Biodegradable
- Smooth and comfortable feel due to a natural and skin-friendly oil
- Wall mount with 2 l soft bottle
- Bulk packing with 3 l

WALL DISPENSER FOR SOFT BOTTLE 2 L

Wall Dispenser



Art.-No.	Specification	SP	MOQ
155.350	Wall dispenser for Soft Bottle	1	1

DESCRIPTION

- Wall dispenser for Hand Cleaner extreme Soft Bottle

PAINTING SUPPLIES

HIGH-QUALITY PAINTING
ACCESSORIES FOR PERFECT
EQUIPMENT


To receive the perfect result of painting, it is important to use professional varnishes, machines, and the right accessories.

Carsystem offers a huge line of high quality products like UV lamps, paint stands, practical tools and flat strips.



PAINT TROLLEY FLEXI PLUS

Paint stand



Art.-No.	Specification	SP	MOQ
152.596	Paint trolley incl. extention	1	1

DESCRIPTION

- Mobile paint stand with 28x adjustable axle
- Extremely robust
- Six fixing arms
- Two additional bumper fixing arms
- Dimensions: 225 × 74 × 101 cm (l/w/h)
- Maximum load: 50 kg

AREA OF APPLICATION

- Holding different car parts e. g. hoods, doors, bumpers, fenders etc.

BENEFITS

- Extremely good quality
- Very high stability

PAINT TROLLEY

Paint stand



Art.-No.	Specification	SP	MOQ
154.253	Paint trolley incl. extention	1	1
138.848	Spare claws for paint trolley	1	1
138.849	Fixing arm	1	1

DESCRIPTION

- Mobile paint stand with 360° adjustable axle
- Four fixing arms
- Two additional bumper fixing arms
- Two hooks for storing of unused fixing arms
- Paint gun holder
- Dimensions: 225 × 88 × 95 cm (l/w/h)
- Maximum load: 50 kg

AREA OF APPLICATION

- Holding different car parts e. g. hoods, doors etc.

BUMPER STAND

Bumper paint stand



Art.-No.	Specification	SP	MOQ
159.413	Bumper paint stand	1	1
159.702	Fixing bar with grip pliers 190-193	1	20

DESCRIPTION

- For a huge variety of different bumpers
- Mobile on wheels
- Maximum load: 35 kg

AREA OF APPLICATION

- For assembly, sanding, painting or polishing of different bumpers

BENEFITS

- 30 seconds of set-up time / adjustment period
- Foldable flat
- Fast rotation and the possibility of locking in any position

MULTI STAND

Paint stand



Art.-No.	Specification	SP	MOQ
159.563	Paint trolley – multifunctional	1	1

DESCRIPTION

- Flexible and universally applicable rotary painting stand for body parts such as wings, doors, bonnets, boot lids, etc.
- Mobile on wheels
- Maximum load: 35 kg

AREA OF APPLICATION


- For painting and polishing, dent removal or assembly, for filling and sanding a wide range of body parts

BENEFITS

- 30 seconds of set-up time
- Quick turning of parts and stepless locking
- Space-saving and secure holding of the body parts
- Can befolded very flat for storage

X-STAND CLASSIC

Paint stand



Art.-No.	Specification		MOQ
137.349	50 – 100 cm	1	1

DESCRIPTION

- Height: 50 – 100 cm
- Maximum load: 50 kg

AREA OF APPLICATION

- Holding different car parts e. g. hoods, doors etc.

PAPER TROLLEY

Triple paper stand



Art.-No.	Specification		MOQ
138.862	Paper Trolley	1	1

DESCRIPTION

- Mobile paper stand for three different paper sizes (22, 60, 90 cm)
- Including adjustable holders for masking tape rolls which fix the tapes perfectly onto the paper edge
- Dimensions: 135 × 59 × 110 cm (l/w/h)

AREA OF APPLICATION

- For fast masking work in the paint shop

X-STAND TOP

Paint stand



Art.-No.	Specification		MOQ
138.851	50 – 125 cm	1	1
138.852	50 – 125 cm incl. extension	1	1

DESCRIPTION

- Height: 50 – 125 cm
- Maximum load: 120 kg
- Extension poles available in 55 cm

AREA OF APPLICATION

- Holding different car parts, e. g. hoods, doors etc.

PAPER TROLLEY 1500

Paper stand



Art.-No.	Specification		MOQ
139.101	150 cm	1	1

DESCRIPTION

- Mobile paper stand for rolls up to 150 cm

AREA OF APPLICATION

- For fast masking work in the paint shop

MMIR TROLLEY "BOX"

Masking film stand



Art.-No.	Specification		MOQ
151.514	MMIR Trolley Box	1	1

DESCRIPTION

- Mobile masking film stand for rolls in a box
- The film is unrolled directly from the box

AREA OF APPLICATION

- For fast masking work in the paint shop

MMIR TROLLEY

Masking film stand



Art.-No.	Specification		MOQ
125.737	MMIR Trolley	1	1

DESCRIPTION

- Mobile masking film stand for holding rolls without a box
- Dimensions: 106 × 44 × 92 cm (l/w/h)

AREA OF APPLICATION

- For fast masking work in the paint shop

CAR CLEAN TROLLEY

Cleaning paper stand



Art.-No.	Specification	SP	MOQ
139.912	Car Clean Trolley / Blue / 564 × 385 × 870 × 725 mm	1	1
139.913	Car Clean Wall Holder / 500 × 264 × 375 mm	1	1

DESCRIPTION

- Floor stand or wall holder for cleaning paper rolls with a width up to 40 cm incl. garbage bag holder

AREA OF APPLICATION

- For flexible cleaning jobs in the paint shop

BENEFITS

- Mobile stand dispenser for portable use
- Wall dispenser for fixed installation

COLOUR MATCH LAMP

Day light lamp



Art.-No.	Specification	SP	MOQ
155.614	Colour Match Lamp	1	12

DESCRIPTION

- Power: 5 Watt
- Battery: 3.7V 2.6 Ah Li-Ion
- Charging time: 4 hours
- Running time: 2.5 hours
- Light intensity:
- 1.Mode = 2,700K – 500 lumen CRI >96+
- 2.Mode = 4,500K – 500 lumen CRI >96+
- 3.Mode = 6,500K – 500 lumen CRI >96+
- Working temperature: -10 °C to +40 °C
- Weight: 310 g
- Dimensions: 190 × 56 × 29 mm
- Certification: IP65 | IK07

AREA OF APPLICATION

- LED Colour matching lamp

BENEFITS

- Battery-powered LED lamp for flexible use
- Adjustable magnetic stand for work on vertical application areas
- Choice between three different colour temperatures
- Extremely robust and resistant

UV SMART LAMP

UV hand lamp



Art.-No.	Specification	SP	MOQ
153.777	190x56x29 mm	1	12

DESCRIPTION

- Power: 5 Watt
- Battery: 3.7V 2.6 Ah Li-Ion
- Charging time: 4 hours
- Running time: 4.5 hours
- Working temperature: -10 °C to +40 °C
- Weight: 310 g
- Dimensions: 190 × 56 × 29 mm
- Certification: IP65 | IK07

AREA OF APPLICATION

- UV hand lamp for curing UV products for spot repair on a surface with a maximum diameter of 10 cm

BENEFITS

- Battery-operated UV hand lamp for flexible use
- Adjustable magnetic stand for working on vertical application areas
- Hook for space-saving storage

APPLICATION ADVICE

Always protect your eyes when using UV lamps. Wear Carsystem UV-protective glasses.

For industrial and professional use only.

BLOW OFF GUN

Blow off gun



Art.-No.	Specification	SP	MOQ
145.270	Blow Off Gun with sound absorption and nipple (EU)	1	5
145.271	Blow Off Gun with sound absorption and nipple (CH, NL)	1	5
145.272	Blow Off Gun with metal nozzle and nipple (EU)	1	5
145.273	Blow Off Gun with metal nozzle and nipple (CH, NL)	1	5

DESCRIPTION

- Ergonomic handle
- Maximum inlet pressure: 10 bar
- Temperature resistance: -15 °C to +70 °C

AREA OF APPLICATION

- For blowing off residual dust from all surfaces

BENEFITS

- Blow off gun with metal tip for precise cleaning of surfaces and cavities
- Blow off gun with noise reduction to ~ 77 db with a scratch preventing plastic nozzle

MAGNETIC FLAT STRIP

Flat strip



Art.-No.	Specification	SP	MOQ
137.214	4 x 55 cm	1	5

DESCRIPTION

- Flexible plastic strip

AREA OF APPLICATION

- Flat and magnetic adhesive plastic strip for sealing the masking film onto the car

For industrial and professional use only.

BLOW OFF STICK

Blow off stick



Art.-No.	Specification	SP	MOQ
154.123	Blow Off Pen Orion (EU)	1	150
154.124	Blow Off Pen ARO (CH, NL)	1	150

DESCRIPTION

- Noise reduction
- Chemical-resistant
- Air consumption: 450 l / min. at 10 bar
- Temperature resistance: -40 °C to +150 °C

AREA OF APPLICATION

- For blowing off residual dust from all surfaces

BENEFITS

- Rubber tip prevents from scratching the surface

MAGNETIC SANDING PROTECTION

Edge protection



Art.-No.	Specification	SP	MOQ
130.992	4 x 55 cm	1	5

DESCRIPTION

- Flexible plastic edge protection

AREA OF APPLICATION

- Magnetic edge protection avoids unwanted sanding on surrounding parts

For industrial and professional use only.

MAGNETIC GUN HOLDER PLUS

Paint gun holder



Art.-No.	Specification	SP	MOQ
159.969	Black rubberised holder	1	24

DESCRIPTION

- Magnetic paint gun holder

AREA OF APPLICATION

- Holder for paint guns
- Can be fixed on ferromagnetic surfaces

AIR HOSE

Air hose coil



Art.-No.	Specification	SP	MOQ
143.131	9 x 16 mm / 50 m length	50	50

DESCRIPTION

- Antistatic rubber air hose
- Size: 9 x 16 mm
- Length: 50 m
- Maximum air pressure: 12 bar
- Inner tube: Smooth EPDM black
- Outer tube: Smooth EPDM blue

AREA OF APPLICATION

- Air supply for spray guns and air driven tools

AIR HOSE

Air hose complete



Art.-No.	Specification	SP	MOQ
139.039	9 x 16 mm / 12.5 m length	1	1

DESCRIPTION

- Antistatic rubber air hose incl. nipple and safety coupling
- Size: 9 x 16 mm
- Length: 12.5 m
- Maximum air pressure: 12 bar
- Inner tube: Smooth EPDM black
- Outer tube: Smooth EPDM blue

AREA OF APPLICATION

- Air supply for spray guns and air driven tools

SAFETY COUPLING

Safety coupling with quick connector



Art.-No.	Specification	SP	MOQ
143.127	Ø 9 mm	1	1

DESCRIPTION

- Air safety coupling for quick connectors

MS COUPLING

MS Coupling



Art.-No.	Specification	SP	MOQ
139.036	Ø 9 mm	1	1

DESCRIPTION

- MS Coupling

NIPPEL

Nipple with outer thread



Art.-No.	Specification	SP	MOQ
139.033	1/4 "	1	10

DESCRIPTION

- Air supply nipple with conic, outer thread
- Teflon-coated

NIPPEL

Nipple with inner thread



Art.-No.	Specification	SP	MOQ
139.034	1/4 "	1	10

DESCRIPTION

- Air supply nipple with inner tread

NIPPEL

Nipple for quick connector



Art.-No.	Specification	SP	MOQ
143.129	Ø 9 mm	1	10

DESCRIPTION

- Air connection nipple for quick connectors

SHOP SEAT PRO

Workshop seat



Art.-No.	Specification	SP	MOQ
160.161	Shop Seat Pro	1	1

DESCRIPTION

- Sturdy and robust heavy-duty workshop stool
- Pneumatic height adjustment
- Comfortable seat, resistant to dirt and light chemicals
- 5-part, removable plastic trays
- 5 low-noise castors with ball bearings (wheels)
- Maximum load: 158 kg

AREA OF APPLICATION

- Comfortable Shop Seat in a modern Carsystem design for carrying out polishing and sanding work in an easy way

BENEFITS

- Easy to assemble
- 5-part storage shelf for storing tools and work utensils

WORKSHOP SEAT

Workshop seat



Art.-No.	Specification	SP	MOQ
149.427	Professional workshop seat	1	1

DESCRIPTION

- Hydraulic height adjustment
- The seat is resistant against chemicals and solvents
- Smooth seat cushion for easy cleaning
- Five rubber-protected wheels on ball bearings
- Maximum load: 150 kg

AREA OF APPLICATION

- Comfortable workshop seat in Carsystem design for all sanding and polishing works

BENEFITS

- Magnetic storage platform for tools and working materials

WORKSHOP BUCKET

10 l



Art.-No.	Specification		MOQ
139.442	Workshop bucket / 10 l	1	1

DESCRIPTION

- Capacity: 10 l

AREA OF APPLICATION

- Universal workshop bucket

For industrial and professional use only.

PAINT ARRESTOR II

Paint mist separator



Art.-No.	Specification	SP	MOQ
160.136	500 mm x 20 m 3"	1	1
160.137	500 mm x 91 m 3"	1	1
160.138	660 mm x 20 m 3"	1	1
160.139	760 mm x 20 m 3"	1	1
160.140	760 mm x 25 m 3"	1	1
160.141	760 mm x 91 m 3"	1	1
160.142	860 mm x 91 m 3"	1	1
160.143	1000 mm x 20 m 3"	1	1
160.144	1000 mm x 25 m 3"	1	1
160.145	1000 mm x 50 m 3"	1	1
160.146	1000 mm x 91 m 3"	1	1
160.147	1250 mm x 91 m 3"	1	1
160.148	1530 mm x 25 m 3"	1	1

DESCRIPTION

- Paint mist separator and paint filter for paint booths
- Glass fibre base with elastic fibre structure
- Temperature-resistant up to 120°C
- Thickness: 3 Inch (+/- 75 mm)

AREA OF APPLICATION

- Paint filter for paint booths
- Separation of paint mist

BENEFITS

- High performance filtering

For industrial and professional use only.

BOOTH MASK WHITE

Booth protection mask



Art.-No.	Specification	SP	MOQ
153.205	19 L	1	1

DESCRIPTION

- Booth protection mask
- Colour: White
- Water-based
- Forms a highly opaque, shiny film

AREA OF APPLICATION

- Protects the spray booth walls against overspray
- Perfectly suitable for paint booths which cannot be cleaned with water

BENEFITS

- Covers all existing paint residues
- Provides perfect light conditions
- Forms a high layer thickness
- Easy to remove

APPLICATION ADVICE

We recommend a nozzle size of 2.2 – 2.5 mm.

ABRASIVES

PUTTIES

MASKING

PAINTING

FINISH

BONDING-SEALING

CLEANING

PERSONAL SAFETY

PAINTING SUPPLIES

BOOTH MASK STICK

Booth protection mask



Art.-No.	Specification	SP	MOQ
149.338	5 L	1	4
149.339	20 L	1	1
149.340	25 L	1	1

DESCRIPTION

- Booth protection mask
- Colour: Transparent
- Water-based
- Provides a clear, tacky protection film

AREA OF APPLICATION

- Protects booth walls and lightings against overspray
- Perfectly suitable for booth walls
- Absorbs the overspray

BENEFITS

- Dust and lints stick on the tacky film
- Water soluble

APPLICATION ADVICE

We recommend a nozzle size of 1.8 – 2.2 mm.

BOOTH MASK

Booth protection mask



Art.-No.	Specification	SP	MOQ
149.358	5 L	1	4
149.359	20 L	1	1

DESCRIPTION

- Booth protection mask
- Colour: Transparent
- Water-based
- Provides a transparent-clear, tack-free protection film

AREA OF APPLICATION

- Protects booth walls and lightings against overspray
- Perfectly suitable for lightings and paint booths which cannot be cleaned with water

BENEFITS

- Clear-transparent
- Does not influence the light conditions
- Protects for 3 months or 150 paint cycles
- Forms a tack free film
- Can be washed off smooth surfaces with water
- Can be removed from rough surfaces with a high-pressure cleaner

APPLICATION ADVICE

We recommend a nozzle size of 1.8 – 2.2 mm.

For industrial and professional use only.

RUPES VACUUM CLEANER S145

Vacuum cleaner



Art.-No.	Specification	SP	MOQ
157.343	S145L Profi Vacuum Cleaner	1	1
157.344	S145PL Profi Vacuum Cleaner	1	1
157.471	S145EM Vacuum cleaner	1	1
157.472	S145EPM Vacuum cleaner	1	1
157.560	Dust bag S Serie pack of 5	1	1

DESCRIPTION

- Movable vacuum cleaner with 5 m hose
- Tank volume: 45 L
- Air flow: 3,400 L/min.
- Noise level: 67 dB (A)
- Power: 1,200 W
- Max. Power: 2,400 W

RUPES CARRIER

Carrier for polishes and abrasives



Art.-No.	Specification	SP	MOQ
157.342	Carrier	1	1

DESCRIPTION

- Workshop carrier for polishes and abrasives
- 3 Systainer with drawers
- Storage compartment with additional suspension for polishing machines
- Power connection for electric tools
- Impact and shock resistant plastic

For industrial and professional use only.

RUPES WORKSHOP CARRIER KC28

Workshop carrier



Art.-No.	Specification	SP	MOQ
157.341	KC28	1	1
157.469	Peg board 016.1110/c for KC28	1	1

DESCRIPTION

- Workshop carrier for vacuum cleaners
- 2 Tool holder
- 2 holders for suction hoses
- 2 rotating front castors with brakes
- Storage compartment, lockable with key
- Working surface with large multipurpose box
- Ergonomic handle

EXPERIENCE. INTERNATIONAL INNOVATION. QUALITY.

AMERICA

Barbados
Canada
USA

SOUTH AMERICA

Chile
Colombia
Costa Rica

AFRICA

Senegal
South Africa

EUROPE

CARSYSTEM Headquarters
Germany
Albania
Austria
Belarus
Belgium
Bosnia-Herzegovina
Bulgaria
Croatia
Czech Republic

Denmark
Estonia
Finland
France
Greece
Hungary
Iceland
Ireland
Italy
Kosovo

Luxemburg
Macedonia
Montenegro
Netherlands
North Macedonia
Norway
Poland
Portugal
Romania
Russia

Serbia
Slovakia
Slovenia
Spain
Sweden
Switzerland
Turkey
United Kingdom

AUSTRALIA


Australia
New Zealand

MIDDLE EAST

Bahrain
Irak
Israel
Kuwait
Qatar
United Arab Emirates

ASIA

Armenia
China
Hong Kong
India
Japan
Kazakhstan
Singapore
South Korea
Taiwan
Thailand



EXPERIENCE.
INNOVATION.
QUALITY.

QUICKFINDER

1

1K Easy Filler	113
1K Easy Primer	112
1K Epoxy Primer	112
1K NC Filler	69

2

2K Carbo Clear Plus	92
2K Carbo Filler Transparent 1,0	103
2K Clear VOC CC.25 HS-AS	94
2K CLEAR VOC CC.26 ECO-X 15/60	95
2K Clear VOC Matt	96
2K Clear VOC Speed Plus	92
2K Epoxy Fill Primer	109
2K Filler Air Plus	100
2K Filler Vario Plus	101
2K High-Speed Klarlack	104
2K VOC Filler 540	100

3

30 Years Ltd. Coverall Jacket	185
-------------------------------	-----

A

Acryl Thinner	97
Activator	96
Adapter for CPS paint cup systems	118
AF.21 1K Filler	99
AF.21 X-pert	99
AF.25 Primer Wet on Wet	102
Air hose	204
All In One Covers	88

Alu Spezial	60
Aluminium mesh	71
Anti Rust Putty	62
Applicator	154
Auto Mask	85

B

Black Tape	81
Blacky	72
Blow Off Gun	203
Blow Off Stick	203
Booth Mask	208
Booth Mask Stick	208
Booth Mask White	207
BPO Hardener	69
Brush Set	123
Bumper Paint	115
Bumper Paint Spray	114
Bumper Stand	199
Bumper Structurant Spray	114

C

C-Wax C-80	128
Can Scraper	121
Car Clean Double Blue	176
Car Clean Double White	173
Car Clean Multi	175
Car Clean Multi Extreme Box	175
Car Clean Multi II	176
Car Clean Triple Blue	176
Car Clean Trolley	201
Car Mop White	138
Car Polish Roll	142
Carbo Putty	66
Carbo Spray	66
Carbo Spray Thinner	67
CC.20 X-pert	93
CC.21 X-press FIVE	93

Classic Coverall Jacket Anthracite	185
Classic Coverall Pants	187
Classic Coverall Pants KneePadFit	186
Classicline Soft Pad	24
Cleaning wipes	177
Clear Coat Spray	105
Cockpit-Spray	174
Coding Caps	173
Color Match Card Paper	122
Colour Match Lamp	202
Compound X1500	131
Control-Spray	43
Cordless Sander CSH-COS01	146
Coverall 2.0	188
Coverall Black Suit	187
Crash Film	86

D

Dispenser bottle incl. Cap	129
Dispenser for paint strainers	120
Dispenser Multi-Mix	119
Double Sanding Soft Pad	23
Dry Coat 2.0	42
Dualmatic	75
Dust Needle	123

E

Easy Clean Box	73
Easy Mask II	83
EF.21 EP-Filler	98
Elastic beige	61
Elastic white	61
Erlking Ltd. 2-Piece Coverall	184
Etch Primer	110
Excenter Back Pad Multi M	30
Excenter Back Pad T.19	30
Excenter Classic	45

PRODUCT CATALOGUE 2026/27

F

Faser	64
Fill putty	70
Fine Block	41
Fine Line Tape Blue	80
Fine putty	71
Finish Back Pad	143
Finish Back Pad M-14	143
Finish Clay	180
Finish Control Foam C-99	139
Finish Foam Black AH	135
Finish Foam Orange	135
Finish Foam White AH	135
Finish Quadra Pad C-10	134
Finish Sander Back Pad	31
Finish Sander RC 9332	46
Finish Sandwich Pad C-30	134
Finish Waffle Foam Black AH	137
Finish Waffle Pad Orange	138
Flex	65
Foam Tape	88
Foam Tape T-Soft	87

G

Glas	63
Glas White	63
Glass fibre mat	71
Glass fibre reinforced putty	70
Grip To Stick Interface Pad	29
Gun Clean Set	181

H

Hand Cleaner	195
Hand Cleaner extreme	195
High Gloss Additive	97

HpP Primer	103
HS-Acryl Tape	162
H ₂ O Cleaner	171

I

Interface Pad	32
ISO-VE 7030	171

J

Japanese Putty Knife	72
----------------------	----

K

KS-100	155
KS-1000	160
KS-1050	160
KS-200	156
KS-250	156
KS-300.2	157
KS-3000 Plus	161
KS-400	157
KS-4000.2	161
KS-50.2	155
KS-500.2	158
KS-550	158
KS-800	159
KS-850	159
KS-Brush	165
KS-Dual Gun	167
KS-Gun	166

CARSYSTEM

L

Lamb Wool Pad Gold S	136
Lamb Wool Pad White S Edge	136
Latex Hand I Premium	192
Liquid Masking	89
Liquid Putty	62

M

Magnetic Flat Strip	203
Magnetic Gun Holder Plus	204
Magnetic Sanding Protection	203
Masking film blue	84
Masking film green	85
Masking film yellow	84
Masking Paper Master II	82
Masking Paper Top II	82
Master Tape Green	78
Master Tape II	78
Metallic	59
Micro Fiber Cloth	140 - 142
Micro Tip	122
Microfiber X300 Duo	133
Mini Back Pad	31
Mini Sanding Machine RC 9330	148
Mixing Stick Black	120
Mixing Stick Fast	120
MMIR Knife Premium	85
MMIR Trolley	201
MMIR Trolley "Box"	201
Mount Tape	162
MS Air Gun	167
MS Coupling	205
Multi	56
Multi Black Rapid	50
Multi Blue Rapid Changer SF	50
Multi Cleaning wipes	172
Multi Flow	53
Multi Green	51
Multi Green Changer	55

Multi Green Glas	55
Multi Green Glas Light	56
Multi Green Plus 1.0 Super Light	51
Multi Green Rapid	54
Multi Green SF	54
Multi Light	57
Multi Plus	58
Multi Silver Light	57
Multi Soft	58
Multi Stand	199
Multi Strain	119
Multi Super Flex	64
Multi-Mix Bucket	121
Multi-Mix Cup	118
Multi-Mix Lids	119

Nano Carnauba Wax	129
Nano Easy Cleaner	179
Neopren Hand	193
Nippel	205
Nitril Hand Premium black	192

Orbital Sander CSH-CMS01 kit	145
------------------------------	-----

Pad Saver	35
Paint Arrestor II	207
Paint Overall Blue	188
Paint Planer	42
Paint Strainer	119
Paint System CPS 3.0	117
Paint Trolley	198
Paint Trolley Flexi Plus	198

Paper Trolley	200
Paper Trolley 1500	200
PDC Easy Paint	88
PG - FG Fine Filter	123
Plastic Can Empty	121
Plastic Primer	113
Plastic Pro	65
Plastic spreader	73
Polish C-05 cut	126
Polish C-07 cut	126
Polish C-10 strong	127
Polish C-30 finish	127
Polish Foam Green	134
Polish Foam White SC	135
Polish Foam Yellow	134
Polish Waffle Foam Yellow	138
Polish X8000	131

Polishing Pad X1500	132
Polishing Pad X8000	132
Polishing Back Pad	143
Polishing Machine RC 166	148
Polyester Repair Resin	69
Polyester Repair Set	69
Power PU Bond	163
Power PU Bond Film	164
Power PU Bond Gun	164
Power PU Bond Mixer	163
Prefill-Spray	115
Prefill-Spray Water	116
Prep & Scuff	44
Prep Hand II	194
Prep Hand III	194
Prep-Brush	44
Primer Spray	110
Primer Surfacing Spray	109
ProFLEX Back Pad PSA	31
ProFLEX Callisto	16 + 17
ProFLEX Hydra	15 + 16
ProFLEX Interface Pad	34 + 35
ProFLEX Interface Pad Finish	33
ProFLEX Jupiter	12 - 14
ProFLEX Jupiter Soft	13
ProFLEX Jupiter Soft H ₂ O	14 + 15
ProFLEX Mercury	26
ProFLEX Mercury Sanding Block	41

ProFLEX Neptune	25
ProFLEX Neptune Pad MaxGrip	35
ProFLEX Neptune Soft	25
ProFLEX Pluto	26
ProFLEX Pluto Sanding Block	40
ProFLEX Styx	27
Protective Film SPF	87
Pump for Hand Cleaner 3 l	195
Pump Sprayer	173
Putty dispenser	75
Putty Knife	72
Putty Mix Board	73

Rallye-Spray gloss	107
Rallye-Spray matt	107
Rallye-Spray Premium	106
Rapid Charger for CSH-battery-powered	147
Red Tape	79
Refinish 1	128
Refinish Restorer	139
Replacement Spray Head	116
Rotary Polisher CSH-CRP01 Kit	144
Rubber Spreader Set	72
RUPES Angle Polishing Machine LH76P	149
RUPES Back Pad	31
RUPES Carrier	209
RUPES Cleaning and maintenance oil	149
RUPES Ibrid Nano	47
RUPES Ibrid Nano Q-MAQ	47
RUPES Mini Polishing Machine HLR75STB	149
RUPES Orbital Sander RE21ALN	46
RUPES Orbital Sander SL42AES	45
RUPES Orbital Sander SLP41A	46
RUPES Polish Pad	137
RUPES Polishing Machine LH19E	148
RUPES Polishing Machine LHR15	148
RUPES Random Orbital Sander RA75	46
RUPES Skorpion E RX	45
RUPES Skorpion III RH	45
RUPES Vacuum Cleaner S145	209
RUPES Workshop Carrier KC28	209

Safety Coupling	204
Safety Lens	191
Sanding Block 100 2.0	39
Sanding Block 198 2.0	38
Sanding Block 198 Kit	38
Sanding Block 300 + 100	37
Sanding Block 400 2.0	36
Sanding Block 400 Grip Flex	36
Sanding Block Disc Kit 150	39
Sanding Block Grip	39
Sanding Block Grip Box	39
Sanding Block Hard	40
Sanding Disc F.19	8 + 11
Sanding Disc F.19 Finish	9 + 11
Sanding Disc F.19 Soft	9
Sanding Disc F.23 Ceramic	8
Sanding Disc P.25 Ceramic	10
Sanding Fleece V.19	20 + 21
Sanding Strips F.23 Ceramic	19
Sanding Strips P.25 Ceramic	18
Sanding Water SW20	29
Scraper	181
Shop Seat Pro	206
Silicone Remover Mild	170
Silicone Remover Water 2.0	170
Silver Tape	81
Silver Wheel	108
Slim Tape	78
Slim Tape Green	80
Soft	59
Soft Interface Pad	32
Soft-Roll	23
Sound Deadening Panels	163
Spare Battery 5,0Ah	147
Speedmixer 10 kg	74
Speedmixer 3 kg	74
Spotblender	98
Spotblender Spray	105
Spray	67
Spray Filler Spray	111
Spray Out Cards Metal	121

Spray Plus	68
Spray Thinner	68
Spraygun cleaner	174
Squeezer	180
Star Dust 2.0 FFP2	190
Star Dust 2.0 FFP3 with Valve	190
Star Mask	189
Star Mask Disc	189
Star Mask Pre P2 R	189
Star Mask Refill	189
Staub Stop	178
Staub Stop Super Wave	179
Staub Stop Water	178
Staub Stop Water Black	177
Steel	60
Stripping Disc	28
Super Nitril Hand I	193

Tape Off Disc Premium	28
Tape Off Tool	47
Tec Line Matt Matting Mousse	43
Tec Line Mattflex Pad	22
Tec Line Mattflex Premium	21
Tec Line N20	19
Tec Line Pro Finish	18
Tec Line Softflex	22
Tec Line Stick	89
Thermo-Spray	108
Tinting paste filler	101
Top Tape	78
Topline Soft Pad	24
Topline WP S	27
Touch Up	122

UNIFLEX Adapter Nozzle	164 + 165
UNIFLEX Air Gun	165

UNIFLEX Glas	153
UNIFLEX Glas Fast-Primer	154
UNIFLEX Glas HM	153
UNIFLEX Gun	165
UNIFLEX MS	152
UNIFLEX Nozzle	164
UNIFLEX PU	152
UV Clear	104
UV Glasses	191
UV Smart Lamp	202

Wall dispenser for Soft Bottle 2 l	195
Wax Puck	138
Wheel Cover	88
WM Tape	82
Workshop Bucket	206
Workshop Seat	206
WR-Lifting Tape	81
WR-Lifting Tape Premium	81

X-Stand Classic	200
X-Stand Top	200

Zinc Spray	111
------------	-----



**EXPERIENCE.
INNOVATION.
QUALITY.**

CARSYSTEM HEADQUARTERS VOSSCHEMIE GmbH
Esinger Steinweg 50 | 25436 Uetersen / Germany

Tel.: +49 (0) 41 22 / 717-0 | Fax: +49 (0) 41 22 / 717-193
E-Mail: info@vosschemie.de

www.carsystem.org



Art.-Nr. 139.759